


NASA/TM-2013-217996  
NESC-RP-12-00867



# Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center

*Stephen J. Minute/NESC  
Langley Research Center, Hampton, Virginia*

## NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA scientific and technical information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Report Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA Programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.


- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include organizing and publishing research results, distributing specialized research announcements and feeds, providing information desk and personal search support, and enabling data exchange services.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at <http://www.sti.nasa.gov>
- E-mail your question to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
- Fax your question to the NASA STI Information Desk at 443-757-5803
- Phone the NASA STI Information Desk at 443-757-5802
- Write to:  
STI Information Desk  
NASA Center for AeroSpace Information  
7115 Standard Drive  
Hanover, MD 21076-1320

NASA/TM-2013-217996  
NESC-RP-12-00867



# Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center

*Stephen J. Minute/NESC  
Langley Research Center, Hampton, Virginia*

National Aeronautics and  
Space Administration

Langley Research Center  
Hampton, Virginia 23681-2199

---


May 2013

The use of trademarks or names of manufacturers in the report is for accurate reporting and does not constitute an official endorsement, either expressed or implied, of such products or manufacturers by the National Aeronautics and Space Administration.

Available from:


NASA Center for AeroSpace Information  
7115 Standard Drive  
Hanover, MD 21076-1320  
443-757-5802



|  |   |   |                        |
|--|---|---|------------------------|
|   | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review of the<br/>Kennedy Space Center Visitors Center Orbiter Atlantis Static<br/>Display</b> |   |   | Page #:<br>1 of 138    |

# **Structural Analysis Peer Review of the Kennedy Space Center Visitors Center Orbiter Atlantis Static Display**

**March 14, 2013**


|   |   |  |                        |
|---|---|--|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |  | Page #:<br>2 of 138    |

### Report Approval and Revision History

NOTE: This document was approved at the March 14, 2013, NRB. This document was submitted to the NESC Director on March 22, 2013, for configuration control.

|           |   |  |
|-----------|---|--|
| Approved: | <div style="text-align: center;"> <i>Original Signature on File</i><br/> <hr/> NESC Director </div> | <div style="text-align: center;"> 3/25/13<br/> <hr/> Date </div> |
|-----------|---|--|

| Version | Description of Revision | Office of Primary Responsibility                   | Effective Date |
|---------|-------------------------|--|----------------|
| 1.0     | Initial Release         | Mr. Stephen Minute,<br>NESC Chief Engineer,<br>KSC | 3/14/13        |

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>3 of 138    |


## Table of Contents

### Technical Assessment Report

|             |   |    |
|-------------|---|----|
| <b>1.0</b>  | <b>Notification and Authorization</b> .....                         | 4  |
| <b>2.0</b>  | <b>Signature Page</b> .....   | 5  |
| <b>3.0</b>  | <b>Team List</b> .....  | 6  |
| <b>4.0</b>  | <b>Executive Summary</b> .....                                      | 7  |
| <b>5.0</b>  | <b>Assessment Plan</b> .....  | 9  |
| <b>6.0</b>  | <b>Problem Description, Scope, Proposed Activities</b> .....        | 9  |
| <b>7.0</b>  | <b>Data Analysis</b> .....  | 10 |
|             | 7.1 Compliance of Attach Points for Thermal Expansion .....         | 10 |
|             | 7.2 Sufficient Control of the Load While On the Lifting Jacks ..... | 12 |
|             | 7.3 Payload Bay Door Support Beam Support Structure Strength .....  | 18 |
|             | 7.4 Payload Bay Door Opening Operations .....                       | 18 |
|             | 7.5 Miscellaneous .....   | 18 |
| <b>8.0</b>  | <b>Findings and NESC Recommendations</b> .....                      | 18 |
| <b>9.0</b>  | <b>Alternate Viewpoint</b> .....                                    | 19 |
| <b>10.0</b> | <b>Acronyms List</b> .....  | 19 |
| <b>11.0</b> | <b>References</b> .....   | 19 |
| <b>12.0</b> | <b>Appendices</b> .....   | 20 |

### List of Figures

|               |  |    |
|---------------|--|----|
| Figure 7.1-1. | Orbiter Attach Point Compliance (Weight and Reaction Loads) .....                      | 12 |
| Figure 7.2-1. | Free Body Diagram of Loads to the Support Structure .....                              | 13 |
| Figure 7.2-2. | Free Body Diagram of Loads to the Jacks .....  | 13 |
| Figure 7.2-3. | BRPH Drawing of Orbiter in Final Rotated Position with Loads Applied<br>to Jacks ..... | 14 |
| Figure 7.2-4. | Pathfinder Demonstration – Initial Lift .....  | 15 |
| Figure 7.2-5. | Pathfinder Demonstration – Rotation (aft view) .....                                   | 16 |
| Figure 7.2-6. | Pathfinder Demonstration – Rotation (side view) .....                                  | 17 |

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>4 of 138    |

## Technical Assessment Report


### 1.0 Notification and Authorization

Mr. Christopher Miller with the NASA Safety & Mission Assurance (S&MA) at the Kennedy Space Center (KSC), in conjunction with the KSC Education and External Relations Directorate, requested an independent peer review of the Orbiter Atlantis static display structural analysis for display at the KSC Visitors Center. The principal focus of the assessment was to review the engineering firm's structural analysis for lifting and aligning the orbiter and its static display configuration.

A NASA Engineering and Safety Center (NESC) initial evaluation was approved to proceed by the NESC Review Board (NRB) on March 22, 2012. Mr. Steve Minute, NESC Chief Engineer at KSC, was assigned to lead this assessment. A preliminary stakeholder summary was approved by the NRB on September 27, 2012.


The key stakeholders for this assessment are the KSC S&MA, KSC Education and External Relations Directorate, Shuttle Transition and Retirement (T&R) Project, and the NESC.



|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>6 of 138    |

### 3.0 Team List

| Name                          | Discipline                                   | Organization |
|-------------------------------|--|--------------|
| <b>Core Team</b>              |  |              |
| Steve Minute                  | NESC Lead                                    | KSC          |
| Kenny Elliott                 | NASA Deputy Discipline Expert for Structures | LaRC         |
| Curt Larsen                   | NASA Technical Fellow for Loads & Dynamics   | JSC          |
| Patricia Pahlavani            | MTSO Program Analyst                         | LaRC         |
| Ivatury Raju                  | NASA Technical Fellow for Structures         | LaRC         |
| Kevin Roscoe                  | Structures Discipline Expert                 | LaRC         |
| Mark Terrone                  | NESC Systems Engineer                        | KSC          |
| <b>Consultant</b>             |  |              |
| Dave Hamilton                 | Structures Discipline Expert                 | Consultant   |
| <b>Administrative Support</b> |  |              |
| Erin Moran                    | Technical Writer                             | LaRC/AMA     |

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>7 of 138    |

## 4.0 Executive Summary

Mr. Christopher Miller with the Kennedy Space Center (KSC) NASA Safety & Mission Assurance (S&MA) office requested the NASA Engineering and Safety Center's (NESC) technical support on March 15, 2012, to review and make recommendations on the structural analysis being performed for the Orbiter Atlantis static display at the KSC Visitor Center. The S&MA office requested the NESC to consider three parts to this review:

1. Final static display – minimal dynamic loads (i.e., indoors, no internal access).
2. Lifting and handling to get orbiter onto final stands – potential dynamic loads on orbiter and support stands.
3. Payload bay door support – Atlantis will be displayed with doors open.

The primary interfaces for NESC team during this review were with the KSC S&MA office and with the KSC Shuttle Transition & Retirement (T&R) Program via their KSC Engineering Project engineering representative. However, there were numerous telecons and meetings convened with participation from NESC, KSC S&MA, KSC Shuttle T&R, KSC Engineering, Delaware North Companies (DNC), BRPH Engineering, and United Space Alliance (USA).


Numerous drawings, analysis, design, and data packages were provided to the NESC team. Because this was a peer review of the engineering analysis, a formal independent NESC assessment was not performed due to time constraints. The NESC team reviewed the existing work with technical experts asking questions about methodology and assumptions, and performing hand and finite element calculations as deemed appropriate. The NESC questions and comments were exchanged directly with the cognizant engineers in a real-time and effective technical interchange.

Throughout the review there were comments and concerns that centered around four specific areas of the proposed design and process.

1. Compliance of attach points primarily for thermal expansion.
2. Sufficient control of the load while on the lifting jacks.
3. Payload bay door support beam support structure strength.
4. Payload bay door opening operations.

DNC, BRPH Engineering, and USA were responsive to the NESC team inquiries and took action to improve their analysis and design, where appropriate. Details of these technical exchanges are discussed in this report. Based on the data and information provided, the NESC team found the DNC, BRPH Engineering, and USA designs and analysis to be appropriate and acceptable.


One observation was noted during the review. In general, there was a lack of “procedures” that NASA engineers are accustomed to seeing, such as detailed documentation on how a structure

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>8 of 138    |

goes from one position to another, and how the load is transitioned from one support system to another. The contractor captured the general processes in the drawing system and drawing notes to convey the activities. To assess the activities involving structures and the orbiter without procedures, assumptions were made on the NESC team's part that the vendor would safely execute the activity as discussed.

However since the conclusion of the NESC peer review activities, the contractors demonstrated the lifting and rotation processes using an orbiter mass simulator. The NESC team contacted KSC S&MA office to confirm that no issues were encountered during the tests.



|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>9 of 138    |

## 5.0 Assessment Plan

Since this was a peer review, the assessment plan was waived.

## 6.0 Problem Description, Scope, Proposed Activities

Mr. Christopher Miller with the KSC S&MA office requested NESC technical support on March 15, 2012, to review and make recommendations on the structural analysis being performed for the Orbiter Atlantis static display at the KSC Visitor Center. In particular, Mr. Miller requested the NESC to consider three parts to the scope of this review and comment effort:

1. Orbiter final static display design and engineering analysis with the assumption that there would be minimal dynamic loads after the orbiter was in place (i.e., indoors – no wind loading, no internal access).
2. Lifting and handling processes to move the orbiter onto the final stands – potential dynamic loads on orbiter and support stands.
3. Process to open the payload bay doors and provide static support of the doors in the open position.<sup>1</sup>

The primary interfaces for the NESC team during this review were with the KSC S&MA office and with the KSC Shuttle T&R Program via their KSC Engineering Project engineering representative.


This peer review was an iterative process. Numerous drawings, analysis, design, and data packages were provided to the NESC team in different drops (See Reference Documents 1-10). The NESC held internal telecons to assess the engineering analysis and formulate questions and comments. In most instances, the NESC questions and comments were transmitted to Mr. John Dillon with the KSC S&MA office, who forwarded the questions to the appropriate responsible contractor personnel. Some of the responses were handled via e-mail but, in some cases, it was more appropriate to have telecons with cognizant Atlantis Display project personnel. The primary organizations included, as appropriate, the NESC, KSC S&MA, KSC Shuttle T&R, KSC Engineering, DNC, BRPH Engineering, and USA.

Because this was a peer review of the engineering analysis, the NESC team did not perform a formal independent modeling and analyses due to time constraints. The NESC reviewed the existing work with technical experts asking questions about methodology and assumptions, and performing hand and finite element calculations as deemed appropriate.

A stakeholder outbrief of the NESC team's activities was approved at the NESC Review Board on September 27, 2012 (Appendix A). It was subsequently shared with KSC S&MA, KSC

---

<sup>1</sup> Activity not performed. See Section 7.4.

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>10 of 138   |

T&R, and KSC Education & External Relations organizations in preparation for their readiness reviews.

## 7.0 Data Analysis

The review focused around several general areas of the proposed design and analysis process with comments and concerns on the first four areas.


1. Compliance of attach points for thermal expansion and dynamic loading (i.e., rotation).
2. Sufficient control of the load while on the lifting jacks.
3. Payload bay door support beam factors of safety (FoS).
4. Payload bay door opening operations.
5. Reaction loads for static display.
6. FoS.

DNC, BRPH Engineering, and USA were responsive to the NESC team inquiries and took appropriate action to modify and improve their analysis and design, where appropriate. Details of these items are discussed in more detail in the following sub-sections.

### 7.1 Compliance of Attach Points for Thermal Expansion

BRPH assessments (References 8 and 9) were provided to NASA as part of an ongoing process to show that the orbiter final display configuration was safe to construction personnel and the public, and would not damage the Orbiter Atlantis. A review of Reference (8) showed that the attachment points on the orbiter and the attachment hardware to be sufficient for the 43 degrees, port wing down roll display configuration. This sufficiency is contingent on the support structure/attachment hardware providing the adequate compliance, especially for thermal expansion. (See Figure 7.1-1 for the aircraft/orbiter (AO)-2 attach point.) The fore/aft direction should be compliant at the AO-1 forward support point, and the lateral direction should be compliant at the AO-2 aft port support point. Without these compliances, there is a risk to exceed the design loads in ICD-2-17001 Table 3.2.3-1.2 of Reference (1). A summary of the telecom to discuss this concern is included in Appendix B, Appendix H, items 1 and 2, and Appendix I, item 1. Comments, concerns, and questions are provided in Appendix C with subsequent responses from BRPH Engineering in Appendix D.

NESC Concern (Roscoe, August 17): The orbiter installation was to be performed in November and without environmental control (i.e., without the building's roof installed). Given a change in temperature event during installation or while on display, differential thermal expansion between the orbiter and the support structure drove the need for compliance between the two articles. The DNC calculations (Appendix E) predicted forces at the AO joints with perfectly compliant (i.e., zero stiffness) support structure. The DNC used Fluorogold<sup>®</sup> bearing elements to add

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>11 of 138   |


compliance. However, these bearings were not “perfectly” compliant. The non-zero compliant bearings would result in additional shear forces at the AO joints during thermal events. Also, the thermal events would have a zero relative velocity starting point at the Fluorogold<sup>®</sup> interface. The joint would tend to stick until sufficient shear force would overcome static friction.

BRPH Response (Paquette, August 20): “We have been looking at the concerns about differential thermal expansion between the Orbiter and the Orbiter Support frame and had the following response.


- a. According to the slide bearing manufacturers, the static coefficient of friction to break away is anywhere from nearly the same as the dynamic friction (0.07) to a maximum of 0.1. So at AO2 the maximum breaking frictional resistance  $Y_o = 93.1(0.1) = 9.31$  kips which we used in our calculations. To assure the 0.07 coefficient of friction in the short term, lubricants are used according to the bearing manufacturers, we are specifying them for the jacking and rotation. The coefficient of friction is also improved with bearing pressures above a minimum of 75 psi according to the slide bearing manufacturers - so for the slide bearings under the spacers, the bottom plate bearing surface was reduced where required to assure that the bearing pressures are above 75 psi for applicable Orbiter orientations. (The Orbiter when level was a controlling factor at the aft slide bearings.)
- b. We have also added high capacity slide bearings at the edges of the shear lugs at the spacers to reduce friction at AO3 and AO1 in the  $X_o$  direction from the  $Y_o$  loads and at AO2 in the  $Z_o$  direction and we have considered the breakaway friction at the edge slide bearings in our calculations as well.
- c. After rotation, the support frame between the Aft and Forward AO supports is intended to be removed, so differential thermal expansion of the Orbiter versus the horizontal support frame between the forward and aft Orbiter supports will not be applicable. The forward support frame is capable of deflecting because it is not braced in the  $X_o$  direction.
- d. We identified as much as 10.2 kips of uplift at AO3, which isn’t very much for all 8 bolts (1.5 inch diameter A325) in the spacer to resist. We have removed the torque requirements after jacking and rotation from the contact documents.
- e. We have analyzed and provided a table considering the Orbiter loads combined with friction developed on the slide bearings prior to movement and differential thermal expansion for cases that include in the level or rotated condition during jacking and rotation.”

#### Static Display Compliance Summary:

The NESC team assessed this item has been satisfactorily addressed, assuming compatibility of the lubricant and Fluorogold<sup>®</sup>, and believing 0.10 is the maximum coefficient of friction per the manufacturer. Both assumptions would rate as a low risk. The contractor team has sufficiently engineered the joint (e.g., contacted the manufacturer to estimate break-away friction, reduced

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>12 of 138   |


bearing area to increase pressure load to the minimum recommended, added slide bearings to the shear lugs, removed post-installation bolt torque, and calculated predicted max break-away shear loads due to thermal expansion). The contractor team could have (or may have) tried to determine the structural compliance between AO-2 and AO-3 for the small thermal expansion difference. However, the 16,300-lb limit may have been too low for the Support Frame. Either way the bearing solution works. Once a slide bearing was introduced under AO-1, the contractor team solved the biggest threat to the thermal expansion issue. Refer to in-depth question and response discussion in Appendix F.




***Figure 7.1-1. Orbiter Attach Point Compliance (Weight and Reaction Loads)***


## **7.2 Sufficient Control of the Load While On the Lifting Jacks**

The NESC team had an initial concern that the jacks will experience a moment as the orbiter is being rotated to final position i.e., 43 degrees, port wing down) (See Figures 7.2-1, 7.2-2, and 7.2-3, and Appendix G and Appendix H, items 3 and 4).


|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>13 of 138   |




**Figure 7.2-1. Free Body Diagram of Loads to the Support Structure**



**Figure 7.2-2. Free Body Diagram of Loads to the Jacks**

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>14 of 138   |



**Figure 7.2-3. BRPH Drawing of Orbiter in Final Rotated Position with Loads Applied to Jacks**


The following response was provided to the initial NESC team's comments and concerns via an email from Mr. Ken Paquette, BRPH to Mr. John Dillon, KSC-Safety & Mission Assurance Support Services (SMASS), dated July 10, 2012:

#### **Response to Atlantis-Pivot.xlsx Load Diagrams in Appendix G**

“Beyel Brothers has the bottom of the jacks stabilized by (propel) hydraulic cylinders that are attached to the jack alignment runway tracks. (See attachments – Propel Jack Cylinder.pdf and Lift Systems Jack Runway.pdf; Appendix J) The hydraulic cylinder allows controlled horizontal movement. Leveling systems are being used to keep the jack straight. The top of the jacks are attached to a hinged connection on the orbiter support beam. There are diagonal braces that extend from the aft jack locations on the orbiter support beam to spreader beams between the aft and forward supports for the orbiter. The rotation procedure will be performed slowly to allow for adjustment to keep the jacks vertical.”

BRPH Engineering and DNC provided jack stability analysis (Reference 10). However, during the telecon on July 27, 2012, the NESC team and DNC agreed that there was insufficient jack data to perform a thorough analysis. DNC agreed to develop a test fixture with an orbiter mass



|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>15 of 138   |


simulator to demonstrate capability and provide a pathfinder test for future processes. DNC modified their design to include load cells at the top of the jack. With the load cells, DNC were able to monitor jack side loads and improve the load control (Appendix I, item 2).

Subsequent to the peer review and stakeholder outbrief, DNC performed a pathfinder demonstration with an orbiter mass simulator. (Figures 7.2-4, 7.2-5, and 7.2-6) No issues were identified as a result of the test. The pathfinder test satisfied the concerns raised in this section.

BRPH Engineering incorporated bracing, sliding tracks for jacks, dunnage, and moved in 2-inch increments to control the load. (Figures 7.2-4, 7.2-5, and 7.2-6)




***Figure 7.2-4. Pathfinder Demonstration – Initial Lift***

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>16 of 138   |



***Figure 7.2-5. Pathfinder Demonstration – Rotation (aft view)***




|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>17 of 138   |



***Figure 7.2-6. Pathfinder Demonstration – Rotation (side view)***

Beyel Brothers completed the lift and rotation demonstration test at their Rigging and Heavy Equipment Yard on October 11, 2012. The test used a mass simulator and equivalent support structure to demonstrate the planned process for lifting and rotating the orbiter at the KSC Visitor Center display site. The contractor demonstrated a well-choreographed process using a combination of lifting jacks and support cribbing/dunnage to lift and rotate the orbiter to its final display configuration (i.e., 43 degrees, port wing down).

Dunnage was used to support the port side jacks, the frame at the 43-degree position, and the load in the event of a jack casualty (loss of hydraulics). The dunnage load capacity was based on an aligned stacking configuration (concentric pipes axis) per page 92 of Volume I, Reference 7. The aft port location had staggered dunnage where the pipes were not aligned and a load capacity rating was not defined. The NESC team performed an assessment of dunnage for this configuration (Appendix K) and found it to be sufficient for this application. No issues were identified from the NESC team.

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>18 of 138   |

### 7.3 Payload Bay Door Support Beam Support Structure Strength

The DNC/USA bolt calculation showed a FoS of 3 on yield and 5 on ultimate (see Appendices L, M, and N). However, the DNC/USA calculations were in error because they did not account for the prying/lever action of the two-piece support arm on the bolt. It was assumed all the cable load would go directly to the bolt. The NESC bolt force load estimation, assuming only one bolt was active out of the six, was 1,591 lbs, versus the DNC/USA value of 679 lbs (1,357/2) (see Appendices O, P, and Q). DNC/USA subsequently revised their analysis and agreed to improve the design by increasing the bolt strength to achieve a FoS of 5 (MP-35N 240KSI tensile strength versus 90-100 KSI for the original bolt).

No further concerns were generated from the NESC team.

### 7.4 Payload Bay Door Opening Operations

Initially, a review of the payload bay door opening operations was included in the initial NESC request. The engineering and operational expertise associated with payload bay door operations for the Space Shuttle Program resides with KSC Engineering, USA, KSC S&MA, and the Shuttle T&R personnel at KSC. It was agreed with all parties, including KSC Education and External Relations Directorate, that the NESC was not the appropriate organization to peer review those operations.


### 7.5 Miscellaneous

There were other items the NESC team reviewed. They were not significant items, but are included in this section for completeness. The NESC considers these items accepted and closed.

1. The DNC orbiter support frame with respect to the orbiter and the test fixture, including center of gravity measurements and checks of critical dimensions of the orbiter-to-shuttle carrier aircraft interfaces as found in the interface control document (ICD).
2. The shuttle documentation for the external tank (ET)-to-orbiter limit loads allowed during ascent flight. Those allowable loads were more severe than the ferry flight ICD limits used in designing the DNC static display structure. The demonstrated ascent loads reflect the true orbiter interface load capability and give additional comfort in accepting the loads to be imposed by the static display structure (Appendix R).

## 8.0 Findings and NESC Recommendations

Because of the iterative nature of this peer review there were no formal findings or NESC recommendations. All comments and concerns were addressed in real-time discussions and e-mail and captured as best as practical in this report. Based on the data and information provided, the NESC finds the DNC, BRPH Engineering, and USA design and analysis results to be appropriate and acceptable.

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>19 of 138   |

One observation was noted during this review and documented in the stakeholder outbrief (Appendix A). In general, there was a lack of “operational procedures” that NASA as an Agency are accustomed to, such as detailed documentation on how a structure goes from one position to another, and how the load is transitioned from one support system to another. The contractor captured the general processes in the drawing system and drawing notes to convey the activities. To assess the activities involving structures and the orbiter without procedures, assumptions were made on the NESC team’s part that the vendor would safely execute the activity as discussed. Subsequent to the peer review and stakeholder outbrief, DNC performed a pathfinder demonstration with an orbiter mass simulator (Figures 7.2-4, 7.2-5, and 7.2-6). No issues were identified to the NESC as a result of the test. The pathfinder satisfies the concerns raised in this observation.

## 9.0 Alternate Viewpoint


There were no alternate viewpoints identified during the course of this assessment by the NESC team or the NESC Review Board quorum.

## 10.0 Acronyms List

|       |   |
|-------|---|
| AO    | Aircraft/Orbiter                              |
| DNC   | Delaware North Companies                      |
| ET    | External Tank                                 |
| FoS   | Factor of Safety                              |
| ICD   | interface control document                    |
| KSC   | Kennedy Space Center                          |
| MTSO  | Management Technical Support Office           |
| NASA  | National Aeronautics and Space Administration |
| NESC  | NASA Engineering and Safety Center            |
| S&MA  | Safety & Mission Assurance                    |
| SMASS | Safety & Mission Assurance Support Services   |
| T&R   | Transition & Retirement                       |
| USA   | United Space Alliance                         |

## 11.0 References

1. Atlantis Loads Assessment, KSC Visitor Complex Analysis Report, Final Submittal, BRPH No. 5636.45, dated July 5, 2012 (pdf)
2. KSC Visitor Complex Atlantis Support Dwg., 60% Submittal, BRPH No. 5636.44, dated June 18, 2012 (pdf)
3. KSC Visitor Complex Atlantis Support Dwg., 90% Submittal, BRPH No. 79K39277, dated August 22, 2012 (pdf)


|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>20 of 138   |

4. Atlantis Support Orbiter Opening Doors, Pre-100% Submittal, BRPH 79K39277, dated September 12, 2012 (pdf)
5. KSC Visitor Complex Atlantis Support Dwg., 100% Submittal, BRPH No. 79K39277, dated September 19, 2012 (pdf)
6. Test Fixture Design, 100% Submittal, BRPH Drawing 6701.01, dated August 9, 2012 (pdf)
7. 100% Structural Calculations Volumes I & II, BRPH No. 5636.44, dated January 19, 2012 (pdf)
8. Atlantis Loads Assessment, KSC Visitor Complex Analysis Report, 90% Submittal, BRPH No. 5636.45, dated May 3, 2012 (pdf)
9. Atlantis Support Concept, KSC Visitor Complex, 100% Submittal, BRPH No. 5636.44, dated February 17, 2012 (pdf)
10. Orbiter Rotation Frame 7-9-2012.pdf (STAAD Analysis File) Propel Jack Cylinder.pdf (Jacks to be used for lift and Orbiter Rotation Frame 7-9-2012.pdf (STAAD Analysis File)

## 12.0 Appendices

- A. NESC Stakeholder Outbrief
- B. Atlantis\_Review-Executive\_Summary-060112[1].docx (Notes from Telecon held 6/1/2012)
- C. AtlantisLoadsAssess\_Comments.xlsx (K. Roscoe Comments from NESC Review of Reference Documents: Attachments D of Ref. 1, Ref. 8, and Ref. 9)
- D. AtlantisLoadsAssess\_Comments RBPH Response.pdf (Response to NESC comments in Appendix C - AtlantisLoadsAssess\_Comments.xlsx)
- E. Orbiter Loads 155K Xo = 159 On SCA Connections.pdf
- F. Email from K. Roscoe to S. Minute on 9/3/2012: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations
- G. Atlantis-Pivot.xlsx (K. Roscoe's Free Body Diagrams)
- H. AtlantisItemsFor072712meeting.docx (Discussion items for telecon held 7/27/2012)
- I. AtlantisReview072712-Summary.docx (Summary of telecon on 7/27/2012)
- J. Propel Jack Cylinder.pdf (jacks to be used for lift and rotation)
- K. Atlantis DunnageRevA.pptx (Assessment of dunnage to be used in lift and rotation procedure)
- L. PLBD Support-C.pdf
- M. G-Ops Support.pdf
- N. Mathcad - OV-104\_Door\_Support\_Analysis\_3.pdf
- O. PLBD Comments.pptx (K. Roscoe's assessment of PLBD analysis)
- P. PLBD Attach Beam calcs.xlsx (K. Roscoe's analysis)
- Q. AttachBeamBolts.xlsx (K. Roscoe's analysis)
- R. Email from C. Larsen to Minute, et. al. on September 5, 2012: Re: Atlantis Support Structure – Orbiter allowable loads.




|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>21 of 138   |


## Appendix A. NESC Stakeholder Outbrief

|   |  |                      |
|---|--|----------------------|
|  |  | Presenter: S. Minute |
|   |  | Date 9/27/2012       |

### Stakeholder Briefing: Atlantis Static Display Structural Analysis Review T-12-00768



Steve Minute  
September 27, 2012

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>22 of 138   |

|   |  |                      |
|---|--|----------------------|
|  | <h2 style="text-align: center;">Scope of Assessment</h2> | Presenter: S. Minute |
|   |  | Date 9/27/2012       |

An engineering firm is performing the structural analysis for the static display of Orbiter Atlantis at the KSC Visitor Center

Because of the significance and visibility of this national asset, S&MA wanted an independent peer review of the engineering analysis

NESC considered three parts to this review


- Final static display of Orbiter to support stands – minimal dynamic loads (i.e. indoors, no internal access)
- Lifting and handling to get orbiter onto final stands
- Assess payload bay door support and connection to support wires - Orbiter will be displayed with doors open (analysis of door structure not provided)
- Did not review the Payload Bay Door opening procedure and required GSE – KSC engineering better suited to review that operation

---

This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768

2

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>23 of 138   |

|   |                               |                      |
|---|-------------------------------|----------------------|
|  | <b>Peer Review Activities</b> | Presenter: S. Minute |
|   |                               | Date 9/27/2012       |


- Team Membership:
  - Steve Minute (NESC CE - KSC)
  - Ivatury Raju (NASA Tech Fellow – Structures)
  - Kevin Roscoe (NASA LaRC Discipline Expert – Structures & GSE)
  - Kenny Elliott (NASA LaRC Discipline Expert – Structures)
  - Curt Larsen (NASA Tech Fellow – Loads & Dynamics)
  - Dave Hamilton (Structural Engineering Consultant – JSC)
  - Mark Terrone (NESC Systems Engineer)
- NESC was requested to peer review the design in March, 2012.
- Over the course of the review period NESC was provided multiple design and analysis packages.
- Held 4 internal team meetings and 2 external meetings (with Delaware North, BRPH, NASA, S&MA, and USA)
- Upcoming - Rollout and Program Readiness Reviews

---

This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768


3


|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>24 of 138   |

|   |  |                      |
|---|--|----------------------|
|  | <h2 style="text-align: center;">Data Analysis</h2> | Presenter: S. Minute |
|   |  | Date 9/27/2012       |

- Data, Designs, and Drawings provided were reviewed.
- Because this was a peer review the NESC questions and comments were fed directly to the program and contractors for consideration.
- Four areas for further discussion/concern developed:
  1. Compliance of attach points for thermal expansion
  2. Sufficient lateral stiffness of the lifting jacks
  3. Payload Bay Door Support Beam Factor of Safety
  4. Payload Bay Door opening operations




|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>25 of 138   |

|   |                              |                      |
|---|------------------------------|----------------------|
|  | <b>Data Analysis (cont.)</b> | Presenter: S. Minute |
|   |                              | Date 9/27/2012       |

## 1. Compliance of attach points for thermal expansion


- BRPH has re-engineered their Flourogold® slide bearing design to better accommodate thermal issues as a result of NESC inquiries:
  - Contacted Flourogold® to estimate break-away friction
  - Reduced bearing area to increase pressure load to minimum recommended (overcomes static friction)
  - Removed post-installation bolt torque
  - Added slide bearings to side of shear lugs (effective when rotated)
  - Calculated predicted max break-away shear loads due to thermal expansion




This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768



5

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>26 of 138   |

|   |                              |                      |
|---|------------------------------|----------------------|
|  | <b>Data Analysis (cont.)</b> | Presenter: S. Minute |
|   |                              | Date 9/27/2012       |

## 2. Sufficient lateral stiffness of the lifting jacks


- Concern that jacks will experience a moment as the orbiter is being rotated to final position (starboard side 43 deg. down)
  - BRPH incorporating bracing, sliding tracks for jacks, and dunnage in 2" increments to control rotation.
  - Insufficient jack data to do analysis – but will demonstrate capability with testing (open work). Plan to use an orbiter mass simulator to perform pathfinder test.




This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768


6

|   |   |  |                        |
|---|---|--|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |  |                        |
|   |   |  | Page #:<br>27 of 138   |

|   |                              |                      |
|---|------------------------------|----------------------|
|  | <b>Data Analysis (cont.)</b> | Presenter: S. Minute |
|   |                              | Date 9/27/2012       |

### 3. Payload Bay Door (PLBD) Support Beam Factor of Safety (FoS)


- PLBD Support Beam design was based on FoS of 2
- NESC concerned with transition of PLBDs from existing GSE to support beam & cables.
  - Weight of GSE still attached; Strongbacks make doors semi-rigid
  - Planned method to transfer load to support cables via turnbuckles
  - Should consider Support beam and cables as lifting devices during transition (NASA Standard required FoS of 5)
- USA opted to use stronger bolts and improve their analysis resulting in FOS greater than 5.




This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768


7

|   |   |  |                        |
|---|---|--|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |  |                        |
|   |   | Page #:<br>28 of 138                   |                        |

|   |                              |                      |
|---|------------------------------|----------------------|
|  | <b>Data Analysis (cont.)</b> | Presenter: S. Minute |
|   |                              | Date 9/27/2012       |

#### 4. Payload Bay Door opening operations


- The NESC team did not have the expertise to assess the PLBD opening operation with modified orbiter GSE (C-hook, etc.)
- Communicated concern back to S&MA and program. NASA and USA Program personnel are reviewing those activities



This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768

8

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>29 of 138   |

|   |                                 |                      |
|---|---------------------------------|----------------------|
|  | <b>Findings/Recommendations</b> | Presenter: S. Minute |
|   |                                 | Date 9/27/2012       |

Based on the data and information provided to NESC we find the Delaware North, BRPH, and USA designs and analysis (as stated in the scope) to be appropriate and acceptable.

- The contractors responded to our NESC inquiries.
- Where appropriate, they improved their analysis and design

In general, there was a lack of “procedures” as we in NASA are accustomed to seeing, like detail on documenting how a structure goes from one position to another, and how the load is transitioned from one support system to another. The contractor captured the general processes in the drawing system and drawing notes to convey the activities. To assess the activities involving structures and the orbiter without procedures, assumptions were made on our part that the vendor would safely execute the activity as discussed. The planned lifting and rotation tests will be helpful in demonstrating the process.


***This was communicated to the Stakeholders***

This briefing is for status only and does not represent complete engineering data analysis

NESC Document No: NESC-PSS-12-00768

9



|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>30 of 138   |

## Appendix B. Atlantis\_Review-Executive\_Summary-060112[1].docx (Notes from Telecon held 6/1/2012)

Subject: Display of Atlantis in the KSC Visitor Complex

References (1) and (2) were provided to NASA as part of an ongoing process to show that all procedural steps from transporting the orbiter to the final display configuration are safe and will not damage the Orbiter Atlantis. A review of Reference (1) shows that the attachment points on the orbiter and the attachment hardware to be sufficient for the 43° roll display configuration. This sufficiency is contingent on the support structure / attachment hardware providing the proper compliance. At the forward support point, AO-1 the fore/aft direction should be compliant. At the aft port support point, AO-2 the lateral direction should be compliant. Without these compliances it could be relatively easy to exceed the design loads in Table 3.2.3-1.2 of Reference (3).

To complete the review and assessment of the process, the following documents are needed:


1. The structural steel support frame (display structure) assessment, including the appropriate support structure / attachment hardware compliances.
2. Payload Bay Door procedure and hardware assessment (crane operations (opening), and supporting)
3. Orbiter lifting / jacking procedure onto the display structure and hardware assessment
4. Orbiter rotation procedure and hardware assessment

Confirmation should be provided stating that all hardware and procedures used for handling the orbiter are the same as those used for the flight articles. If not, an assessment of the variances should be provided for review.

Note: Reference (2) contains operations that conflict with those in Reference (1). These conflicts need to be addressed and resolved.

### References:

1. Atlantis Loads Assessment, KSC Visitor Complex Analysis Report, 90% Submittal, BRPH No. 5636.45, dated May 3, 2012
2. Atlantis Support Concept, KSC Visitor Complex, 100% Submittal, BRPH No. 5636.44, dated February 17, 2012
3. ICD-2-17001, rev G-1, Orbiter Vehicle / Carrier Aircraft, Dated March 5, 2007


|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>31 of 138   |

## Appendix C. AtlantisLoadsAssess\_Comments.xlsx (K. Roscoe Comments from NESC Review of Reference Documents: Attachments D of Ref. 1, Ref. 8, and Ref. 9):

### Atlantis Review

brph Atlantis *Loads Assessment*

| Section | Paragraph   | Comments or Notes   |
|---------|-------------|---|
| 1       | 2           | Do not need to make an exception. Comparison to the worst case tensile condition is not applicable. See ICD-2-17001, Section 3.2.3              |
| 1.2     | 2           | Bullet 6: Cannot have a rigid support frame. All loading is contingent on AO-2 not transmitting lateral loads.                                  |
| 1.3     | 4           | Support frame analysis is TBD   |
| 2.2     | Figure      | Sideslip Maneuver Forces: shows vertical tensile force of 128 kips. This case was used to size the bolt preload. See ICD-2-17001, Section 3.2.3 |
| 2.4     | Last        | Statement that they will design the support stand with AO-2 lateral compliance.   |
| 3       | 1           | Don't need exception  |
| 3       | 3           | Disagree with their Z load at AO-3. See Figure in 2.1 and "Loads" sheet   |
| 4.1     |             | Orbiter support structure:<br>AO-1 should be compliant in fore/aft direction<br>AO-2 should be compliant in lateral direction                   |
| 4.2     | all         | Don't need FEA when all the dofs are released.  |
| 4.3     | all         | Don't need FEA when all the dofs are released.  |
| 4.4     |             | ICD-2-17001 rev G-1   |
|         | Figure      | 1.2-1.1 has the attachment coordinates  |
|         | 3.2.3       | Shows sideslip maneuver only used to derive preload   |
|         | Table       | 3.2.3-1.2 shows worst case loads on attachment hardware   |
|         | Table       | 3.2.3-1.3 shows sideslip maneuver loads   |
| 4.5     | Figure 1    | Figure is different from brph Atlantis Support Concept 2/17/12  |
|         | Step 2      | Does not describe how they are going to install Atlantis on support frame   |
|         | Step 3      | Does not describe how they are going to rotate frame  |
|         | Assumptions | Bullet 3: Only applies to attach points (not doors) and needs to have a FS<br>Bullet 6: Frame must be appropriately compliant, not "rigid"      |
|         | Limitations | Assumption that there will be no differences between normal lifting and handling of the Orbiter and landing the Orbiter on the support stand.   |
| 4.6     | email       | Analysis weight appears to be conservative.   |
| End     |             |   |

|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |  |  | Page #:<br>32 of 138   |


## Appendix D. AtlantisLoadsAssess\_Comments RBPH Response.pdf (Response to NESC comments in Appendix C - AtlantisLoadsAssess\_Comments.xlsx)

ATLANTIS LOAD ANALYSIS - Project # 5636.45  
Atlantis Review (06-26-2012)  
brph Atlantis Loads Assessment

DNC Parks & Recreation

| Section | Paragraph          | Comments or Notes  | BRPH Response   |
|---------|--------------------|--|---|
| 1       | 2                  | Do not need to make an exception. Comparison to the worst case tensile condition is not applicable. See ICD-2-17001, Section 3.2.3   | Accept - Will remove exception from report  |
| 1.2     | 2                  | Bullet 6: Cannot have a rigid support frame. All loading in contingent on AO-2 not transmitting lateral loads.   | Accept - Will remove bullet 6 from report   |
| 1.3     | 4                  | Support frame analysis is TBD  | 60% Atlantis Support Package will have the support  |
| 2.2     | Figure             | Sideslip Maneuver Forces: shows vertical tensile force of 128 kips. This case was used to size the bolt preload. See ICD-2-17001, Section 3.2.3  | Information - no action required  |
| 2.4     | Last               | Statement that they will design the support stand with AO-2 lateral compliance.  | 60% Atlantis Support Package will show spacers with slide bearings under the A02 and A03 Aft SCA Bases  |
| 3       | 1                  | Don't need exception   | Accept - Will remove exception from report  |
| 3       | 3                  | Disagree with their Z load at AO-3. See Figure in 2.1 and "Loads" sheet  | BRPH value is slightly higher -9.36 vs 2.712<br>This is due to the Analysis Software and method used and is more conservative than the reviewers result.<br>The conservative results were used in the Orbiter Support frame analysis.               |
| 4.1     |                    | Orbiter support structure:<br>AO-1 should be compliant in fore/aft direction<br>AO-2 should be compliant in lateral direction  | The Teepee for the forward flight ferry is capable of rotating, so special connections for the Teepee to the support are not anticipated.<br>60% Atlantis Support Package will show spacers with slide bearings under the A02 and A03 Aft SCA Bases |
| 4.2     | all                | Don't need FEA when all the dofs are released.   | FEA was not performed, plates were added to an Orbiter model to change the stiffness to review the affect of allowing A03 to support loads in the Xo direction. This lead to not allowing A03 to support Xo loads.                                  |
| 4.3     | all                | Don't need FEA when all the dofs are released.   |   |
| 4.4     | Figure 3.2.3 Table | ICD-2-17001 rev G-1<br>1.2-1.1 has the attachment coordinates<br>Shows sideslip maneuver only used to derive preload<br>3.2.3-1.2 shows worst case loads on attachment hardware<br>3.2.3-1.3 shows sideslip maneuver loads | Information - no action required  |
| 4.5     | Figure 1           | Figure is different from brph Atlantis Support Concept 2/17/12   | If you are referring to "Figure- Orbiter Support Plan" this figure just gives a simple reference horizontal plan location of the connection attachments.<br>This figure is not indicating the support frame.  |
|         | Step 2             | Does not describe how they are going to install Atlantis on support frame  | 60% Atlantis Support Package will basic method.<br>USA will make the ferry flight attachments to the Orbiter.<br>Rigging plans from the Contractor will provide a detailed full procedure and equipment used.                                       |



|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1>NASA Engineering and Safety Center</h1> <h2>Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>33 of 138   |

| Section    | Paragraph   | Comments or Notes   | BRPH Response   |
|------------|-------------|---|---|
|            | Step 3      | Does not describe how they are going to rotate frame  | 60% Atlantis Support Package will basic method.<br>Rigging plans from the Contractor will provide a detailed full procedure and equipment used.                   |
|            | Assumptions | Bullet 3: Only applies to attach points (not doors) and needs to have a FS  | Assuming that this is referring to the Approach section, approximately 1/2 of the final door weight should be supported from the roof structure above.            |
|            | Limitations | Bullet 6: Frame must be appropriately compliant, not "rigid"<br>Assumption that there will be no differences between normal lifting and handling of the Orbiter and landing the Orbiter on the support stand. | See 60% Atlantis Support package for Orbiter installation.<br>Framing between the aft and forward vertical support frames will be removed after Orbiter rotation. |
| 4.6<br>End | email       | Analysis weight appears to be conservative.   | We haven't been able to get sufficiently detailed information to make any reductions.   |



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

## Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center

Page #:  
34 of 138

### Atlantis Review

brph Atlantis Loads Assessment

#### Pinned-Pinned Load Distribution

| Transform Coordinates    |         |       |         |                               |      |        |                  |        |
|--------------------------|---------|-------|---------|-------------------------------|------|--------|------------------|--------|
| ICD-2-17001, Fig 1.2-1.1 |         |       |         |                               |      |        |                  |        |
| Location                 | Xo      | Yo    | Zo      | Relative to AO-1 X & AO-2 Y&Z |      |        | Pivot about AO-2 |        |
|                          |         |       |         | Xo'                           | Yo'  | Zo'    | Yo''             | Zo''   |
| AO-1                     | 388.045 | 0     | 283.841 | 0                             | 96.5 | 16.285 | 59.47            | 77.72  |
| AO-2                     | 1317    | -96.5 | 267.556 | 928.955                       | 0    | 0      | 0                | 0      |
| AO-3                     | 1317    | 96.5  | 267.556 | 928.955                       | 193  | 0      | 141.15           | 131.63 |
| CG*                      | 1082.6  | 0     | 364.9   | 694.555                       | 96.5 | 97.344 | 4.19             | 137.01 |

\* Per brph Loads assessment, Attach F

#### Load Distribution

| X-Direction     |        | Y-Direction       |        |
|-----------------|--------|-------------------|--------|
| Fwd             | 25.23% | AO-2              | 97.03% |
| Aft             | 74.77% | AO-3              | 2.97%  |
| Aft = 694 / 929 |        | AO-3 = 4.19 / 141 |        |
| Fwd = 1 - Aft   |        | AO-2 = 1 - AO-3   |        |


#### Loads


| Atlantis Weight |         | 167,216 |        | Analysis Loads** |         | Limit Loads |    | Factor of Safety |      |
|-----------------|---------|---------|--------|------------------|---------|-------------|----|------------------|------|
|                 | X - Dir | Yo      | Zo     | Yo               | Zo      | Yo          | Zo | Yo               | Zo   |
|                 |         |         |        |                  |         |             |    |                  |      |
| Aft             | AO-2&3  | 125,023 | 85,265 | 91,436           |         |             |    |                  |      |
| Fwd             | AO-1    | 42,193  | 28,776 | 30,858           | 95,300  | 190,400     |    | 3.31             | 6.17 |
|                 | AO-2    |         | 0      | 88,724           | 16,300  | 355,000     |    |                  | 4.00 |
|                 | AO-3    |         | 85,265 | 2,712            | 248,400 | 355,000     |    | 2.91             | 131  |

\*\*Analysis Xo loads were all zero

#### Graphical Display of Rotation


| AO-3   |        |
|--------|--------|
| 193    | 0      |
| 0      | 0      |
| 141.15 | 131.63 |
| CG*    |        |
| 96.5   | 97.344 |
| 0      | 0      |
| 4.19   | 137.01 |




|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>35 of 138   |


**Atlantis Review**  
brph Atlantis *Support Concept*

| Section | Paragraph  | Comments or Notes  | BRPH Response  |
|---------|------------|--|--|
| 1.2     | Step 2-7   | Assume: brph Atlantis <i>Loads Assessment</i> section 4.5, limitations applies and they will not need steps 2-7.   | Steps 2 to 7 are required to get the Orbiter up to the vertical height needed to rotate the Orbiter.   |
| 1.2     | Step 8     | Assume: brph Atlantis <i>Loads Assessment</i> section 4.5, Figure 1 is different from Step 8 (pivot point). Rotation not shown. Step 8 "as-is" is appears unstable.  | See 60% Atlantis Support package.<br>Dunnage has been added on the port side and bracing to the dunnage has been added at all of the dunnage.  |
| 1.2     | Step 9     | Dunnage will not likely work in this configuration.  | See 60% Atlantis Support package.  |
| 1.3     | Step 1     | Port door CG and lift point appear to be in-line with or on the port side of the hinge (eyeball). Crane would need to pull sideways to open.   | A detailed Orbiter door opening procedure is being developed by USA.   |
|         | Step 2 & 6 | Door going over top dead center will want to bounce. Coordinating crane translation with cable tension likely needed.<br><br>Preference: rather ground, support structure, or vehicle support doors. Storms will move rafters and a small cable easier to vandalize. | A detailed Orbiter door opening procedure is being developed by USA.   |
| 4.1     | Appendix A | Is the "Forward Jack" still needed with the current lift plan?<br>Concerns with structure: Clevis ring on post, Foot Plates can't take moments, Lateral braces are flexible.   | Yes - Unless USA comes up with something, there is inadequate clearance from the forward landing gear to the Ferry Flight Teepee support beam. |
| 4.9     | Appendix I | "C-Frame": Flange is not continuous at corner.   | Illustration provided by NASA. Additional drawings from USA have only recently been obtained.  |
| End     |            |  |  |

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>36 of 138   |

## Appendix E. Orbiter Loads 155K Xo = 159 On SCA Connections.pdf



|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>37 of 138   |

Thursday, August 09, 2012, 03:58 PM

PAGE NO. 1

```

*****
*
*      STAAD.Pro V8i SELECTseries2
*      Version  20.07.07.32
*      Proprietary Program of
*      Bentley Systems, Inc.
*      Date=    JUL 17, 2012
*      Time=    14:28:30
*
*      USER ID: BRPH Companies, Inc.
*
*****


```

```

1. STAAD SPACE
INPUT FILE: Orbiter Loads 155K Xo = 159 43 deg Flexible - No Xo Couple.STD
2. START JOB INFORMATION
3. JOB NAME ORBITER SUPPORT LOADS
4. JOB CLIENT DNC
5. JOB NO 5636.45
6. JOB PART ORBITER LOADS ON SCA CONNECTIONS
7. ENGINEER NAME KPAQUETTE
8. ENGINEER DATE 21 MAR 2012
9. END JOB INFORMATION
10. INPUT WIDTH 79
11. UNIT INCHES KIP
12. JOINT COORDINATES
13. 2000 1052.6 272.344 0; 2001 388.045 283.841 0; 2002 1317 267.556 96.5
14. 2003 1317 267.556 -96.5; 10000 1052.6 364.9 0; 10001 1052.6 408.78 -40.92
15. 10037 388.045 283.841 77.88; 10038 484.75 281.54 97.976
16. 10039 581.46 279.238 105; 10040 726.406 276.937 105; 10041 871.35 274.636 105
17. 10042 1016.23 272.335 105; 10043 1148.94 270.033 105
18. 10045 1508.14 267.556 96.5; 10133 235.285 325.841 0; 10138 484.75 281.54 0
19. 10139 581.46 279.238 0; 10140 726.406 276.937 0; 10141 871.35 274.636 0
20. 10142 1016.23 272.335 0; 10143 1148.94 270.033 0; 10144 1317 267.556 0
21. 10145 1524.82 267.556 0; 10237 388.045 283.841 -77.88
22. 10238 484.75 281.54 -97.976; 10239 581.46 279.238 -105
23. 10240 726.406 276.937 -105; 10241 871.35 274.636 -105
24. 10242 1016.23 272.335 -105; 10243 1148.94 270.033 -105
25. 10245 1508.14 267.556 -96.5; 10342 1016.23 272.335 -187.68
26. 10343 1148.94 270.033 -222.96; 10344 1317 267.556 -222.96
27. 10345 1488.7 267.556 -222.96; 10443 1148.94 270.033 -309.72
28. 10444 1317 267.556 -350.04; 10445 1469.62 267.556 -350.04
29. 10544 1317 267.556 -455.4; 10545 1439.38 267.556 -486.48
30. 20137 388.039 412.9 0; 20142 871.35 274.636 -163.56
31. 20143 1016.23 272.335 187.68; 20144 1148.94 270.033 222.96
32. 20145 1317 267.556 222.96; 20146 1488.7 267.556 222.96
33. 20147 1148.94 270.033 309.72; 20148 1317 267.556 350.04
34. 20149 1469.62 267.556 350.04; 20150 1317 267.556 455.4
35. 20151 1439.38 267.556 486.48; 20152 871.35 274.636 163.56
36. 20155 1317 501.699 0; 20156 1439.38 501.699 0; 20157 1317 416.548 96.5
37. 20158 1317 416.548 -96.5; 20159 581.46 428.23 105; 20160 726.406 425.929 105
38. 20161 871.35 423.628 105; 20162 1016.23 421.327 105; 20163 1148.94 419.025 105
39. 20164 581.46 428.23 -105; 20165 726.406 425.929 -105
40. 20166 871.35 423.628 -105; 20167 1016.23 421.327 -105

```

K:\STRUCT\5636.44 Orbiter Installation Concept\Calcs for Kevin Roscoe\Orbiter Loads 155K Xo = 159 43 deg Flexible - No Xo Couple.STD

|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>38 of 138   |

Thursday, August 09, 2012, 03:58 PM


STAAD SPACE

-- PAGE NO. 2

41. 20168 1148.94 419.025 -105; 20170 581.46 428.23 0; 20171 484.75 430.532 97.976  
 42. 20172 484.75 430.532 -97.976; 20173 1439.38 416.548 96.5  
 43. 20174 1439.38 416.548 -96.5; 20175 581.46 529.15 0  
 44. 20176 726.406 276.937 -136.8; 20177 726.406 276.937 136.8  
 45. MEMBER INCIDENCES  
 46. 2001 2001 10038; 2002 2001 10238; 2003 2002 10144; 10001 10000 10001  
 47. 10003 10238 10239; 10004 10239 10240; 10005 10240 10241; 10006 10241 10242  
 48. 10007 10242 10243; 10008 10243 2003; 10009 10038 10039; 10010 10039 10040  
 49. 10011 10040 10041; 10012 10041 10042; 10013 10042 10043; 10014 10043 2002  
 50. 10015 10238 10138; 10016 10239 10139; 10017 10240 10140; 10018 10241 10141  
 51. 10019 10242 10142; 10020 10139 10039; 10021 10140 10040; 10022 10141 10041  
 52. 10023 10142 10042; 10024 10139 10140; 10025 10140 10141; 10026 10141 10142  
 53. 10027 10142 2000; 10034 2000 10242; 10035 2000 10042; 10036 10242 10141  
 54. 10037 10042 10141; 10038 10141 10240; 10039 10141 10040; 10040 10240 10139  
 55. 10041 10139 10040; 10042 2000 10243; 10043 2000 10043; 10044 10144 2003  
 56. 10045 10243 10143; 10046 10143 10043; 10047 2000 10143; 10048 10143 10144  
 57. 10049 2003 10143; 10050 2002 10143; 10060 10242 10000; 10077 10000 10043  
 58. 10078 10000 10243; 10080 10042 10000; 10083 10238 10139; 10084 10038 10139  
 59. 10085 10138 10038; 10086 2001 10138; 10087 10138 10139; 10088 10342 10343  
 60. 10089 10043 10344; 10090 10344 10345; 10091 10443 10444; 10092 10444 10445  
 61. 10093 10544 10545; 10094 2003 10344; 10095 10344 10444; 10096 10444 10544  
 62. 10097 10145 10245; 10098 10245 10345; 10099 10345 10445; 10100 10445 10545  
 63. 10101 10240 20142; 10102 20142 10342; 10103 10342 10443; 10104 10443 10544  
 64. 10105 10243 10343; 10106 10343 10443; 10107 10242 10342; 10108 10241 20142  
 65. 10109 20142 10242; 10110 10242 10343; 10111 10343 10444; 10112 10444 10545  
 66. 10113 10343 2003; 10114 2003 10145; 10115 2003 10345; 10116 10345 10444  
 67. 10117 2003 10245; 10118 10144 10145; 10119 20143 20144; 10120 20144 20145  
 68. 10121 20145 20146; 10122 20147 20148; 10123 20148 20149; 10124 20150 20151  
 69. 10125 2002 20145; 10126 20145 20148; 10127 20148 20150; 10128 10145 10045  
 70. 10129 10045 20146; 10130 20146 20149; 10131 20149 20151; 10132 10040 20152  
 71. 10133 20152 20143; 10134 20143 20147; 10135 20147 20150; 10136 10043 20144  
 72. 10137 20144 20147; 10138 10042 20143; 10139 10041 20152; 10140 20152 10042  
 73. 10141 10042 20144; 10142 20144 20148; 10143 20148 20151; 10144 20144 2002  
 74. 10145 2002 10145; 10146 2002 20146; 10147 20146 20148; 10148 2002 10045  
 75. 10149 10133 2001; 10150 10133 10237; 10151 10237 10238; 10152 10133 10037  
 76. 10153 10037 10038; 10154 10237 2001; 10155 2001 10037; 10159 20155 20156  
 77. 10160 10133 20137; 10161 20137 20172; 10162 20137 2001; 10163 20137 10237  
 78. 10164 20137 10037; 10165 20156 10145; 10166 10045 20156; 10167 20156 10245  
 79. 10168 2002 20155; 10169 2003 20155; 10180 20164 20165; 10181 20165 20166  
 80. 10182 20166 20167; 10183 20167 20168; 10184 20168 20158; 10185 20159 20160  
 81. 10186 20160 20161; 10187 20161 20162; 10188 20162 20163; 10189 20163 20157  
 82. 10190 20157 20155; 10191 20155 20158; 10192 10039 20159; 10193 10040 20160  
 83. 10194 10041 20161; 10195 10042 20162; 10196 10043 20163; 10197 2002 20157  
 84. 10198 10239 20164; 10199 10240 20165; 10200 10241 20166; 10201 10242 20167  
 85. 10202 10243 20168; 10203 2003 20158; 10204 10239 20165; 10205 10240 20166  
 86. 10206 10241 20167; 10207 10242 20168; 10208 10243 20158; 10209 10039 20160  
 87. 10210 10040 20161; 10211 10041 20162; 10212 10042 20163; 10213 10043 20157  
 88. 10214 20159 20170; 10215 20170 20164; 10216 10139 20170; 10217 20159 10139  
 89. 10218 10139 20164; 10220 20172 20170; 10222 20172 10238; 10223 20164 20172  
 90. 10224 20159 20171; 10225 20171 20172; 10227 20171 20137; 10229 10038 20171  
 91. 10231 20157 20173; 10232 20158 20174; 10233 10045 20173; 10234 10245 20174  
 92. 10235 20173 20156; 10236 20156 20174; 10237 20155 20174; 10238 20155 20173  
 93. 10239 2002 20173; 10240 2003 20174; 10241 10037 20171; 10242 10038 20159  
 94. 10243 10237 20172; 10244 10238 20164; 10245 20159 20175; 10246 20164 20175  
 95. 10247 20170 20175; 10248 20175 20171; 10249 20175 20172; 10251 20155 10144  
 96. 10252 10239 20176; 10253 20176 20142; 10254 10240 20176; 10255 10039 20177

K:\STRUCT\5636.44 Orbiter Installation Concept\Calcs for Kevin Roscoe\Orbiter Loads 155K Xo = 159 43 deg Flexible - No Xo Cx



|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>39 of 138   |

Thursday, August 09, 2012, 03:58 PM

STAAD SPACE


-- PAGE NO. 3

```

97. 10256 20177 20152; 10257 10040 20177; 10258 10138 20172; 10259 10138 20171
98. 10260 20170 20171
99. *10230 20172 10238
100. *10226 20138 20172
101. MEMBER PROPERTY AMERICAN
102. 2001 2002 10003 TO 10014 TABLE ST TUB1201205
103. 10001 TABLE ST TUB1201205
104. 10017 TO 10019 10021 TO 10027 10047 10048 TABLE ST TUB50505
105. 10015 10016 10020 10085 TABLE ST TUB50505
106. 10086 10087 TABLE ST TUB50505
107. 10034 10035 10042 10043 10060 10077 10078 10080 TABLE ST TUB1201208
108. 10088 TO 10091 10093 10101 TO 10104 10107 TO 10111 10113 10119 TO 10122 10124 -
109. 10132 TO 10135 10138 TO 10142 10144 TABLE ST TUB80806
110. 10149 TO 10155 TABLE ST TUB80806
111. 10160 TO 10164 TABLE ST TUB80806
112. 10192 TO 10213 TABLE ST TUB80806
113. 10214 TO 10218 TABLE ST TUB80806
114. 10251 TABLE ST TUB80806
115. 10222 TABLE ST TUB50506
116. 10220 10225 10227 TABLE ST TUB80806
117. 10229 TABLE ST TUB50506
118. 10241 TO 10244 TABLE ST TUB50506
119. 10245 TO 10247 TABLE ST TUB50506
120. 10248 10249 TABLE ST TUB50506
121. 10254 10257 TABLE ST TUB50506
122. 10252 10253 10255 10256 TABLE ST TUB80806
123. 10180 TO 10184 10223 10232 TABLE ST TUB1201205
124. 10185 TO 10189 10224 10231 TABLE ST TUB1201205
125. 10036 TO 10041 10083 10084 TABLE ST TUB80806
126. 10049 10050 10114 10145 TABLE ST TUB50506
127. 10117 10118 10148 TABLE ST TUB50506
128. 10092 10112 10115 10116 10123 10143 10146 10147 TABLE ST TUB50506
129. 10097 10128 TABLE ST TUB50506
130. 10159 10165 TO 10167 10235 TO 10238 TABLE ST TUB50506
131. 10190 10191 TABLE ST TUB50506
132. 10168 10169 10233 10234 10239 10240 TABLE ST TUB80806
133. 10258 10259 TABLE ST TUB50506
134. 10260 TABLE ST TUB80806
135. 2003 10044 TO 10046 10094 TO 10096 10098 TO 10100 10105 10106 10125 TO 10127 -
136. 10129 TO 10131 10136 10137 TABLE ST TUB1201205
137. DEFINE MATERIAL START
138. ISOTROPIC MATERIAL1
139. E 10000
140. POISSON 0.33
141. DENSITY 9.549E-005
142. ISOTROPIC STEEL
143. E 29000
144. POISSON 0.3
145. DENSITY 0.000283
146. ALPHA 6E-006
147. DAMP 0.03
148. TYPE STEEL
149. STRENGTH FY 36 FU 58 RY 1.5 RT 1.2
150. END DEFINE MATERIAL
151. CONSTANTS
152. MATERIAL MATERIAL1 ALL

```

K:\STRUCT\5636.44 Orbiter Installation Concept\Calcs for Kevin Roscoe\Orbiter Loads 155K Xo = 159 43 deg Flexible - No Xo Cx

|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>40 of 138   |

Thursday, August 09, 2012, 03:58 PM

STAAD SPACE -- PAGE NO. 4

```

153. SUPPORTS
154. 2001 FIXED BUT FX MX MY MZ
155. 2002 FIXED BUT FZ MX MY MZ
156. 2003 FIXED BUT FX MX MY MZ
157. 10001 FIXED BUT MX MY MZ KFX 0.001 KFY 0.001 KFZ 0.001
158. LOAD 1 LOADTYPE NONE
159. MEMBER LOAD
160. 10001 CON X -155 0
161. PERFORM ANALYSIS

```

#### P R O B L E M   S T A T I S T I C S

-----

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS =    74/   209/    4

SOLVER USED IS THE OUT-OF-CORE BASIC SOLVER

```


ORIGINAL/FINAL BAND-WIDTH=   67/    14/    90 DOF
TOTAL PRIMARY LOAD CASES =   1, TOTAL DEGREES OF FREEDOM =   438
SIZE OF STIFFNESS MATRIX =    40 DOUBLE KILO-WORDS
REQD/AVAIL. DISK SPACE =    12.7/ 305323.7 MB

```

162. PRINT SUPPORT REACTION

K:\STRUCT\5636.44 Orbiter Installation Concept\Calcs for Kevin Roscoe\Orbiter Loads 155K Xo = 159 43 deg Flexible - No Xo Cx



|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>41 of 138   |

SUPPORT REACTIONS -UNIT KIP INCH      STRUCTURE TYPE = SPACE  
 -----


| JOINT | LOAD | FORCE-X | FORCE-Y | FORCE-Z | MOM-X | MOM-Y | MOM Z |
|-------|------|---------|---------|---------|-------|-------|-------|
| 2001  | 1    | 0.00    | 32.26   | -30.09  | 0.00  | 0.00  | 0.00  |
| 2002  | 1    | 0.00    | 91.33   | 0.00    | 0.00  | 0.00  | 0.00  |
| 2003  | 1    | 0.00    | -10.23  | -75.62  | 0.00  | 0.00  | 0.00  |
| 10001 | 1    | 0.00    | 0.00    | 0.00    | 0.00  | 0.00  | 0.00  |

\*\*\*\*\* END OF LATEST ANALYSIS RESULT \*\*\*\*\*

163. FINISH

\*\*\*\*\* END OF THE STAAD.Pro RUN \*\*\*\*\*

\*\*\*\* DATE= JUL 17,2012    TIME= 14:28:31 \*\*\*\*

|   |  |  |                        |
|---|--|--|------------------------|
|    | <h1 style="text-align: center;">NASA Engineering and Safety Center</h1> <h2 style="text-align: center;">Technical Assessment Report</h2> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><h3 style="text-align: center;">Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> |  |  | Page #:<br>42 of 138   |

Thursday, August 09, 2012, 03:58 PM

STAAD SPACE


-- PAGE NO. 6

```

*****
*       For questions on STAAD.Pro, please contact       *
*       Bentley Systems or Partner offices               *
*                                                       *
*       Telephone           Web / Email                 *
* USA          +1 (714) 974-2500                         *
* UK           +44 (0) 808 101 9246                      *
* SINGAPORE    +65 6225-6158                             *
* FRANCE       +33 (0) 1 55238400                       *
* GERMANY      +49 0931 40468                            *
* INDIA        +91 (033) 4006-2021                      *
* JAPAN        +81 (03)5952-6500   http://www.ctc-g.co.jp *
* CHINA        +86 21 6288 4040                         *
* THAILAND     +66 (0)2645-1018/19 partha.p@reisoftwareth.com*
*                                                       *
* Worldwide    http://selectservices.bentley.com/en-US/  *
*                                                       *
*****

```

K:\STRUCT\5636.44 Orbiter Installation Concept\Calcs for Kevin Roscoe\Orbiter Loads 155K Xo = 159 43 deg Flexible - No Xo Cx

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>43 of 138   |

**Appendix F. Email from K. Roscoe to S. Minute on 9/3/2012: 5636.44 RE:  
Atlantis Support Structure - Additional Design Calculations**

**From:** ROSCOE, KEVIN (LARC-D206)  
**Sent:** Monday, September 03, 2012 4:19 PM  
**To:** Minute, Stephen A. (KSC-C105)  
**Cc:** Raju, Ivatury S. (LARC-C104); Elliott, Kenny B. (LARC-D210); Larsen, Curtis E. (JSC-C104); 'David Hamilton' (dave@lifethoughts.com)  
**Subject:** RE: FW: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations  
**Importance:** High

Steve,

I think they closed this item, assuming compatibility of the lubricant and Flourogold, and believing 0.10 is the maximum coefficient of friction per the manufacture (we have margin if it is slightly higher). Both assumptions I would rate as a low risk.

Prior to this response they assumed it would work and didn't think about it (my opinion). Now they have engineered the joint (reduced bearing area to increase pressure load to the minimum recommended, removed post-installation bolt torque, added slide bearings to the shear lugs, contacted the manufacturer to estimate break-away friction, and calculated predicted max break-away shear loads due to thermal expansion).

They could have (or may have) tried to determine the structural compliance between AO-2 and -3 for the small thermal expansion difference. However, the 16,300 lb limit may have been too low for the massive Support Frame. Either way the bearing solution works.

Once they put a slide bearing under AO-1, they solved the biggest threat to the thermal expansion issue. The rest of this work is more or less good engineering (details).

Disclaimer: I haven't looked at the details in the analysis or the drawings, but BRPH gave the right response. I plan on looking at the details after I go thru the hot items in my inbox.

Sincerely,

*Kevin Roscoe*

*Structural & Thermal Systems Branch*


Engineering Directorate

NASA Langley Research Center, MS 431

1 N. Dryden Street / Hampton, VA 23681

Bldg. 1209, Rm. 150B, Off: 757-864-4173

**From:** Minute, Stephen A. (KSC-C105)  
**Sent:** Wednesday, August 29, 2012 12:45 PM  
**To:** Raju, Ivatury S. (LARC-C104); ROSCOE, KEVIN (LARC-D206); Elliott, Kenny B. (LARC-D210); Larsen, Curtis E. (JSC-C104); 'David Hamilton' ([dave@lifethoughts.com](mailto:dave@lifethoughts.com))

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>44 of 138   |

**Subject:** FW: FW: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations  
**Importance:** High

I haven't read any of this yet – wanted to get it directly into your hands.

**From:** Dillon III, John Thurman Rascoe (KSC-SMASS-E)[Millennium Engineering and Integration Company]  
**Sent:** Wednesday, August 29, 2012 12:24 PM  
**To:** Minute, Stephen A. (KSC-C105)  
**Cc:** Braden, Barry M. (KSC-SA000)  
**Subject:** FW: FW: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations  
**Importance:** High

Steve,  
Here is the response from BRPH.  
John

**From:** Ken E. Paquette [<mailto:kpaquette@brph.com>]  
**Sent:** Wednesday, August 29, 2012 12:01 PM  
**To:** Dillon III, John Thurman Rascoe (KSC-SMASS-E)[Millennium Engineering and Integration Company]  
**Cc:** Wohler, William D. (KSC)[DELAWARE NORTH COMPANIES PARKS & RES]; Andrew H. Miller  
**Subject:** RE: FW: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations

John  
See my responses in Red below and forward with my attachments to Mr. Roscoe.  
Thanks Ken


**KEN E. PAQUETTE** | *Senior Structural Engineer*

**BRPH** | 5700 North Harbor City Boulevard, Suite 400 | Melbourne, Florida 32940  
**O:** 321-751-3035 | **F:** 321-259-4703  
[KEP@brph.com](mailto:KEP@brph.com) | [www.brph.com](http://www.brph.com)

**ARCHITECTS | ENGINEERS | CONSTRUCTORS**

**From:** ROSCOE, KEVIN (LARC-D206)  
**Sent:** Monday, August 20, 2012 1:00 PM  
**To:** Minute, Stephen A. (KSC-C105); Raju, Ivatury S. (LARC-C104); Elliott, Kenny B. (LARC-D210); 'David Hamilton' ([dave@lifethoughts.com](mailto:dave@lifethoughts.com)); Larsen, Curtis E. (JSC-C104)  
**Cc:** Dillon III, John Thurman Rascoe (KSC-SMASS-E)[Millennium Engineering and Integration Company]  
**Subject:** RE: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations

Steve,

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>45 of 138   |

**Great. Based on my understanding that takes care of the connection from AO-1 to AO-2 (and AO-3) in the X direction for the post installation condition. An estimate of shear force given the assumptions and calculations can be added to the predicted load summary for the AO joints, provided this is the worst case.**

**Is the connection situation identical for the AO-2 to AO-3 in the lateral direction?**

**There isn't a separate frame in between AO-2 and AO-3 so we considered the full breaking friction force in the Yo directions at the slide bearing at AO-2 for thermal stresses.**

**The Change in length of the Orbiter from AO2 to A03 due to a 30 degree temperature swing is approximately:**

$$13 \times 10^{-6} (30 \text{ degrees})(96.25 + 96.25) = 0.075 \text{ inches}$$

**The change in length of the steel Orbiter support beam for the same length is:**

$$6 \times 10^{-6} (30)(96.25 + 96.25) = 0.03465 \text{ inches}$$

**The change in length difference is 0.0404 inches – a little more than 1/32 of an inch.**

**According to the slide bearing manufacturers, the static coefficient of friction to break away is anywhere from nearly the same as the dynamic friction (0.07) to a maximum of 0.1. So at AO2 the maximum breaking frictional resistance  $Y_o = 93.1(0.1) = 9.31$  kips which we used in our calculations. To assure the 0.07 coefficient of friction in the short term, lubricants are used according to the bearing manufacturers, we are specifying them for the jacking and rotation. The coefficient of friction is also improved with bearing pressures above a minimum of 75 psi according to the slide bearing manufacturers - so for the slide bearings under the spacers, the bottom plate bearing surface was reduced where required to assure that the bearing pressures are above 75 psi for applicable Orbiter orientations. ( The Orbiter when level was a controlling factor at the aft slide bearings.)**

**We have also added high capacity slide bearings at the edges of the shear lugs at the spacers to reduce friction at AO3 and AO1 in the Xo direction from the Yo loads and at AO2 in the Zo direction, and we have considered the breakaway friction at the edge slide bearings in our calculations as well.**


**Also, does environmental control from the time the orbiter is secured to the support frame till the final display configuration exist?**

**Environmental control is not expected, however this procedure is intended to be done in November, when milder temperatures occur.**

**After the building is in use and conditioned, emergency systems to keep the artifacts at a constant temperature are part of the facility design.**

**If not, then there is a risk during this time (jacking and rotation) of an environmental load condition. The event could occur in the level or rotated condition.**

**We have analyzed and provided a table considering the Orbiter loads combined with friction developed on the slide bearings prior to movement and differential thermal expansion for cases that include in the level or rotated condition during jacking and rotation.**

|   |   |  |                        |
|---|---|--|------------------------|
|   | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>46 of 138   |

**Preload:**

We haven't had a lot of discussion concerning bolt torque after installation at the AO joints. The Fluorogold® slide bearings provide compliance once they start sliding. Until then, the bearings provide a rigid structural connection. The bearing's compliance begins once the static friction times the normal force acting on the bearing is exceeded. Bolt preload increases the normal load, thus reduces the compliance (higher break-away force).

The structural compliance as described in the email below should cover the reduction in bearing compliance due bolt preloading at the AO-1 joint. I don't think that is the case at the AO-2 and AO-3 joints. Is there a need to torque the bolts at both AO-2 and AO-3 joints?

**We identified as much as 10.2 kips of uplift at AO3, which isn't very much for all 8 bolts ( 1.5 inch diameter A325) in the spacer to resist. We have removed the torque requirements after jacking and rotation from the contact documents.**

**Note: A rigid bearing joint would not meet the contingency per "Atlantis Review 6-1-12 - Summary.docx" (excerpt):**

"A review of Reference (1) shows the attachment points on the Orbiter and the attachment hardware to be sufficient for the 43° roll display configuration. This sufficiency is contingent on the support structure / attachment hardware providing the proper compliance."

**It should be demonstrated (calculated) that proper compliance exists.**


**We have included additional tabulated comparisons with the Interface loads from ICD-2-17001.**

**Sincerely,  
Kevin Roscoe**

*Structural & Thermal Systems Branch*  
Engineering Directorate  
NASA Langley Research Center, MS 431  
1 N. Dryden Street / Hampton, VA 23681  
Bldg. 1209, Rm. 150B, Off: 757-864-4173

**From:** Minute, Stephen A. (KSC-C105)  
**Sent:** Monday, August 20, 2012 11:51 AM  
**To:** Raju, Ivatury S. (LARC-C104); ROSCOE, KEVIN (LARC-D206); Elliott, Kenny B. (LARC-D210); 'David Hamilton' ([dave@lifethoughts.com](mailto:dave@lifethoughts.com)); Larsen, Curtis E. (JSC-C104)  
**Cc:** Dillon III, John Thurman Rascoe (KSC-SMASS-E)[Millennium Engineering and Integration Company]  
**Subject:** FW: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations  
**Importance:** High



|   |   |   |                        |
|---|---|---|------------------------|
|   | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>47 of 138   |

Folks,

Please see included email and attachment.

Thanks John.

SM

**From:** Dillon III, John Thurman Rascoe (KSC-SMASS-E)[Millennium Engineering and Integration Company]

**Sent:** Monday, August 20, 2012 11:02 AM

**To:** Minute, Stephen A. (KSC-C105)

**Subject:** FW: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations

**Importance:** High

Please forward.

Thanks!

John

**From:** Ken E. Paquette [<mailto:kpaquette@brph.com>]

**Sent:** Monday, August 20, 2012 10:51 AM

**To:** Dillon III, John Thurman Rascoe (KSC-SMASS-E)[Millennium Engineering and Integration Company]


**Cc:** Wohlert, William D. (KSC)[DELAWARE NORTH COMPANIES PARKS & RES]; Andrew H. Miller

**Subject:** RE: 5636.44 RE: Atlantis Support Structure - Additional Design Calculations

**John – Please Forward to Mr. Roscoe**

- 1. We have been looking at the concerns about differential thermal expansion between the Orbiter and the Orbiter Support frame and have the following response.**
  - a. After rotation, the support frame between the Aft and Forward AO supports is intended to be removed, so differential thermal expansion of the Orbiter versus the horizontal support frame between the forward and aft Orbiter supports will not be applicable. The forward support frame is capable of deflecting because it is not braced in the Xo direction.**
  - b. We reviewed the lateral stiffness of the Orbiter forward support frame on its own, and determined that it would deflect about 1 inch for a 1000 lb force conservatively applied at the column below the Teepee support stand. We also determined that the change of length of the Orbiter due to a temperature change from 100 degrees to 70 degrees would be about 0.36 inches based on the coefficient of thermal expansion for Aluminum.**

$$13.0 \times 10^{-6} (100-70)(1317-388.045) = 0.36 \text{ inches}$$

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>48 of 138   |

**So if the slide bearing is not effective for thermal movement, the forward Orbiter support frame will deflect in the Xo direction significantly under low lateral forces.**


Thanks Ken

**KEN E. PAQUETTE** | *Senior Structural Engineer*

**BRPH** | 5700 North Harbor City Boulevard, Suite 400 | Melbourne, Florida 32940


**O:** 321-751-3035 | **F:** 321-259-4703


| [www.brph.com](http://www.brph.com)


|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>49 of 138   |


## Appendix G. Atlantis-Pivot.xlsx (K. Roscoe's Free Body Diagrams)

Enclosure (1) to Atlantis Review 7-5-12 - Summary.docx




|   |   |  |                        |
|---|---|--|------------------------|
|  | <h1>NASA Engineering and Safety Center</h1> <h2>Technical Assessment Report</h2>  | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <h3>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</h3> | Page #:<br>50 of 138                   |                        |



|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>51 of 138   |


Load at top of left side jack depending on interaction of jack to frame:




If the jack is on a slide, then the horizontal component would be zero?


If that is the case, then the horizontal component load would push the jack inboard (couldn't remove dunnage) and wouldn't stop rotating until impacting dunnage.

If there is a horizontal reaction, then the horizontal load would tend to bend the jack and tip it over.

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>52 of 138   |







|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>53 of 138   |

Consider a pinned / pinned jack connected as shown. Once the shuttle is over top dead center, simply throttle the jack until 43°.

Use current planned jack on right side to push it over the top.

The peak load on the jack is when it is the shortest.




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>54 of 138   |


## **Appendix H. AtlantisItemsFor072712meeting.docx (Discussion items for telecon held 7/27/2012)**

### Discussion Items for Atlantis Display Meeting on July 27, 2012

1. Did not find calculations showing the design (including Flourogold) limits the loads at the AO-1 and AO-2 location to the allowable values.
  - a. Found Flourogold coefficient of friction data in vendor brochure. Could not find data for zero velocity (stick/slip).
  - b. Found Flourogold recommended pressure data, but no calculations showing it was not exceeded when torque is applied to bolts the 8 1½-inch bolts. Did not find the torque call-out.
2. Found space between Aft Support Spacer and Shear Lugs. Did not find shims to close the gap (sheet 18 in Atlantis Support.pdf).
3. Orbiter Rotation Frame Analysis:
  - a. Sliding jack has 4 wheels contacting the XZ plane. The wheels will react translation loads in the Y direction (vertical) and moments about the X and Z axes. The Analysis released the moments at this joint, thus could not assess bending in the jack (line 91 of STAAD input deck and joint 3510 output on page 9 of analysis package. Could not find another method where the moments were assessed.
  - b. Could not find documentation for jack vertical stiffness
  - c. Could not find documentation for Propel cylinder stiffness.
    - i. Propel cylinder line of action is in the YZ plane at a shallow horizontal angle. Could not find where the analysis accounted for this vector.
  - d. Did not find lateral load strength or limitation for gantry system, nor lateral stiffness
  - e. Beam model joins member of different size. Without joint releases, the joint is rigid where all degrees of freedom are transmitted. Did not find in Atlantis Support.pdf joint details that were consistent with the analysis method.
    - i. For example, the long Fore/aft beams (X direction) were connected together in the Z direction with smaller beams. Could not find the joint detail.
4. Could not find the “Rigging plans from the Contractor will provide a detailed full procedure and equipment used” document.
  - a. Cannot interpret the lifting note 1 on page 7 of Atlantis Support.pdf, zone F7 without “Rigging Plan”. Alternate the lift fore/aft or port/starboard?

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>55 of 138   |

- b. Could not find a plan to control the load
  - i. Could not find position sensors or load indicators
- c. Could not find lateral load limits for the gantry system
- d. Cannot fully assess rotation operations without more detail

|   |   |   |                        |
|---|---|---|------------------------|
|   | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>56 of 138   |

## Appendix I. AtlantisReview072712-Summary.docx (Summary of telecon on 7/27/2012)


Subject: Display of Atlantis in the KSC Visitor Complex  
Subject: 7/27/2012 Meeting minutes

Doug Wohlert opened the meeting by describing three tasks that DNC is performing:

- 1) Atlantis load assessment – 90% design review package released in May and transmitted to NASA on July 12.
- 2) Transportation of Orbiter Planning – the 90% transportation plan is released and they plan to move the orbiter in November.
- 3) Atlantis Structural Support – the concept was released on Feb 17, 30% design package was released in May, 60% released on June 21. They plan to release the 90% package on August 22 and hold a 2-week review period. The final package is planned to be released on Sept. 19.

This was followed by a review of the attachment to Reference (1) with the bulk of the conversation closing out the drawing comments. A portion of the content of the Reference (1) material was deferred and addressed in the discussion based on the comment in the attachment to Reference (2). The conversation about Reference (2) resulted in the following action items for DNC:


- 1) Redesign AO-1 joint to allow for axial displacement. Although the fitting to the orbiter allows rotation, it transmits forces. Thermal expansion could overload the joint with the current design.
  1. A calculation package showing the predicted loads at the orbiter supports (AO-1, AO-2 and AO-3) was requested. Although the design has elements to reduce the joint shear loads, the predicted values were not presented. The predicted loads would be compared to the orbiter limits to show margin in the design during operations.
- 2) Develop a test fixture, test plan, conduct qualification tests to demonstrate control of the load and provide the obiter operation plan. The test fixture would simulate the orbiter weight and center of gravity. The test plan would envelop the orbiter plan operation environment. The jacks would also be operated asynchronously to demonstrate control of the load.
  1. Due to lack of technical data such as jack lateral stiffness, DNC is not able to analytically show the design is sufficient.

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>57 of 138   |

The beam finite element model presented was too simplistic when it came to joint details and jack simulation. DNC stated they had separate detail analysis results for some critical joints and that they could provide a package for review.

References:


4. Email from Doug Wohlert [DWohlert@dncinc.com] on Mon 7/23/2012 at 11:09 AM with attachment “(2012-07-20) 60% Review Comments and Support Documentation.pdf”.
5. Email from Raju, Ivatury S. (LARC-C104) on Fri 7/27/2012 with attachment “AtlantisItemsFor072712meeting.docx”

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>58 of 138   |

## Appendix J. Propel Jack Cylinder.pdf (Jacks to be used for lift and rotation)


Propel Jack Cylinder.pdf is available at:  
<http://lift-systems.com/>




|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>59 of 138   |



|  |  |  |
|--|--|--|
| <b>LIFT SYSTEMS, INC.</b><br><br>OFFICE:<br>1505 - 7th Street<br>East Moline, IL 61244 |  | MAILING ADDRESS:<br>P.O. Box 906<br>Moline, IL 61266<br><br>TEL: +1-309-764-9842<br>FAX: +1-309-764-9848<br>EMAIL: <a href="mailto:liftit@lift-systems.com">liftit@lift-systems.com</a><br>WEB: <a href="http://www.lift-systems.com">www.lift-systems.com</a> |
|--|--|--|


|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>60 of 138   |

**Appendix K. Atlantis DunnageRevA.pptx (Assessment of dunnage to be used  
in lift and rotation procedure)**


|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>61 of 138   |

# Atlantis Dunnage

10/11/12


|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>62 of 138   |

## Dunnage: Actual





Slide 3

Slide 4

|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>63 of 138   |

## Dunnage: Drawing vs. Actual




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>64 of 138   |

## Dunnage: Drawing vs. Actual



1. Load Path via flat plates?

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>65 of 138   |

## Dunnage: Summary

### Questions:

1. Are they testing the dunnage?
  1. Load removed from jacks and without center pivot posts.  
If they missed the opportunity due to installation of the posts, they can test when they reverse the process.
2. Will the dunnage be in the identical configuration (each piece has an identification number, orientation and location, and includes bracing)?





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**


Version:  
**1.0**


Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**


Page #:  
66 of 138

## Dunnage Stacking



|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>67 of 138   |

## Dunnage FEA (Aft Starboard) with Staggered Stacking





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**


Version:  
**1.0**


Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**


Page #:  
68 of 138

## ¼ Symmetry Dunnage FEMs




|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>69 of 138   |

## ¼ Symmetry FEM and Displacements







|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>70 of 138   |

## Contact Surfaces and Pressure

Normal vectors of  
contact surfaces (TYP)



Surface contact pressure on  
Middle Dunnage plates





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**


Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
71 of 138

## Stress Results

Peak Stress (40 ksi) at pipe to plate interface





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**


Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**


Page #:  
72 of 138

## Stress Results

Stress plot using A36 material, FS of 2 on Yield or an 18 ksi stress limit.  
Most of plate material has capacity (not gray)







|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>73 of 138   |

## Stress Results Summary

- Desirable to have FS of 3 on yield for buckling
- Plate is probably stronger than A36
- Peak stresses at base of pipes
- Center of short length pipes have low to moderate stress
  - Not likely to buckle due to localized end effects
- Geometry will vary, not likely to significantly affect results
- Not the way I would design it, but it will likely work

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>74 of 138   |


## Appendix L. PLBD Support-C.pdf

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>75 of 138   |

## OV-104 PLBD Support


### Display at KSC-VC

May 2012

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>76 of 138   |

#### OV-104 PLBD Support


- Objective – Support PLBD mass and maintain shape integrity
- Composite Payload Bay Doors are not self-supporting in gravity environment
- Construction is multi-ply GR/Ep honeycomb panel over GR/Ep framework
- Door assembly divided into four primary segments and one aft closeout segment
  - door segments jointed with shear transfer pins and a sliding seal system
- Doors are opened and supported using H70-0529 GSE Strongbacks
  - Strongbacks support entire door weight (negligible amount at hinges)
  - counterbalanced to simulate zero gravity using weight and cable system
  - last known values from RTOMI V9023.303/304 (OV-104, OPF-2, July 2011)
    - LH Fwd: 1201 lb, LH Aft: 1715 lb, RH Fwd: 1285 lb, RH Aft: 1768 lb
- Use these approximate values for preliminary design
  - Boeing mass prop. engineer to provide accurate weight and CG

|   |   |  |                             |
|---|---|--|-----------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b>      |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br><b>77 of 138</b> |

### OV-104 PLBD Support

|        | H/L                      |                          | FWD                      |                          | H/L |  |
|--------|--------------------------|--------------------------|--------------------------|--------------------------|-----|--|
|        |                          |                          |                          |                          |     |  |
| Xo624  | G070-340072-001<br>..... | G070-340073-001<br>..... | G070-340073-002<br>..... | G070-340072-002<br>..... |     |  |
| Xo714  | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo805  | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo895  | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo888  | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo1078 | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo1164 | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo1244 | G070-340072-003<br>..... | G070-340073-003<br>..... | G070-340073-004<br>..... | G070-340072-004<br>..... |     |  |
| Xo1301 | G070-340072-005<br>..... | G070-340073-005<br>..... | G070-340073-005<br>..... | G070-340072-005<br>..... |     |  |


GSE Strongback Attach – 18 locations per side

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>78 of 138   |


OV-104 PLBD Support




GSE Strongback Attach

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>79 of 138   |

### OV-104 PLBD Support





|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>80 of 138   |

#### OV-104 PLBD Support


- Consider PLBD support to be a critical lift operation, Ref NASA-STD 9719.19
  - Requires minimum Design Load Safety Factor of 5 for wire rope slings
  - Requires proofload test factor of 2.0 for wire rope slings
- National Air and Space Museum spacecraft curatorial staff recommendation
  - Use non-oiled 7x19 316 stainless wire rope
- Minimize loading into hinge fittings until capability is confirmed
  - Stress analysis review required
- Recommend 3 cable types, 9 cables per side minimum, 3/16" diameter (3400# Ult)
- Final size, attach locations, and quantity TBD by Design Center stress analysis
  - cable "A" (2 per side) connects to PLBD latch mech. at Xo 576 & Xo 1307
  - cable "B" (3 per side) joins Yo 40 & Yo 68 shear tubes at Xo 758, Xo 941, and Xo 1125
  - cable "C" (4 per side) connects to centerline latch mech., joining two rollers per door
- Opportunity – Install cables/fittings in OPF prior to closing doors
  - connect to PLBD, then coil and stow extra length. Position to avoid interference with latching mech.
  - minimizes onsite PLBD work using manlifts


**Title:**

# Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center


Page #: 81 of 138


## OV-104 PLBD Support




|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>82 of 138   |


### OV-104 PLBD Support



|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>83 of 138   |


### OV-104 PLBD Support




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>84 of 138   |


## OV-104 PLBD Support


Cable "C" attach – spreader beam option




|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>85 of 138   |

### OV-104 PLBD Support



|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>86 of 138   |

OV-104 PLBD Support




Connect Locations

Door 1: Xo 647 & Xo 692 (joined)  
Door 2: Xo 828 & Xo 872 (joined)  
Door 3: Xo 1011 & Xo 1055 (joined)  
Door 4: Xo 1184 & Xo 1224 (joined)

RH door cable "C" connect to 594324 roller


LH door cable "C" connect to 594336 roller




|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>87 of 138   |

### OV-104 PLBD Support


COTS attach fitting option




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>88 of 138   |


OV-104 PLBD Support

|        |
|--------|
| BACKUP |
|--------|


|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>89 of 138   |


OV-104 PLBD Support




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>90 of 138   |

OV-104 PLBD Support




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>91 of 138   |


OV-104 PLBD Support






|   |   |   |                        |
|---|---|---|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>92 of 138   |

OV-104 PLBD Support




|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>93 of 138   |

OV-104 PLBD Support






|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>94 of 138   |

OV-104 PLBD Support



port centerline latch fitting

|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |                        |
|   |   |   | Page #:<br>95 of 138   |

OV-104 PLBD Support



starboard centerline latch fitting



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**


Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
96 of 138

## OV-104 PLBD Support



22



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**


Version:  
**1.0**

Title:


**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
97 of 138


## OV-104 PLBD Support




| NODE | Y <sub>o</sub> | Z <sub>o</sub> | RADIUS  |
|------|----------------|----------------|---------|
| A    | 5.560          | 499.874        | 131.974 |
| B    | 17.000         | 498.887        | 150.588 |
| C    | 41.500         | 493.837        | 170.428 |
| D    | 69.500         | 482.960        | 135.683 |
| E    | 82.603         | 475.264        | 101.951 |
| F    | 94.488         | 465.500        | 60.703  |
| G    | 104.129        | 450.620        | 22.937  |
| H    | 105.000        | 438.500        | ∞       |
| I    | 105.000        | 429.500        | ∞       |
| J    | 105.000        | 420.000        | ∞       |


|   |   |   |                        |
|---|---|---|------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b> |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>98 of 138   |

## Appendix M. G-Ops Support.pdf

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center</b><br><b>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>99 of 138   |

## OV-104 Payload Bay Door Securing




|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>100 of<br>138 |


## Assumption


- Minimal cables
- Doors 140 Degrees
- Vehicle 44 Degrees
- Doors Opened after Vehicle positioned
- Trolley Hoist and Strongback used for door opening




|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>101 of<br>138 |


## Rear View of Payload Bay Doors In Hang Position




|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>102 of<br>138 |


## Attach Point Design For Door Panel Interfaces(Radiator Not Show)




|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>103 of<br>138 |


## Attach Point Interfaces for Fore and Aft Ends of Door




|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>104 of<br>138 |


## Attach Type and Location



|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>105 of<br>138 |


## Attach With Radiators in Position




|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>106 of<br>138 |

## Concerns/Data Required


- Upper side wall deflection/stiffness
- Door mass/ center of mass
  - Left door opening when unlatched
  - Cable loading/design
- Do the panels need mid span support
  - If any left door only

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>107 of<br>138 |


## Center of Mass for Lower Door






|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>108 of<br>138 |


## Appendix N. Mathcad - OV-104\_Door\_Support\_Analysis\_3.pdf

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>109 of<br>138 |


## OV-104 DOOR SUPPORT ARM ANALYSIS



DATE: 2012, JULY 12

|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>110 of<br>138 |

## 1.0 Support Arm Analysis



Weights based on counterweight values for 104s last door cycles.  
RH door: 3569, LH door 3458. Conservatively used 3600 lbs


Strongback assy weights are 1400 lbs per side. Only upper tube will be used.  
Assume 2/3 of strongback weight removed. Final counterweight value used  
should be approximately 2600 lbs.


Assume aft-most support is only used to support door 5 interface. No 'load' used to  
support door assys.

$$\frac{2666}{4} = 666.50$$


$F_x := 667 \text{ lbf}$  Estimated load applied at each extension rod (in any direction)

$SF := 2$  Required Safety Factor for design

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>111 of<br>138 |



The forward-most and aft-most of the attachpoints will be hooked to the door roller assys. The inner four will use this support.

|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>112 of<br>138 |

### 1.1 Extension Beam Analysis

bolt calculation 6 .25-28 bolts installed assume the bolt carries all the load

$Z := 1357 \text{ lbf}$  Load from free body diagram

$$A_{ts} := 0.036 \cdot \text{in}^2$$

$$\sigma_{\max 2} := \frac{Z}{2 \cdot A_{ts}} = 18.85 \text{ ksi}$$

Material: Cold worked 300 series stainless steel per ASTM F593

$F_y := 65 \cdot \text{ksi}$   $F_u := 100 \cdot \text{ksi}$  (size 1/4" thru 5/8")

$$Sf_{ys2} := \frac{F_y}{\sigma_{\max 2}} = 3.45$$

$$Sf_{us} := \frac{F_u}{\sigma_{\max 2}} = 5.31$$

#### Bending Calculation

$\underline{W} := F = 667.00 \text{ lbf}$  (Load)

$\underline{H} := 1.5 \cdot \text{in}$

$B := 1 \cdot \text{in}$

$\underline{L} := 3.50 \cdot \text{in}$

$$\underline{S} := \frac{B \cdot H^2}{12} = 0.19 \cdot \text{in}^3 \quad (\text{Section Modulus})$$

#### Stress at Support

$$\sigma_{\max} := \frac{(W \cdot L)}{S} = 12.45 \cdot \text{ksi}$$

Material: 4340

$F_y := 60 \cdot \text{ksi}$

$F_u := 108 \cdot \text{ksi}$

$$Sf_{ys} := \frac{F_y}{\sigma_{\max}} = 4.82$$

$$\underline{Sf}_{us} := \frac{F_u}{\sigma_{\max}} = 8.67$$



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**


Page #:  
113 of  
138

## Tension Calculation


$$A_{\text{beam}} := .75 \cdot \text{in} \cdot 1.5 \cdot \text{in}$$

$$Sf_{\text{beam}} := \frac{F_y \cdot A_{\text{beam}}}{W} = 101.20$$


$$Sf_{\text{beam}} := \frac{F_u \cdot A_{\text{beam}}}{W} = 182.16$$

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>114 of<br>138 |

## **1.2 Clamp Block Analysis**






|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>115 of<br>138 |

### Lug Analysis

#### Notes

Calculations based on *Analysis and Design of Flight Vehicle Structures* by E. F. Bruhn.



#### Input

$a := 1.25 \text{ in}$

$d := 1.625 \text{ in}$

$h := 1.00 \text{ in}$

$k := 2.50 \text{ in}$

Distance between clamping bolt hole centers

$\alpha := 40 \text{ deg}$

$B := 1200 \text{ lbf}$

Conservative value obtained from free body diagram



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
116 of  
138

## Calculations

### Shear Tear out

$$g := \frac{d}{2} \cdot \cos(\alpha)$$

$$g := a - c$$

$$A_s := 2 \cdot g \cdot h = 1.26 \text{ in}^2 \quad (\text{shear area})$$

$$f_s := \frac{B}{A_s} = 0.96 \text{ ksi} \quad (\text{shear stress})$$

Material: 4340

$$F_u := 60 \cdot \text{ksi}$$

$$F_u := 108 \cdot \text{ksi}$$

$$Sf_y := \frac{F_y}{\sqrt{3} \cdot f_s} = 36.23$$

$$Sf_u := \frac{F_u}{\sqrt{3} \cdot f_s} = 65.22$$

(safety factor, per von Mises criteria)

### Bearing stress

$$A_{br} := d \cdot h = 1.63 \text{ in}^2 \quad (\text{bearing stress})$$

$$f_{br} := \frac{B}{A_{br}} = 0.74 \text{ ksi}$$

Note: If bearing properties are not available KSC-STD-Z-0004  
permits use of the following formulas:

$$F_{bry} := 1.4 \cdot F_y$$

$$F_{bru} := 1.4 \cdot F_u$$

(for hole edge distance < 2 x dia)

$$Sf_{yb} := \frac{F_{bry}}{f_{br}} = 113.75$$

$$Sf_{ub} := \frac{F_{bru}}{f_{br}} = 204.75$$

(safety factor)



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
117 of  
138

## Clamping Bolt Analysis

$$F := B = 1200.00 \text{ lbf}$$

Fastener Thread: 3/8-16 UNC-2A

$$A_t := .0775 \cdot \text{in}^2$$


$$\sigma_{\text{max}} := \frac{F}{2 \cdot A_t} = 7.74 \text{ ksi}$$

Material: Cold worked 300 series stainless steel per ASTM F593

$$F_y := 65 \cdot \text{ksi} \quad F_u := 100 \cdot \text{ksi} \quad (\text{size } 1/4" \text{ thru } 5/8")$$


$$Sf_y := \frac{F_y}{\sigma_{\text{max}}} = 7.75$$


$$Sf_u := \frac{F_u}{\sigma_{\text{max}}} = 13.95$$


|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>118 of<br>138 |


### 1.3 Support Beam Analysis


A worst case bending load of this support beam was analyzed using a conservative 667 lbf load applied at such an angle that the worst case bending stress would be obtained at the weakest point of the structure -- the thin area of the beam located at the vehicle pin pivot point in the center of the beam.



|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>119 of<br>138 |



|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>120 of<br>138 |




Maximum principal stress at inside of pivot hole from update FEM

$$\sigma_{\max} := 26.84 \cdot \text{ksi}$$


Material: AISI SAE 4340

$$F_y := 60 \cdot \text{ksi}$$


$$sf := \frac{F_y}{\sigma_{\max}} = 2.24$$

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>121 of<br>138 |


For final install, tabs will be installed and shimmed at outer edge of door supports to keep the door joints from fanning out at the centerline of the doors. Recommend beam and angles be fabricated from 6061 T6 aluminum and primed and painted. Recommend block and round be fabricated from 300 series stainless steel.






|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>122 of<br>138 |

**Appendix O. PLBD Comments.pptx (K. Roscoe's assessment of PLBD  
analysis)**

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>123 of<br>138 |

## PLBD Comments

9/18/2012

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>124 of<br>138 |

# Requirements


*Per PLBD Support-C.pdf, provided via attachment of email from T. Kott, JSC to T. Roberts KSC on 6/1/2012, and subsequently by C. Larsen, on 6/18/2012*

- Consider PLBD support to be a **critical lift operation**, Ref NASA-STD 9719.19 Requires minimum Design Load **Safety Factor of 5** for wire rope slings
  - Requires proofload test factor of 2.0 for wire rope slings

*Per Mathcad - OV-104\_Door\_Support\_Analysis\_3.pdf, provided via attachment of email from S. Minute, KSC to I. Raju on 9/12/2012*

- SF := 2 Required Safety Factor for design


The FS of 5 should be maintained until the load can be distributed into the structure. This doesn't happen until the load is into the PLBD shear tubes. A single failure of a membrane loaded member (pin or bolt) that would result in loss of a critical lift should have FS of 5.

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>125 of<br>138 |

## Total Supported Load

Assumes total per side is 3,600 lbs when using two GSE tubes. 2/3rds of GSE weight (1,400 lbs) is lost when using the 1 tube GSE? Source?

Supported by GSE to open position.  
Worst case is PLBD open, suspended from cables and prior to removing GSE



*Per Mathcad - OV-104\_Door\_Support\_Analysis\_3.pdf*

Weights based on counterweight values for 104s last door cycles. RH door: 3569, LH door 3458. Conservatively used 3600 lbs

Strongback assy weights are 1400 lbs per side. Only upper tube will be used.

Assume 2/3 of strongback weight removed.

3



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**



Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
126 of  
138

## Door Open and Supported



How are the turnbuckles adjusted to provide the proper load per cable? If one turnbuckle is adjusted  $\frac{1}{4}$ " shorter than needed, that turnbuckle/cable picks up additional load from the adjacent cables. Analysis *assumes* uniform distribution.



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
127 of  
138

## Attach Beam

Assuming uniform cable loading:  $F = 667$  lbs




Assumes load normal to AB (worst case)

|                      |         |                    |
|----------------------|---------|--------------------|
| Overall length       | 8       |                    |
| pivot end            | 0.58    |                    |
| pin end              | 0.5     |                    |
| Cable lever arm      | 6.92    | $= 8 - 0.58 - 0.5$ |
| number of spacings   | 5       |                    |
| spacing              | 0.57    |                    |
| Bolt lever arm       | 2.9     | $= 5 * 0.57$       |
| Force ratio          | 2.39    |                    |
| Bolt force           | 1,591   |                    |
|                      | 1/4"    | 3/8"               |
| Bolt tensile area    | 0.0364  | 0.0775             |
| Bolt tensile stress  | 43,735  | 20,529             |
| Bolt ultimate stress | 100,000 | 100,000            |
| Bolt FS, ult         | 2.29    | 4.87               |

Using other bolts may get to FS of 5, but they have diminishing lever arms.

|                        |       |
|------------------------|-------|
| Load per side w/ GSE   | 3,600 |
| GSE 2 Tube Wt          | 1,400 |
| Total Door Wt at cable | 2,200 |
| Ratio 1 to 2 Tube GSE  | 33.3% |
| GSE 1 Tube Wt          | 467   |
| Wt on Cable            | 2,667 |
| Num of Support Cables  | 4     |
| Wt per support cable   | 667   |
| Distribution factor    | 1.00  |
| Wt per Attach Beam     | 667   |



Note:  
Sketch  
is NTS





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
128 of  
138

## Attach Beam


Assuming uniform cable loading:  $F = 667$  lbs



### Attach Beam Bending

| Thru Bolt          | 1/4"    | 3/8"                |
|--------------------|---------|---------------------|
| Height             | 1.5     | 1.5                 |
| Width              | 1       | 1                   |
| Hole thru          | 0.257   | 0.382               |
| Net width          | 0.743   | 0.618               |
| Section modulus    | 0.279   | $0.232 = bh^2/6$    |
| Lever              | 4.02    | $4.02 = 6.92 - 2.9$ |
| Moment             | 2,680   | 2,680               |
| Bending stress     | 9,619   | 11,564              |
| AB ultimate stress | 108,000 | 108,001             |
| AB FS, ult         | 11.23   | 9.34                |

Lots of bending capacity, not a lot of bolt capacity. Consider using 3/8" bolt at end.



Note:  
Sketch  
is NTS





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**

Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**


Page #:  
129 of  
138

## Support Beam

Assuming uniform cable loading:  $F = 667$  lbs




FBD



### Geometry

|                                   |        |
|-----------------------------------|--------|
| Shear Tube to shear tube distance |        |
| Radius at bottom of hole          | 161.69 |
| Shear tube radius                 | 0.81   |
| Radius at shear tube ctr          | 162.5  |
| Arc length to Block edge          | 22.89  |
| Distance to block edge            | 22.87  |
| Block edge to tube ctr            | 1.875  |
| Tube to tube distance             | 24.75  |
| Edge to SB edge                   | 10.36  |
| Approx Tubt to SB edge            | 12.235 |
| Tube to 1/4" bolt                 | 11.665 |
| Tube to cable                     | 15.69  |
| Cable to 1st 3/8" bolt            | 15.00  |





# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**

Version:  
**1.0**


Title:

**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
130 of  
138

## Support Beam

Assuming uniform cable loading:  $F = 667$  lbs




FBD

### SB Bending

|                 |        |        |            |
|-----------------|--------|--------|------------|
| Approx Depth    | 2.144  | 1.572  | Scaled     |
| Width           | 1      | 1      |            |
| Hole thru       | 0.386  | 0      |            |
| Net width       | 0.614  | 1      |            |
| Section modulus | 0.470  | 0.412  | $= bh^2/6$ |
| Moment approx   | 9,997  | 10,457 |            |
| Bending stress  | 21,258 | 25,388 |            |
| AB Yield stress | 60,000 | 60,000 |            |
| AB FS, Yld      | 2.82   | 2.36   | Ultimate?  |

At: 3/8" hole Shear Tube



Same as in Mathcad doc. Ultimate? Note: Not concerned about stress concentrations (Kt). They are for fatigue and slight yielding, neither are a concern. FEA will pick up some Kt.



# NASA Engineering and Safety Center Technical Assessment Report

Document #:  
**NESC-RP-  
12-00768**


Version:  
**1.0**

Title:


**Structural Analysis Peer Review for the Static Display of the  
Orbiter Atlantis at the Kennedy Space Center Visitors Center**

Page #:  
131 of  
138


## Support Beam




Approx same as in Mathcad doc when scaled (force ratio, load).

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>132 of 138  |

## Support Beam




10

|   |   |   |                          |
|---|---|---|--------------------------|
|  | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b>   | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:  | <b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   | Page #:<br>133 of<br>138 |

## Summary


- The cables are in an indeterminate system
  - Analysis did not account for possibility of extra load
  - Cable tensioning procedure?
  - MS is dependent on Cable tensioning
- Recommend modifying 1 bolt from a 1/4" to a 3/8".  
Modifications:
  - Drill 1 hole bigger
  - Drill and tap 1 hole bigger
  - Acquire an extra 3/8" bolt

|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>134 of<br>138 |

## Appendix P. PLBD Attach Beam calcs.xlsx (K. Roscoe's analysis)

### PLBD Calcs

|                                     |         |                  |
|-------------------------------------|---------|------------------|
| Load per side w/<br>GSE             | 3,600   |                  |
| GSE 2 Tube Wt                       | 1,400   |                  |
| Total Door Wt at cable              | 2,200   |                  |
| Ratio 1 to 2 Tube<br>GSE            | 33.3%   |                  |
| GSE 1 Tube Wt                       | 467     |                  |
| Wt on Cable                         | 2,667   |                  |
| Num of Support Cables               | 4       |                  |
| Wt per support<br>cable             | 667     |                  |
| Distribution factor                 | 1.00    |                  |
| Wt per Attach Beam                  | 667     |                  |
| Overall length                      | 8       |                  |
| pivot end                           | 0.58    |                  |
| pin end                             | 0.5     |                  |
| Cable lever arm                     | 6.92    | = 8 - 0.58 - 0.5 |
| number of spacings                  | 5       |                  |
| spacing                             | 0.57    |                  |
| Bolt lever arm                      | 2.9     | = 5 *<br>0.57    |
| Force ratio                         | 2.39    |                  |
| Bolt force                          | 1,591   |                  |
|                                     | 1/4"    | 3/8"             |
| Bolt tensile area                   | 0.0364  | 0.0775           |
| Bolt tensile stress                 | 43,735  | 20,529           |
| Bolt ultimate stress                | 100,000 | 100,000          |
| Bolt FS, ult                        | 2.29    | 4.87             |
| Attach Beam<br>Bending<br>Thru Bolt | 1/4"    | 3/8"             |

|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>135 of 138  |

|                    |         |         |              |
|--------------------|---------|---------|--------------|
| Height             | 1.5     | 1.5     |              |
| Width              | 1       | 1       |              |
| Hole thru          | 0.257   | 0.382   |              |
| Net width          | 0.743   | 0.618   |              |
| Section modulus    | 0.279   | 0.232   | = $bh^2/6$   |
| Lever              | 4.02    | 4.02    | = 6.92 - 2.9 |
| Moment             | 2,680   | 2,680   |              |
| Bending stress     | 9,619   | 11,564  |              |
| AB ultimate stress | 108,000 | 108,001 |              |
| AB FS, ult         | 11.23   | 9.34    |              |


**Lots of bending capacity, not a lot of bolt capacity:  
Consider using larger bolt**

Shear Tube to shear tube distance

|                          |        |
|--------------------------|--------|
| Radius at bottom of hole | 161.69 |
| Shear tube radius        | 0.81   |
| Radius at shear tube ctr | 162.5  |
| Arc length to Block edge | 22.89  |
| Distance to block edge   | 22.87  |
| Block edge to tube ctr   | 1.875  |
| Tube to tube distance    | 24.75  |
| Edge to SB edge          | 10.36  |
| Approx Tubt to SB edge   | 12.235 |
| Tube to 1/4" bolt        | 11.665 |
| Tube to cable            | 15.69  |
| Cable to 1st 3/8" bolt   | 15.00  |

|                 |     |           |            |            |
|-----------------|-----|-----------|------------|------------|
|                 | At: | 3/8" hole | Shear Tube |            |
| Approx Depth    |     | 2.144     | 1.572      | Scaled     |
| Width           |     | 1         | 1          |            |
| Hole thru       |     | 0.386     | 0          |            |
| Net width       |     | 0.614     | 1          |            |
| Section modulus |     | 0.470     | 0.412      | = $bh^2/6$ |




|   |   |  |                        |
|---|---|--|------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>136 of 138  |

|                 |        |        |            |
|-----------------|--------|--------|------------|
| Moment approx   | 9,997  | 10,457 |            |
| Bending stress  | 21,258 | 25,388 |            |
| AB Yield stress | 60,000 | 60,000 |            |
| AB FS, Yld      | 2.82   | 2.36   | Ultimate?? |

#### Reaction Loads

|                      |         |                       |
|----------------------|---------|-----------------------|
| Cable lever arm      | 40.43   |                       |
| Shear Tube lever arm | 24.75   |                       |
| Force ratio          | 1.63    |                       |
| ST force middle      | 1,089   |                       |
| ST force end         | 423     |                       |
| 3/8" bolt Force      | 545     | ~ 1/2 ST force middle |
| Bolt tensile area    | 0.0775  |                       |
| Bolt tensile stress  | 14,056  |                       |
| Bolt ultimate stress | 100,000 |                       |
| Bolt FS, ult         | 7.11    | > 5                   |

|   |   |   |                          |
|---|---|---|--------------------------|
|    | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-<br/>12-00768</b> | Version:<br><b>1.0</b>   |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the<br/>Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |   | Page #:<br>137 of<br>138 |

### Appendix Q. AttachBeamBolts.xlsx (K. Roscoe's analysis)

| bolt | load | Strength | area   | factor   |
|------|------|----------|--------|----------|
| 1    | -810 | 180,000  | 0.0364 | n/a      |
| 2    | -440 | 180,000  | 0.0364 | n/a      |
| 3    | -70  | 180,000  | 0.0364 | n/a      |
| 4    | 290  | 180,000  | 0.0364 | 22.5931  |
| 5    | 660  | 180,000  | 0.0364 | 9.927273 |
| 6    | 1020 | 180,000  | 0.0364 | 6.423529 |

Load lb **667**

Load Arm in **6.92**

#### Current Bolts

At in2 **0.0364**  
Ftu psi **100,000**  
Fty psi **60,000**

**FEA**  
Bolt force **1,003**  
Stress **27,555**


Strength **180,000**  
FS **6.5**

| Bolt         |       | 1          | 2      | 3      |
|--------------|-------|------------|--------|--------|
| Strength     | psi   | 100,000    | 60,000 | 60,000 |
| Capacity     | lbs   | 3640       | 2184   | 2184   |
| L            | in    | 2.9        | 2.33   | 1.76   |
| Moment       | in-lb | 10,556     | 5,089  | 3,844  |
| Total moment | in-lb | 19,489     |        |        |
| Applied mom  | in-lb | 4,616      |        |        |
| FS           | -     | <b>4.2</b> |        |        |

#### High Strength Bolts

At in2 **0.0364**  
Ftu psi **180,000**  
Fty psi **120,000**

| Bolt         |       | 1          | 2       | 3       |
|--------------|-------|------------|---------|---------|
| Strength     | psi   | 180,000    | 120,000 | 120,000 |
| Capacity     | lbs   | 6552       | 4368    | 4368    |
| L            | in    | 2.9        | 2.33    | 1.76    |
| Moment       | in-lb | 19,001     | 10,177  | 7,688   |
| Total moment | in-lb | 36,866     |         |         |
| Applied mom  | in-lb | 4,616      |         |         |
| FS           | -     | <b>8.0</b> |         |         |

|   |   |  |                        |
|---|---|--|------------------------|
|   | <b>NASA Engineering and Safety Center<br/>Technical Assessment Report</b> | Document #:<br><b>NESC-RP-12-00768</b> | Version:<br><b>1.0</b> |
| Title:<br><b>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center</b> |   |  | Page #:<br>138 of 138  |

**Appendix R. Email from C. Larsen to Minute, et. al. on September 5, 2012:  
Re: Atlantis Support Structure – Orbiter allowable loads**

**From:** Larsen, Curtis E. (JSC-C104)  
**Sent:** Wednesday, September 05, 2012 12:43 PM  
**To:** Minute, Stephen A. (KSC-C105); Raju, Ivatury S. (LARC-C104); ROSCOE, KEVIN (LARC-D206); Elliott, Kenny B. (LARC-D210); 'David Hamilton' (dave@lifethoughts.com)  
**Subject:** RE: Atlantis Support Structure - Orbiter allowable loads  
**Importance:** High

Folks –

I have gone back to Shuttle documentation and tabulated below the ET to Orbiter limit loads allowed during ascent flight. These allowable loads are higher than those in the ferry flight ICD for the obvious reason of the more severe flight environment. Thus they reflect the true Orbiter interface load capability and should give us additional comfort in accepting the loads to be imposed by the static display support structure. My reference for these loads is: Lockheed Martin report no. 826-2470, Jan. 2001, "SLWT Structural Load Indicators and Capabilities".

All loads are in kips (1000 lbs), in Orbiter coordinate system.

Interface AO-1: Fx = 10.8/-8.5 Fy = 64.5/-70.9 Fz = 96.4/-127.8

Interface AO-2: Fx = 154.3/-705.3 Fy = 82.0/-107.8 Fz = 247.8/-326.0

Interface AO-3: Fx = 152.9/-699.8 Fy = 103.7/-70.7 Fz = 243.1/-395.7

I hope this helps in our discussions.

Thanks,

Curt

Curtis E. Larsen, Ph.D., P.E.

NASA Technical Fellow for Loads & Dynamics

NASA Engineering and Safety Center (NESC)

281-483-8401 phone

713-392-4923 cell

<http://nesc.nasa.gov/>

NASA (internal only) Loads and Dynamics Community of Practice:

<https://nen.nasa.gov/web/lnd>

| REPORT DOCUMENTATION PAGE   |             |                      |                               |   | Form Approved<br>OMB No. 0704-0188                          |  |
|---|-------------|----------------------|-------------------------------|---|---|--|
| <p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p> |             |                      |                               |   |   |  |
| 1. REPORT DATE (DD-MM-YYYY)   |             | 2. REPORT TYPE       |                               | 3. DATES COVERED (From - To)  |   |  |
| 01-05 - 2013  |             | Technical Memorandum |                               | March 2012 - March 2013   |   |  |
| 4. TITLE AND SUBTITLE<br>Structural Analysis Peer Review for the Static Display of the Orbiter Atlantis at the Kennedy Space Center Visitors Center   |             |                      |                               | 5a. CONTRACT NUMBER   |   |  |
|   |             |                      |                               | 5b. GRANT NUMBER  |   |  |
|   |             |                      |                               | 5c. PROGRAM ELEMENT NUMBER  |   |  |
| 6. AUTHOR(S)<br>Minute, Stephen A.  |             |                      |                               | 5d. PROJECT NUMBER  |   |  |
|   |             |                      |                               | 5e. TASK NUMBER   |   |  |
|   |             |                      |                               | 5f. WORK UNIT NUMBER<br>869021.03.07.01.11                                  |   |  |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)<br>NASA Langley Research Center<br>Hampton, VA 23681-2199  |             |                      |                               | 8. PERFORMING ORGANIZATION<br>REPORT NUMBER<br><br>L-20266 NESC-RP-12-00768 |   |  |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)<br>National Aeronautics and Space Administration<br>Washington, DC 20546-0001   |             |                      |                               | 10. SPONSOR/MONITOR'S ACRONYM(S)<br><br>NASA                                |   |  |
|   |             |                      |                               | 11. SPONSOR/MONITOR'S REPORT<br>NUMBER(S)<br>NASA/TM-2013-217996            |   |  |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT<br>Unclassified - Unlimited<br>Subject Category 39 Structural Mechanics<br>Availability: NASA CASI (443) 757-5802   |             |                      |                               |   |   |  |
| 13. SUPPLEMENTARY NOTES   |             |                      |                               |   |   |  |
| 14. ABSTRACT<br>Mr. Christopher Miller with the Kennedy Space Center (KSC) NASA Safety & Mission Assurance (S&MA) office requested the NASA Engineering and Safety Center's (NESC) technical support on March 15, 2012, to review and make recommendations on the structural analysis being performed for the Orbiter Atlantis static display at the KSC Visitor Center. The principal focus of the assessment was to review the engineering firm's structural analysis for lifting and aligning the orbiter and its static display configuration.  |             |                      |                               |   |   |  |
| 15. SUBJECT TERMS<br>NASA Engineering and Safety Center; Orbiter Atlantis; Retirement; Safety and Mission Assurance; Static Display; Transition   |             |                      |                               |   |   |  |
| 16. SECURITY CLASSIFICATION OF:   |             |                      | 17. LIMITATION OF<br>ABSTRACT | 18. NUMBER<br>OF<br>PAGES   | 19a. NAME OF RESPONSIBLE PERSON                             |  |
| a. REPORT   | b. ABSTRACT | c. THIS PAGE         |                               |   | STI Help Desk (email: help@sti.nasa.gov)                    |  |
| U   | U           | U                    | UU                            | 143   | 19b. TELEPHONE NUMBER (Include area code)<br>(443) 757-5802 |  |