# UNITED STATES DEPARTMENT OF THE INTERIOR Harold L. Ickes, Secretary

GEOLOGICAL SURVEY
W. C. Mendenhall, Director

18

#### Bulletin 881

# SPIRIT LEVELING IN CONNECTICUT 1922-35

J. G. STAACK Chief Topographic Engineer



UNITED STATES
GOVERNMENT PRINTING OFFICE
WASHINGTON: 1937

### CONTENTS

Introduction	1
Cooperation	1
Classification of leveling	<b>2</b>
Adjustments	3
Benchmarks	3
Preservation and restoration of benchmarks	4
Datum	4
Index map	5
Personnel	5
Third-order leveling	7
Index	63
·	
·	
ILLUSTRATIONS	
PLATE 1. Geological Survey benchmarks	4
FIGURE 1. Index map of Connecticut, showing the quadrangles into	
which the State has been divided and the routes followed by	
levelmen of the United States Geological Survey	6
TT .	

## SPIRIT LEVELING IN CONNECTICUT, 1922-35

J. G. STAACK, Chief Topographic Engineer

#### INTRODUCTION

Cooperation.—Connecticut was entirely mapped by the United States Geological Survey in cooperation with the State prior to 1896, the year in which the Federal Survey was first authorized to establish benchmarks. These early maps, however, were based only upon whatever leveling control was then available, mainly railroad profiles and tide gages. The elevations for contouring were extended from such control surveys by barometer and vertical angles, and no additional benchmarks were established by work done at that time for topographic mapping.

In August 1922, to meet the needs of the State and Federal Governments for an accurate system of reference elevations above mean sea level throughout the State, the Director of the United States Geological Survey and the highway commissioner of the State of Connecticut entered into an agreement for a cooperative level-control survey of the State. The first paragraph of the agreement reads as follows:

The level-control surveys (including the establishment of permanent benchmarks) and the preparation of notes resulting therefrom shall be under the supervision of the Director of the United States Geological Survey, or his representative, who shall have complete charge of the surveys and determine the methods to be employed in the field to secure accuracy in establishing the permanent benchmarks based on mean sea level in accordance with United States Geological Survey regulations.

The agreement was made for the period beginning in August 1922 and ending June 30, 1923.

It was understood at the beginning of this program that the United States Coast and Geodetic Survey contemplated the running of certain lines of first-order leveling across the State as part of its general net covering the United States. The plans for the leveling to be done by the United States Geological Survey were accordingly made to supplement the first-order net by a system of third-order, single-run lines, these to be run, however, with first-order equipment, prism levels, and invar-strip rods graduated to decimals of a yard. The regulations governing leveling by the United States Geological

491728

Survey are given in a pamphlet entitled "Topographic instructions of the United States Geological Survey" (Bull. 788).

Concurrently with the leveling begun by the United States Geological Survey in Connecticut, the United States Coast and Geodetic Survey ran a first-order line in 1922 from Yonkers, N. Y., to Westerly, R. I., skirting the coast line. In 1923 first-order lines were run by the Coast and Geodetic Survey along routes from New Haven to Springfield, Mass.; New Britain to East Morris; and Hartford to Auburn, R. I. Additional first-order leveling in Connecticut was done by the Columbia University Summer School of Surveying along the following routes: In 1916, from Dover Plains, N. Y., to East Morris; in 1925-32, from Morris station, by way of Torrington, to Thomaston; in 1932 from Camp Columbia to Bantam and from Morris station, by way of Mount Tom, to Bantam.

The main scheme of third-order leveling in Connecticut by the United States Geological Survey was completed, in accordance with instructions, in the summer of 1923. Some additional benchmarks, however, were set after that date in the northwestern part of the State, in control for Granville and Springfield quadrangles, upon lines of leveling which lie mostly in Massachusetts and which were run in cooperation with that State.

All the third-order leveling in Connecticut was done by parties, each made up of a levelman, two rodmen, and a recorder, using prism levels and invar-strip yard rods. The notes were checked against gross errors by recording the color identifying the various yard intervals, and the computed sums of recorded three-thread readings in yards made upon the invar strips for backsights and foresights were checked by direct readings to hundredths of a foot upon supplementary wooden scales on the backs of the rods. The intervals between the threads were used as measures of the lengths of sights.

Classification of leveling.—Spirit leveling is classified according to the degree of refinement in the instruments and methods used and according to the closure errors.

First-order leveling <sup>1</sup> consists of leveling done with the most improved instruments, all sections being leveled twice, in opposite directions, under varying conditions. Closures are not allowed to exceed the amount in feet represented by the formula

### $0.017 \sqrt{\text{length of section in miles}}$ .

All corrections for rod error, temperature, and unbalanced sights are applied, as well as the orthometric corrections for convergence of level surfaces of different elevations toward the north.

<sup>1</sup> See Avers, H. G., Manual of first-order leveling: U. S. Coast and Geodetic Survey Special Pub. 140, 1929.

Second-order leveling, according to regulations of the United States Geological Survey, comprises lines leveled twice with reliable instruments, though not necessarily of the most improved type. Closures are not allowed to exceed 0.035 length of section in miles.

Third-order leveling is made up of lines that are run, either with first-order equipment or with an engineer's wye level and New York rods, in single-line circuits that are required to close within the limits, in feet, of  $0.05\sqrt{\text{length}}$  of circuit in miles. This is equivalent to  $0.071\sqrt{\text{length}}$  of section if the line is leveled twice.

Adjustments.—The adjustment of a leveling net begins with the first-order lines. Most of these lines in both the United States and Canada have already been combined in a general net, and the orthometric differences, derived from the observed values by correction for the convergence of level surfaces toward the north, have been adjusted to remove accidental closure errors by the mathematical method known as least squares. The latest adjustment of this kind was made in 1929 by the Coast and Geodetic Survey and is known as the 1929 general adjustment of first-order leveling. This adjustment included the first-order lines in Connecticut, and the elevations thus derived are the fundamental references for elevations determined by second- and third-order nets. The third-order leveling of the United States Geological Survey in Connecticut has been adjusted by determining weighted mean elevations for new junction points and prorating the errors of each link. The weights are taken as the reciprocals of lengths of links. The third-order net has been thus brought into agreement with the best information available from the results of the fundamental first-order leveling.

Benchmarks.—The standard benchmarks used by the United States Geological Survey in Connecticut in 1922-23 are circular tablets 3% inches in diameter, with a thickness tapering from three-eighths of an inch at the center to about one-fourth of an inch near the rounded (See pl. 1.) Each tablet has a 3-inch shank attached to its under side at the center, by means of which it is cemented in place. The face of the tablet is cast with the words "U. S. Geological Survey", "In cooperation with the State of", "Elevation above sea - feet", and "250 dollars fine for disturbing this mark." cross inside a triangle at the center indicates the fiducial point for position or elevation. If the tablet is to mark a traverse station, the traverseman stamps it with his identifying letter or letters, the serial number of the station, and the year, using steel dies. tablet is set as a benchmark, the levelman stamps it with his identifying letter or letters, the serial number, and the year; the figures of elevation to the nearest foot are added later. The tablets often serve a dual purpose, but they are supposed to be stamped only by

the party setting them. The latest style of tablet, not yet used in Connecticut, omits the penalty phrase and substitutes the words "For information write the Director" and "Washington, D. C.", and adds the word "benchmark." The elevations stamped upon the tablets as determined in the field are sometimes found to be in error, as shown by office computation, but the figures still serve to identify the marks. It is assumed that engineers and others who have occasion to use the benchmarks will apply to the Director of the United States Geological Survey, Washington, D. C., for accurate figures of the elevations.


The tablets, of whatever style, are cemented into holes drilled in solid rocks or in the walls of public buildings, bridge abutments, or other masonry structures. Where masonry or rock is not available concrete posts are constructed with the tablets set in their tops. As a rule the posts are about 8 inches square or 8 inches in diameter at the top, broader at the base, and reinforced with iron bars. They are generally set so as to project about 6 inches above ground and are made sufficiently long to reach below frost line.

Supplementary benchmarks are of several types. One type consists of a copper nail 1½ inches long supplied with a ½-inch copper washer, through which it is driven into the root of a tree or some timber structure or cemented into rock after bending the point. The washers are stamped "USGS BM", and on some of them the abbreviation of the name of the State is added. Another type of supplementary benchmark is a chiseled square, used on rocks or masonry structures in horizontal position, or a chiseled cross, used on structures in vertical position. Ordinary nails and track spikes are also used and, occasionally, easily described and recognized points, such as doorsills and tops of hydrants.

Preservation and restoration of benchmarks.—Any person who finds that a standard benchmark has been damaged, disturbed, or destroyed or that it should be reset or redescribed on account of highway or other improvements will render a public service by communicating the facts to the Director, United States Geological Survey, Washington, D. C., before taking any action affecting the location or elevation of the mark. The Director will then advise him as to the correct procedure to follow and, if he grants permission to remove or reset the mark, will send a suitable form, accompanied by a self-addressed franked envelope, for use in reporting the action taken, the revised description of the mark, if any, and the notes made in obtaining the revised elevation.

1

Datum.—All elevations determined by the United States Geological Survey and those determined by the United States Coast and Geodetic Survey for inland mapping are referred to mean sea level, which is the level that the sea would assume if the influence of winds, tides, and currents was eliminated. This level is not the elevation



GEOLOGICAL SURVEY BENCHMARKS.

A, Tablet used in cooperating States. The State name is inserted at G. B and D, Copper temporary benchmark, consisting of a nail and washer. A, C, and E, Tablets for stone or concrete structures.

determined from the mean of the highest and the lowest tides, nor is it the half sum of the mean of all the high tides and the mean of all the low tides, which is called the half-tide level. Mean sea level is the average height of the water, all stages of the tide being considered. It is determined from observations made by means of tidal gages placed at stations where local conditions, such as those due to long, narrow bays, rivers, and like features, will not affect the height of the water. To obtain even approximately correct results these observations must extend over at least one lunar month, and if accuracy is desired they must extend over several years. At ocean stations the half-tide level and the mean sea level usually differ but little. It is assumed that there is no difference between the mean sea levels determined from observations made in the Atlantic Ocean, the Gulf of Mexico, and the Pacific Ocean.

Index map.—The accompanying index map of Connecticut (fig. 1) shows the relative position of the mapped quadrangle areas which make up the State. The benchmark descriptions in this bulletin are grouped according to these quadrangle areas. Maps of the quadrangles may be purchased at 10 cents each retail or 6 cents wholesale—in lots of 50 or more. Prepayment is required and may be made by money order, payable to the Director of the United States Geological Survey, or in cash—the exact amount—at sender's risk. Postage stamps should not be sent.

Personnel.—The field work on most of the third-order lines of leveling run by the United States Geological Survey in Connecticut was done by a party in charge of R. M. Wilson, who acted as levelman. The names of the chiefs of other parties are given under the appropriate route titles. Approximate elevations to the nearest foot consistent with a preliminary adjustment of the level net made in 1923 by Mr. Wilson were stamped upon the tablets by C. A. King in 1923. The office work incident to the latest adjustment of the lines, the assembling of the lists, and the reviewing of descriptions was done by E. W. Tibbott, computer, under the supervision of R. M. Wilson, chief of the section of computing, under the general direction of J. G. Staack, chief topographic engineer.

<sup>&</sup>lt;sup>2</sup> See Jones, E. L., Hypsometry—Use of mean sea level as the datum for elevations: U. S. Coast and Geodetic Survey Special Pub. 41, 1917. Manual of tide observations: U. S. Coast and Geodetic Survey Special Pub. 196, 1935.




FIGURE 1.—Index map of Connecticut showing the quadrangles into which the State has been divided and the routes followed by levelmen

# THIRD-ORDER LEVELING BRIDGEPORT QUADRANGLE

[Latitude 41°-41°15'; longitude 73°-73°15']

#### FAIRFIELD AND NEW HAVEN COUNTIES

Leveling in 1922 by R. M. Wilson

From Norwalk quadrangle southeast along Easton-Bridgeport highway to Bridgeport, thence north along Bridgeport-Newtown highway into Derby quadrangle

Bridgeport, 2.5 mi. NW. of, 600 ft. E. of top of first long hill out from Bridgeport on Danbury rd., on N. side of rd., in top of large boulder; standard tablet stamped "152 16 W 1922"Bridgeport, at foot of Bostwick Street, at Sewage Disposal Plant 1, on S. side of building, 3 ft. E. of S. entrance, 1 ft. S. of S. face of building, in concrete foundation of pumping sta.; standard tablet	Feet 152, 188
stamped "19 W 1922 11.11", U. S. C. & G. S. designation "L 2" Bridgeport, on Hollister Avenue, 300 ft. S. of its intersection with Stratford Avenue, at McKinley School, at southernmost entrance on Hollister Avenue, in S. end of bottom step; standard tablet	11. 050
stamped "18 W 1922 20.49", U. S. C. & G. S. designation "V 2" Bridgeport, at corner of Wayne Street and Fairview Avenue, at Wayne Street entrance to Madison School, in S. end of third step; standard tablet stamped "17 W 1922 135.56", U. S. C. & G. S. des-	20. 420
ignation "N 2" North Bridgeport, at SW. corner of Main Street and Jewett Avenue,	135. 505
in curb; copper nailNorth Bridgeport, 0.8 mi. N. of, 300 ft. N. of large rocky bank, on	15 <b>2.</b> 35
W. side of rd., in top of boulder; copper nail North Bridgeport, 2.0 mi. N. of, 200 ft. S. of large frame farmhouse, on W. side of rd., in stone wall, on S. side of gate, in lower end	227. 56
stone of wall; standard tablet stamped "361 20 W 1922"	361. 072
From Stratford northeast along Stratford-Shelton highway into Derby quadrangle	
U. S. C. & G. S. B. M. designated "Y 2 24.63"	24. 557
copper nail	45. 62
Stratford, 2.0 mi. N. of, at corner of Main Street and Cut Spring Road, on W. side of rd., in culvert; copper nail 3Stratford, 2.6 mi. N. of, 200 ft. S. of crossing of trolley tracks, across	65. 43
rd. from small pond, 3 ft. SE. of S. end of concrete railing on E. side of rd., in solid rock; copper nail	24. 08
Stratford, 4.1 mi. N. of, 200 ft. S. of farmhouse situated at point where trolley tracks leave highway, on W. side of rd., at base of stone wall, in solid rock; standard tablet stamped "49 62 W 1922"	
(reported in 1924 as destroyed)	49. 338

A chisel cut on a boundary stone 80 ft. N. of this culvert is 0.333 ft. lower than the copper nail.

#### BROOKFIELD QUADRANGLE

[Latitude 42°-42°15'; longitude 72°-72°15']

#### TOLLAND AND WINDHAM COUNTIES

#### Leveling in 1934 by E. M. Wheeler

# From Connecticut-Massachusetts State line near Muddy Pond along winding roads west and back to State line

WOST MALE DIGITAL TO SHARE MALE	
North Woodstock, 3.2 mi. NW. of, 4.5 mi. S. of town hall at Southbridge (Mass.), in NW. angle of junction of EW. rd. with T-rd. N., 20 ft. W. of junction, 20 ft. N. of center line of EW. rd., in root on W. side of 16-in. pine tree; copper nail and washerNorth Woodstock; 4.3 mi. NW. of, near NW. abutment of abandoned bridge over W. branch of Lebanon Brook, 20 ft. NE. of center line of abandoned rd., in root on S. side of 12-in. twin maple tree;	Feet 760. 21
copper nail and washer	<b>624</b> . 60
North Ashford, 5.4 mi. NE. of, 4.9 mi. SW. of Southbridge (Mass.), 0.5 mi. S. of State line, 90 ft. NE. of junction of NESW. rd. with T-rd. E., 20 ft. NW. of center line of rd., in root on SE. side of 10-in.	
ash tree; copper nail and washer	771. 95
[Line jogs into Massachusetts.]	
North Ashford, 4.4 mi. by rd. N. of, 1.1 mi. SW. of State line, 10 ft.	
NW. of center line of rd., on top of boulder; chiseled square	872. 45
North Ashford, 3.3 mi. N. of, 3.4 mi. by rd. SE. of Mashapaug, in grass triangle at junction of NWSE. rd. with T-rd. E., in root	
on SE. side of 20-in. maple tree; copper nail and washer	911. 62
and washer	687. 93
opposite junction of NESW. rd. with rd. E., 10 ft. W. of center	
line of rd., in root on SE. side of 14-in. maple tree; wire nail Mashapaug, 220 ft. NW. of junction of Stafford Springs-Sturbridge highway with rd. NW., 50 ft. NE. of center line of rd., in SE. side	702. 88
• • •	717. 547
of ledge; standard tablet stamped "WH 24 718 1934"Reference mark, 160 ft. S. and 100 ft. E. of tablet, in N. angle of junction of highway with rd. NW., in root on NE. side of 24-in.	717. 547
elm tree; copper nail and washer	701. 37
SE. of State line, 10 ft. NE. of center line of rd., in root on E. side	
of 48-in. pine tree; rail spike	737. 92

#### CORNWALL QUADRANGLE

[Latitude 41°45′-42°; longitude 73°15′-73°30′]

#### LITCHFIELD COUNTY

#### Leveling in 1923 by R. M. Wilson

From Sheffield quadrangle at point about 3 miles north of Falls Village south along sand road and Canaan-Danbury highway to Cornwall Bridge

Falls Village, 2.2 mi. N. of Iron State Bank at, 3.2 mi. S. of Canaan post office, near SE. base of steep wooded hill, 200 ft. SW. of small	<del>-</del> .
timbered mound, on W. side of rd., part way up sandy bank, on large fragment of embedded limestone; chiseled squareFalls Village, 1.6 mi. N. of, 100 ft. S. of R. R. crossing at rd. forks, on W. side of rd., on N. wing wall of concrete highway over stream;	Feet 659. 15
chiseled square	643. 34
SE. corner of capstone; chiseled square	616. 42
"628 210 W 1923"  Lime Rock sta., 600 ft. NW. of, 1.6 mi. S. of Falls Village, at E. end of street bridge over Housatonic River, on S. side of rd., about 2 ft.	627. 947
below floor level of bridge, at SW. corner of bridge seat, on obtuse angle of corner stone; chiseled squareLime Rock sta., 1.8 mi. S. of, 2.9 mi. N. of West Cornwall, on W.	540. 83
bank of river, opposite small summerhouse in front of Pine Villa Park, on E. side of rd., in root on W. side of 18-in. elm tree; copper nail	534. 67
West Cornwall, 1.5 mi. N. of, 700 ft. N. of rd. fork W., 60 ft. N. of schoolhouse, 50 ft. W. of rd., on large boulder projecting 2 ft. above ground; standard tablet stamped "647 121 W 1923"	646, 289
West Cornwall, 150 ft. W. of R. R. crossing, on W. side of door, at base of corner post of white picket fence, on large slab of rock; chiseled square	515. 67
West Cornwall, 50 ft. N. of R. R. erossing, on NW. wing wall of small R. R. bridge, on limestone masonry; chiseled square	527. 60
West Cornwall, 1.7 mi. S. of, 2.7 mi. N. of Cornwall Bridge, on W. side of river, 500 ft. S. of rd. forks, 100 ft. S. of large house, on E. side of rd., on large rock at E. side of stone wall; chiseled square.	499, 92
Cornwall Bridge, 400 ft. N. of R. R. sta., on S. abutment of small R. R. bridge, on W. side of tracks, on masonry; chiseled square	441. 00
Cornwall Bridge, 150 ft. S. of R. R. sta, on E. side of tracks, on low concrete retaining wall between roadway and sta. platform; standard tablet stamped "442 212 W 1923"	441. 784
From Cornwall Bridge east along Cornwall Bridge-Torrington highway into Winsted quadrangle	
Cornwall Bridge, 630 ft. E. of R. R. sta., on S. side of rd., at W. end of head wall of small concrete bridge; standard tablet stamped "465 213 W 1923"	464. 490
Cornwall Bridge, 1.5 mi. NE. of, 1.9 mi. SW. of Cornwall, at W. end of sharp curve in rd. near E. end of site of old sawmill, on small knoll just E. of old building foundation, 25 ft. S. of rd.,	
near bank of stream, on flat embedded rock; chiseled square	631. 46

•	
Cornwall, 1.1 mi. W. of, 40 ft. S. of rd. forks, in SE. corner of junction, at end of stone wall, on large embedded rock; chiseled squareCornwall, at NW. corner of Calhoun Memorial Library, at W. end	Feet 699. 78
of steps to N. entrance of building, on granite guard stone; standard tablet stamped "719 214 W 1923"	718. 290
Cornwall, on opposite corner of street from library; top of hydrant.	717. 86
Cornwall, 1.3 mi. NE. of, 60 ft. SW. of crossroad, in pasture land, on	
top of large sunken boulder, about 3 ft. above ground; chiseled	1 016 99
squareCornwall, 1.9 mi. E. of, 3.4 mi. NW. of West Goshen, at steep, sharp	1, 016. 32
curve in rd., near junction of old woods rd. S., 25 ft. S. of rd., on	
large flat, smooth outcrop of solid rock; chiseled square	1, 157. 20
West Goshen, 2.7 mi. NW. of, near top of hill, directly opposite	
driveway to house, on N. side of rd., about 8 ft. above rd. level, in upper part of large sloping outcrop of solid rock; standard tablet	
stamped "1413 215 W 1923"	1. 412. 411
West Goshen, 1.3 mi. NW. of, 100 ft. N. of rd. fork W., on NE. side	<b>.,</b>
of rd., near base of rocky knob, on sunken rock; chiseled square-	1, 290. 30
West Goshen, in W. part of town, at S. side of rd. forks, on large	1 201 06
sunken rock; chiseled square	1, 281. 00
N. of rd., on sunken rock; chiseled square	1, 298. 50
DANBURY QUADRANGLE [Latitude 41°15'-41°30'; longitude 73°15'-73°30']	
FAIRFIELD, LITCHFIELD, AND NEW HAVEN COUNTIES	
Leveling in 1922 by R. M. Wilson	,
From Norwalk quadrangle north along Norwalk-Danbury highway to	
Danbury	
Branchville, 0.5 mi. S. of, at forks of paved rd. E., opposite rd. junc-	Feet
tion, on W. side of rd., in retaining wall in front of house, in lower concrete step; standard tablet stamped "338 4 W 1922"	338. 348
Branchville, 0.8 mi. N. of, between rd. and R. R., at base of granite	000. 040
outcrop 10 ft. high, about 1 ft. above rd. level; copper nail	374. 84
Branchville, 2.4 mi. N. of, 300 ft. S. of junction of rds. NW. and N.	
(to Topstone sta.), on W. side of rd., in granite outcrop; copper nail_	422. 14 <sup>-</sup>
Branchville, 3.5 mi. N. of, at sharp bend in rd., on E. side of rd., at W. end of small dam across stream, in rock; copper nail	477. 10 <sup>-</sup>
Branchville, 4.6 mi. N. of, 6.1 mi. S. of Danbury, at junction of paved	111.10
rd. SW. to Ridgefield, on E. side of junction, on top of large sunken	
boulder; standard tablet stamped "510 5 W 1922"	509. 525
Danbury, 4.3 mi. S. of city hall at, 50 ft. S. of rd. fork SE., on W. side	512. 77
of rd., in granite outcrop; copper nail	312. 77
main rd., on E. side of rd., in front of cemetery, in concrete base of	
iron fence post; standard tablet stamped "456 6 W 1922"	<b>4</b> 56. <b>2</b> 62 ·
Danbury, 1.7 mi. SW. of, 50 ft. S. of rd. fork W., on E. side of rd., in	400.04
sunken boulder; copper nail	482. 04
Danbury, on S. side of Park Avenue, 50 it. Sw. of Pleasant Street, at	404.05

corner house, in lower concrete step; copper nail\_\_\_\_\_

Danbury, at West and Division Streets, near SE. corner of base of "Eagle" statue; small chiseled depression.....

494.05

437.68

Danbury, at front entrance of Morris Street School, on doorsill; standard tablet stamped "517 7 W 1922"	Feet 516. 547
Danbury, at West Street Armory, inside portico at front door, in vertical face of E. end of top step; standard tablet stamped "423 8 W 1922"	423, 321
Danbury, at city hall, on S. side of areaway under Main Street entrance, on coping stone; standard tablet stamped "398 9 W 1922"	397. 897
From Danbury southeast along Danbury-Bridgeport highway into Norwalk quadrangle	
Danbury, 1.2 mi. SE. of city hall, 300 ft. S. of top of rise in rd., on E.	
side of rd., in outcrop of solid rock; copper nail	428. 14
Avenue, cemented in curbing; copper nail	372. 16
tablet stamped "411 10 W 1922"	410. 848
at corner of stone wall, in corner of large rock; copper nail Bethel, 1.9 mi. SE. of, on S. side of rd., in wing wall of large culvert;	473. 86
copper nail.  Bethel, 2.7 mi. SE. of, 3.5 mi. NW. of Ridgewold, 500 ft. NW. of top of hill, 150 ft. SE. of small gravel pit, on E. side of rd., in rock out-	460. 24
crop 5 ft. high; standard tablet stamped "632 11 W 1922"	631. 715
Grounds, on W. side of rd., in outcrop of solid rock; copper nail	622. 63
Ridgewold, 1.4 mi. NW. of, 300 ft. SE. of sharp bend in rd., on N. side of culvert; copper nail	557. 49
Ridgewold, at crossroads, on S. end of lower step of Episcopal Church; standard tablet stamped "685 12 W 1922"	685. 267
Ridgewold, 1.1 mi. SE. of, on E. side of rd., 30 ft. N. of corner of stone wall at gate to dim private rd., in granite outcrop; copper nail	587. 79
Ridgewold, 2.1 mi. SE. of, 2.9 mi. NW. of Easton, 200 ft. S. of large house, on E. side of rd., in large rock under maple tree; copper nail	538. 44
Easton, 1.8 mi. NW. of, at middle of steep pitch in rd., on E. side of rd., in granite outcrop; standard tablet stamped "392 13 W 1922" Easton, 1.0 mi. NW. of, in front of Easton Auto Service Station, on N.	392. 198
end of lower concrete step; copper nail	275. 81
From Danbury northeast along Danbury-Hartford highway into Derby quadrangle	
Danbury, 2.0 mi. NE. of city hall at, 200 ft. N. of junction of Newtown and New Milford rds., on W. side of New Milford rd., in con-	
crete culvert; copper nail	311. 66
W. side of T-rd., in large rock in stone wall; copper nail	356. 75
"513 25 W 1922"	512, 714
nail	485. 54

Newtown, 2.9 mi. W. of, at T-rd. S. to Taunton, in center of grass triangle at rd. junction, in large rock; copper nail	Feet
	451. 85
Newtown, 1.7 mi. W. of, N. of Lake Taunton, at top of long hill, in	400. 368
center of grass triangle at rd. fork SW., in rock; copper nail Newtown, 1.2 mi. W. of, on S. side of main rd., 300 ft. E. of house	662. 26
surrounded by coursed stone wall, embedded in rock; copper nail Newtown, 0.8 mi. W. of, at top of hill, on S. side of rd., in lower	693. 03
Newtown, 300 ft. N. of paved T-rd. E. to Hartford, on W. side of rd., at N. side of door of Newtown Savings Bank, in top of granite step;	741. 35
standard tablet stamped "562 24 W 1922"	562. 113
level; copper nailSandy Hook, 0.8 mi. E. of R.R. sta. at Newtown, at SE. corner of	382. 11
bridge across small stream, in concrete sidewalk; copper nail Sandy Hook, 1.7 mi. NE. of, at highway bridge over Housatonic River, on S. side of E. abutment; standard tablet stamped "120 27	240. 55
W 1922''	119. 616
Sandy Hook Bridge, 0.9 mi. NE. of, 2.7 mi. NE. of Sandy Hook, 600 ft. S. of point where rd. turns away from river bank, at NE. corner of	
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	122. 72
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail  From Derby quadrangle northwest along Bridgeport-Newtown highway to Newtown	122. 72
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail  From Derby quadrangle northwest along Bridgeport-Newtown highway to Newtown  Stepney, 200 ft. N. of store of M. Horowitz & Co., on E. side of rd., at foot of S. gatepost at driveway to farmhouse, in rock foundation;	
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91 344. 74
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91 344. 74 361. 577
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91 344. 74 361. 577 427. 70
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91 344. 74 361. 577 427. 70 429. 13
ft. S. of point where rd. turns away from river bank, at NE. corner of large concrete bridge, in curbing; copper nail	347. 91 344. 74 361. 577 427. 70 429. 13 430. 921

From Derby quadrangle northwest along road paralleling Housatonic River into . New Milford quadrangle	*
Sandy Hook Bridge, 1.3 mi. N. of, 3.3 mi. SE. of Shepaug, 150 ft. E. of rd., at foot of hill, on large rock; copper nail	Feet 107. 92
Shepaug, 2.0 mi. SE. of, at point where rocky ledge crowds rd. close to river, on N. side of rd., in solid rock; copper nailShepaug, 0.9 mi. SE. of, 50 ft. NE. of small bridge, 30 ft. E. of rd., in	117. 62
barnyard, on top of small knob, in embedded rock; copper nail Shepaug, near junction of Shepaug and Housatonic Rivers, at NE. corner of highway bridge over Shepaug River; in capstone of abutment: standard tablet stamped "128 28 W 1922" (reported	125. 94
May 15, 1934, as destroyed by ice and flood)Shepaug, 0.9 mi. NW. of, 0.2 mi. SE. of T-rd. E., in front of large	128. 314
white house, in root of large maple tree; copper nail	137. 12
side of rd., near stone wall, in solid rock; copper nail	154, 24
stamped "152 29 W 1922" Shepaug, 3.3 mi. NW. of, 7.7 mi. S. of New Milford, near small bridge,	151. 556
10 ft. E. of stream, 5 ft. N. of rd., in sunken rock; copper nail	149. 52
From New Milford quadrangle south along New Milford-Danbury highway to Danbury	
brookfield, 0.5 mi. N. of, 6.3 mi. S. of New Milford, opposite end of highway fence, in base of rock bank and near its upper end, in solid	
Brookfield, 0.5 mi. N. of, 6.3 mi. S. of New Milford, opposite end of highway fence, in base of rock bank and near its upper end, in solid rock; copper nail	266. 68
Brookfield, 0.5 mi. N. of, 6.3 mi. S. of New Milford, opposite end of highway fence, in base of rock bank and near its upper end, in solid rock; copper nail	
Brookfield, 0.5 mi. N. of, 6.3 mi. S. of New Milford, opposite end of highway fence, in base of rock bank and near its upper end, in solid rock; copper nail.  Brookfield, 400 ft. N. of crossroads, on W. side of rd., near S. end of concrete retaining wall, in upper surface of wall; standard tablet stamped "302 34 W 1922".  Brookfield, 1.5 mi. S. of, 600 ft. S. of crossroads, on W. side of rd., in concrete culvert; copper nail.	266. 68
Brookfield, 0.5 mi. N. of, 6.3 mi. S. of New Milford, opposite end of highway fence, in base of rock bank and near its upper end, in solid rock; copper nail	266. 68 301. 456
Brookfield, 0.5 mi. N. of, 6.3 mi. S. of New Milford, opposite end of highway fence, in base of rock bank and near its upper end, in solid rock; copper nail	266. 68 301. 456 282. 92

#### DERBY QUADRANGLE

[Latitude 41°15′-41°30; longitude 73°-73°15′]

#### FAIRFIELD AND NEW HAVEN COUNTIES

Leveling in 1922 by R. M. Wilson

From Waterbury quadrangle south along Waterbury-Stratford highway into Bridgeport quadrangle

Naugatuck. on NW. corner of St. Mary's Church, 350 N. Main Street, set vertically in wall; standard tablet stamped "209 54 W 1922"	Feet 209. 054
Naugatuck, at Naugatuck High School, at E. side of door, in front wall, about 4 ft. above ground, set vertically; standard tablet	
stamped "257 55 W 1922"	257.376
Naugatuck, near S. end of borough, in E. face of vault building of	•
Naugatuck Chemical Co., about 2 ft. above ground; standard tablet stamped "180 56 W 1922"	179. 703
Naugatuck, 1.5 mi. S. of, 2.0 mi. N. of Beacon Falls, at T-rd. E., at sharp bend in rd., on NE. corner of concrete bridge, in parapet; cop-	
per nail	173. 49
Beacon Falls, 1.2 mi. N. of, on N. side of rd., in concrete culvert;	100 50
copper nail	160. 76
Beacon Falls, in N. part of town, on W. side of rd., in S. abutment of	•
small concrete bridge over mill race; standard tablet stamped	145 464
"146 57 W 1922"	145. 464
at top of small grade, in solid rock; copper nail	161. 80
Seymour, 2.1 mi. N. of, 150 ft. S. of watering trough, on E. side of	101. 60
rd., in sunken boulder; copper nail.	127. 88
Seymour, 1.1 mi. N. of, at trolley crossing, on E. side of rd., in solid	121. 00
rock; copper nail.	101. 85
Seymour, at front entrance of post office, at E. side of door behind	101. 00
column, in stone step; standard tablet stamped "93 58 W 1922"	93. 033
Seymour, 1.0 mi. S. of, 2.6 mi. N. of Ansonia, at fork of back rd.,	00.000
on W. side of rd., in N. end of outcrop of solid rock; copper nail	62. 92
Ansonia, 1.0 mi. N. of, on W. side of rd., near middle of grade, near	
N. end of large masonry culvert, in capping stone of parapet;	
copper nail	81. 16
Ansonia, on W. side of river, on Holbrook Street between Clarkson	
and Jackson Streets, at front entrance to Holbrook School, on N.	
side of door, in lower stone step; standard tablet stamped "122	
59 W 1922''	121. 628
Ansonia, 0.8 mi. S. of, 0.8 mi. N. of Shelton, at Y-rd., on SE. side	
of Ansonia rd., near S. end of high retaining wall, in capping	
stone under iron railing; copper nail	112. 84
Shelton, at concrete arch bridge over Housatonic River between	
Shelton and Derby, on S. side of W. abutment, in S. end of wing-	
wall parapet, about 4 ft. above sidewalk; standard tablet stamped	
"39 60 W 1922"	38. 655
Shelton, on W. bank of river, at S. end of coal yards, in ledge that	
juts out into river, in drill hole; brass plug, U. S. Corps of En-	
gineers B. M. designated "A 21"	7. 059
Shelton, on Grove Street, at Lafayette School, on N. side of front	
entrance, 2 in. from wall of building, on railing of steps; chiseled	114 17
cross	114. 17
Shelton, 2.6 mi. S. of, 1,400 ft. N. of entrance to State Sanatorium,	
near N. end of trolley switch, on E. side of rd. and tracks, on	00.00
boundary stone; large chiseled cross	92. 33

Shelton, 3.1 mi. S. of, 100 ft. S. of T-rd. W., on W. side of rd., in bank, about 10 ft. above rd. level, on top of large boulder; standard tablet stamped "46 61 W 1922"	Feet 46. 107
Shelton, 4.3 mi. S. of, 6.3 mi. N. of Stratford, 200 ft. S. of rd. forks and of long retaining wall, on W. side of rd., in solid rock; copper	E9 709
Stratford, 5.0 mi. N. of, 50 ft. S. of S. junction of T-rd. W., on W. side of rd., in solid rock; copper nail	52. 708 75. 42
From Naugatuck southeast along Naugatuck-New Haven highway into New Haven quadrangle	
Naugatuck, 1.0 mi. SE. of, in NW. corner of junction of T-rd. S., in rock; copper nail	260. 56
Naugatuck, 2.0 mi. SE. of, at T-rd. E., on W. side of rd., in large concrete culvert; copper nail	322. 67
corner of large concrete culvert, on top of E. parapet; standard tablet stamped "370 63 W 1922"	369. 787
From New Haven quadrangle near Round Hill south along Naugatuck-New Haven highway and back into New Haven quadrangle	
Bethany, 1.0 mi. S. of, at foot of hill, on E. side of rd., at culvert at side of barnyard, in large rock forming wing wall; copper nailBethany, 2.1 mi. S. of, in N. corner of junction of T-rd. E., opposite brick house, at base of corner of stone wall, in large rock; copper	564. 73
nail	549. 62
W. side of rd., 4 ft. E. of stone wall, in outcrop of solid rock; standard tablet stamped "456 65 W 1922"	455. 670
From Danbury quadrangle southeast along Newtown-Bridgeport highway into Bridgeport quadrangle	
Long Hill, 1.1 mi. NW. of, 1.2 mi. S. of Stepney, at rd. fork NE. to Monroe, 50 ft. N. of junction, on E. side of rd., in large rock; stand-	227 222
ard tablet stamped "325 21 W 1922"Long Hill, at NE. corner of intersection of Main and Elizabeth	325. 309
Streets, cemented in large rock; iron pin	412. 13
Trumbull, at fence corner, in top of rock; copper nail  From Danbury quadrangle near Sandy Hook Bridge, over Housatonic River, north-	<b>422.</b> 58
east along Danbury-Watertown-Hartford highway into Waterbury quadrangle South Britain sta., in front of, on E. rail of track	211. 16
South Britain sta., 0.4 mi. N. of, 2.5 mi. S. of Southbury, at abutment of highway bridge over R. R., on W. side of rd. and track, on	211. 10
lower step of wing wall; copper nailSouthbury, 1.1 mi. S. of, at T-rd. W., in root of large maple tree;	199. 60
copper nailSouthbury, 0.4 mi. S. of, in SE. corner of junction of paved T-rd. E.	187. 85
to R. R. sta., 50 ft. W. of house, in sunken rock; standard tablet stamped "268 43 W 1922"	268. 325
Southbury, at forks of main rd. to New Haven, on E. side of rd., 50 ft. N. of N. corner of grass triangle formed by rd. junction, in	
concrete culvert; copper nailSouthbury, 1.4 mi. N. of, at T-rd. S., on E. side of rd., in rock; copper	230. 91
nail	243. 16

#### GILEAD QUADRANGLE

[Latitude 41°30'-41°45'; longitude 72°15'-72°30']

#### HARTFORD, MIDDLESEX, NEW LONDON, AND TOLLAND COUNTIES

#### Leveling in 1923 by R. M. Wilson

From Middletown quadrangle near Pocotopaug Lake northeast along Waterbury-Willimantic highway into Norwich quadrangle

East Hampton, 1.2 mi. E. of, 3.2 mi. SW. of Marlboro, on S. side of	Feet
rd., on heading of small culvert; chiseled cross Marlboro, 1.6 mi. SW. of, at bottom of hill, on N. side of rd., at con-	530. 78
crete bridge over stream, on top of W. wing wall; chiseled square Marlboro, 0.8 mi. SW. of, 150 ft. SW. of small culvert, on SE. side	400. 09
of rd., in front of house, in large rock; chiseled square	581. 18
stone wall, cemented in large rock; standard tablet stamped "508 107 W 1923"	508. 370
Marlboro, at crossroads, in foundation of church, on E. side of building,	000 <b>. 010</b> .
1 ft. S. of S. basement window and at approximately same level as window sill, on vertical face of stone; chiseled cross	512. 92
Marlboro, 0.9 mi. NE. of, in SW. corner of rd. crossing, 50 ft. E. of stream crossing, near corner of stone wall, on highest part of large	
rock; chiseled square	380. 18
Marlboro, 2.2 mi. NE. of, 3.4 mi. SW. of Hebron, at top of long hill,	496 70
on N. side of rd., on large rock; chiseled square————————————————————————————————————	436. 72
rock; chiseled circle	457. 34
Hebron, 2.2 mi. W. of, at rd. forks, on N. side of junction, 10 ft. NW. of corner of stone wall, cemented in large rock; standard tablet	
stamped "370 108 W 1923"	370. 194
of stone wall, about 6 ft. W. of wall, on top of large sunken rock;	
chiseled square	476. 29
Hebron, at W. end of green, on N. side of base of soldiers' monument; standard tablet stamped "542 120 W 1923"	541. 730
Hebron, 1.7 mi. NE. of, 100 ft. E. of crossroads, at top of hill, on S. side	341. 730
of EW. rd., 10 ft. W. of gate, in foundation of stone wall, on top of	
large rock; chiseled square	<b>754. 43</b>
Hebron, 2.3 mi. NE. of, 2.4 mi. SW. of Columbia, in NW. corner of crossroads, on corner stone in base of stone wall; chiseled square.	711. 35
Columbia, 1.0 mi. SW. of, 150 ft. SW. of crossroads, on S. side of rd.,	711. 00
on top of middle capstone of small masonry culvert; chiseled square_	567. 69
Columbia, 0.2 mi. SW. of post office, 80 ft. S. of rd., 50 ft. NW. of stream, at edge of driveway, in front yard of house, in large outcrop	
of solid rock and near its N. end; standard tablet stamped "473 12"	
W 1923"	473. 102
Columbia, at E. end of green, on memorial stone; right-hand corner	
of extreme upper edge of bronze plate, stamped "B. M."Columbia, 1.2 mi. NE. of, 4.4 mi. W. of Willimantic, at sharp bend	518. 48
in rd. at rd. fork N., on W. side of junction, on top of large rock	
embedded in bank; chiseled square	<b>344. 02</b>

Willimantic, 3.5 mi. W. of, in SW. corner of junction of Hebron rd. with main Hartford-Willimantic rd., near fence corner, cemented in sunken rock; standard tablet stamped "265 122 W 1923"	Feet 265. 003
From Saybrook quadrangle near Salem northwest along New London-Hartford highway to Marlboro	
Salem, 1.2 mi. N. of schoolhouse, at foot of small hill, on SW. side of rd., in head wall of concrete culvert; chiseled square	303. 70
SquareColchester, 3.0 mi. SE. of, 1,300 ft. NW. of rd. fork E., 125 ft. NW. of driveway to house, 25 ft. SW. of rd., in pasture land, cemented in	470. 40
large sunken rock; standard tablet stamped "554 140 W 1923" Colchester, 1.9 mi. SE. of, at top of hill, in NW. corner of junction of rd. W., on large rock at corner of stone wall, about 5 ft. above rd.	553. 397
level; chiseled squareColchester, 0.7 mi. SE. of, 100 ft. NW. of rd. forks, on NE. side of rd., at corner of yard of house, 6 ft. SE. of T-corner in wall, at base of	561. 31
wall, in large rock; chiseled square	439. 00
water table of building; standard tablet stamped "458 141 W 1923". Colchester, 1.2 mi. NW. of, at top of hill, on W. side of rd., on large	458. 297
triangular granite rock standing about 2 ft. above ground; chiseled squareColchester, 2.1 mi. NW. of, 100 ft. S. of small culvert, 8 ft. E. of rd.,	426. 85
about 1 ft. above rd. level, on large sloping outcrop of solid rock and near its lower end; chiseled squareColchester, 3.6 mi. NW. of, 4.6 mi. SE. of Marlboro, 450 ft. NW. of	325. 51
R. R. crossing, 150 ft. E. of rd. crossing, 115 ft. NE. of main rd., in pasture land, on top of large sunken boulder, about 1 ft. above ground; standard tablet stamped "294 142 W 1923"	294. 222
of rd., about 15 ft. above rd. level, in base of stone wall, on large rock; chiseled square	428. 02
Marlboro, 2.9 mi. SE. of, at foot of hill near rd. fork E., at SW. corner of bridge over Fawn Creek, on head wall; chiseled square	184. 72
ft. S. of gate in fence, on top of large rock; chiseled square	419. 44
"508 107 W 1923"  Near northeast corner of quadrangle, on Willimantic-Stafford Springs highway	508. 370
Willimantic, 3.0 mi. NW. of county courthouse at, 100 ft. SE. of rd. forks, on E. side of rd., in middle of short concrete section of stone	
retaining wall, on upper surface of wall; chiseled square	289. 23

#### GRANBY QUADRANGLE

[Latitude 41°45′-42°; longitude 72°45′-73°]

#### HARTFORD AND LITCHFIELD COUNTIES

#### Leveling in 1923 by R. M. Wilson

From Hartford quadrangle at a point on Farmington River near North Bloomfield northwest along Hartford-Granby highway to Granby, thence northwest and west along Windsor Locks-Riverton highway into Winsted quadrangle

7	
Tariffville, 1.3 mi. SE. of, 75 ft. S. of forks of main rd., at steel bridge over Farmington River, on NE. corner of N. end of bridge, on bridge seat; chiseled square	Feet 113. 00
Tariffville, 0.4 mi. S. of, at NW. corner of bridge over Farmington River, on bridge seat; chiseled square	
Tariffville, 300 ft. E. of R. R. sta., at large steel bridge over Farmington River, on E. side of roadway, on S. bridge seat; standard tablet stamped "162 181 W 1923"	161. 379
Tariffville, 1.0 mi. N. of, 1.1 mi. S. of Granby Station, 200 ft. W. of schoolhouse, in SW. corner of cross roads, at fence corner, on large sunken rock; chiseled square	
Granby Station, at S. end of sta. building, on NW. corner of concrete	
foundation of R. R. semaphore signal; chiseled square Granby, in center square of town, on red sandstone soldiers' monument, on N. side of base; standard tablet stamped "215 182 W	
Granby, 1.4 mi. W. of, 1.5 mi. E. of West Granby post office, in NW. corner of crossroads, at base of large maple tree, on sunken rock;	214. 540
chiseled square	244. 48
West Granby, 0.8 mi. E. of post office, at top of hill, on S. side of rd., on top of large boulder; chiseled square	447. 87
West Granby, 700 ft. E. of store and post office, on N. side of rd., in large outcrop of rock; standard tablet stamped "375 183 W 1923" West Granby, 30 ft. S. of Luther & George's store, at E. side of rd., in	374. 197
small grass plot, on top of sunken rock; chiseled square West Granby, 1.0 mi. W. of, at rd. forks to S. over bridge, near NE.	396. 58
corner of bridge, on corner stone of bridge seat, 1.5 ft. below rd. level; chiseled square	485. 94
of house of Mr. Parmelee, 100 ft. W. of rd. fork N., 15 ft. NE. of corner of stone wall between two branches of rd., just inside pasture land, on sunken rock; chiseled square	650. <b>97</b>
bridge over small stream, in pasture land, in large sunken rock; standard tablet stamped "835 184 W 1923"	83 <b>4. 379</b>
East Hartland, 1.0 mi. SE. of, in SW. corner of crossroads, 30 ft. W. of main rd., 10 ft. N. of stone wall, on large granite rock; chiseled	1 107 91
East Hartland, 20 ft. N. of NW. corner of Society Hall, on S. side of rd., near base of large maple tree, in sunken rock; standard tablet	
stamped "1202 185 W 1923"	1, 201. 534
rd., on sunken rock; chiseled crossEast Hartland, 0.5 mi. W. of, 1.9 mi. E. of Hartland, at highest part	1, 201. 61
of rd., on N. side of rd., on solid ledge; chiseled square	1, 229. 68

Hartland, 0.5 mi. E. of, about in middle of long steep hill, at upper end of more gradual slope 150 ft. SW. of small cabin, 10 ft. N. of rd.,		Feet
on sunken rock; chiseled square		785. 09 486. 34
head wall of small concrete culvert; chiseled square		
Hartland, 1.0 mi. W. of, about in middle of long, steep hill, 50 ft. W.		566. 264
of rd. fork N., 5 ft. N. of rd., on solid ledge; chiseled square Hartland, 1.5 mi. W. of, near top of hill, 75 ft. SW. of crossroads,		868. 53
10 ft. E. of stone wall, in large granite rock; chiseled square Hartland, 2.5 mi. W. of, 2.8 mi. NE. of Riverton, 50 ft. NE. of rd. fork to N., on N. side of rd., near edge of small pond, at fence line,		125. 70
in rock; standard tablet stamped "969 187 W 1923"		968. 169
From Winsted quadrangle at point on Morgan River southeast along Winsted- Hartford highway into Hartford quadrangle		
New Hartford, 1.8 mi. NW. of, 200 ft. NW. of large culvert at rd. crossing, 30 ft. S. of rd., on top of large rock; chiseled squareNew Hartford, in N. part of town, at steel bridge over river near dam,		427. 41
on N. side of W. abutment, on granite corner stone; chiseled square. New Hartford, 1,000 ft. SE. of R. R. sta., at SE. end of steel R. R. trestle, on E. side of track, about 3 ft. below track level, on sand-		419. 64
stone bridge seat; standard tablet stamped "404 191 W 1923"  New Hartford, at steel R. R. trestle, on base of first support from SE. end, on NE. corner of sandstone block, about 2 ft. above ground;		404. 171
chiseled squareNew Hartford, 1.2 mi. SE. of, 150 ft. NW. of R. R. crossing, on W.		386. 14
side of rd., in root on SE. side of 24-in. elm tree; copper nail		374. 09
N. end of rock cut, on solid granite rock; chiseled square		358. 12
small brook, 6 ft. E. of stone wall in pasture land, on sunken rock; standard tablet stamped "327 192 W 1923"Canton, about 2.1 mi. NW. of, 100 ft. S. of crossroads, at Cherry		326. 944
Brook sta., 20 ft. S. of gate to field, at E. side of Collinsville rd., on rock at fence line; chiseled square		331. 28
Canton, 1.0 mi. NW. of, in SE. corner of crossroads, 8 ft. E. of end of stone wall, on large rock in base of wall; chiseled square		398. 34
Canton, in E. part of town, 530 ft. W. of R. R. crossing, 30 ft. N. of rd., about 15 ft. above rd. level, in side hill pasture, on outcrop of		
solid ledge; standard tablet stamped "357 193 W 1923"	į	356. 621
square	:	295. 12
Avon, 0.4 mi. W. of, near W. end of factory grounds, on S. side of rd., on E. end of head wall of concrete culvert; chiseled squareAvon, 150 ft. NW. of R. R. crossing, on E. end of lower front step of	:	215. 94 <sup>°</sup>
church; chiseled square		200. 81

Avon, 250 ft. E. of R. R. crossing, on N. side of rd., on concrete top of E. end of stone wall; chiseled square	Feet 201. 28
Avon, 0.9 mi. E. of, at NW. corner of crossroads, on top of red- sandstone guard rock at corner; chiseled square	185. 83
head wall of large concrete culvert; standard tablet stamped "198 109 W 1923"	198. 281
Avon, 2.3 mi. E. of, at highest point in rd. between Avon and Hartford, about in middle of long rock cut, on N. side of rd., about 2 ft.	
above rd. level, on bench of solid rock; chiseled circle	667. 31
Avon, 3.5 mi. SE. of, 6.5 mi. W. of Hartford, at E. end of level tangent, on rd. directly opposite rd. fork to S., about 2 ft. above rd.	448. 73
level, on bench of solid rock; chiseled square	387, 90
of flight leading to house, 3 in. NW. of iron railing post; chiseled squareAvon, 4.4 mi. SE. of, 5.5 mi. W. of Hartford, 1,000 ft. E. of cross-	177. 52
roads, at foot of hill, on top of SE. wing wall of concrete culvert; standard tablet stamped "159 110 W 1923"	159. 305
From crossroads 1.0 mile east of Avon south along Northampton-New Haven highway into Meriden quadrangle	
Avon, 1.5 mi. SE. of, 1.0 mi. S. of crossroads, on rd. to Farmington, on E. side of rd., on heading of small concrete culvert; chiseled square.  Avon, 2.9 mi. SE. of, 4.1 mi. N. of Farmington, 1,000 ft. SE. of ceme-	224. 03
tery on top of hill, on W. side of rd., 100 ft. N. of small culvert, on large flat rock 2 ft. W. of right-of-way fence; chiseled square  Farmington, 3.0 mi. N. of, at rd. fork SE., in pointed grass plot between the two rds, shout 100 ft. S. of their innerties in large supplies.	196. 75.
tween the two rds., about 100 ft. S. of their junction, in large sunken rock; standard tablet stamped "189 82 1923"	189. 330
side of rd.; chiseled cross	183. 64
GRANVILLE QUADRANGLE	
[Latitude 42°-42°15'; longitude 72°45'-73°]	
HARTFORD COUNTY	
Leveling in 1934 by R. G. Clinite	
From Connecticut-Massachusetts State line near North Hollow southwest along valley road into Granby quadrangle	
North Hollow, 150 ft. N. of steel bridge over Hubbard Brook, 120 ft. W. of Newgate Coon Club, 50 ft. S. and 35 ft. E. of rd. forks, in shelf in S. slope of ledge; standard tablet stamped "C 192 560 1934" Reference mark, 9 ft. S. of tablet, in root on S. side of 38-in. elm tree;	Feet 560. 175
rail spike	555. <b>7</b> 5
North Hollow, 1.3 mi. SW. of, 1.7 mi. NE. of Hartland, on E. side of rd., in root on W. side of 30-in. maple tree; copper nail and washer. Hartland, 0.9 mi. N. of junction of valley rd. and EW. highway at,	648. 72
10 ft. NW. of center line of rd., on top of boulder; chiseled square.	537.06

279. 482

255.99

157. 14

226. 455

188. 50

330. 61

62. 141

133.88

93. 51

87.713

GUILFORD QUADRANGLE	21
From Connecticut-Massachusetts State line near South Mountain southwest along roads into Granby quadrangle	
East Hartland, 3.5 mi. NE. of, 2.8 mi. SE. of Granville Center (Mass.), at junction of abandoned rd. SW., 15 ft. W. of center line of rd., at corner of stone fence, in W. side of 14-in. elm tree; rail spikeEast Hartland, 2.4 mi. NE. of, 50 ft. W. of abandoned school, at junction of rds. to SE. and SW., 20 ft. S. of center of junction, in	Feet 634. 87
root on NW. side of 14-in. pine tree; copper nail and washer East Hartland, 1.1 mi. NE. of, 55 ft. SW. of brook, 12 ft. W. of rd., in root on NW. side of 10-in. birch tree; copper nail and washer	959. 09 989. 34
GUILFORD QUADRANGLE	•
[Latitude 41°15′-41°30′; longitude 72°30′-72°45′;	
MIDDLESEX AND NEW HAVEN COUNTIES	
Leveling in 1923 by R. M. Wilson	
From New Haven quadrangle northeast along New Haven-Hartford highway into Middletown quadrangle	
Northford, 3.0 mi. NE. of, 6.2 mi. SW. of Durham, at rd. fork E. to Durant Farm, on E. side of main rd. and N. side of branch rd., at fence corner, on large rock; chiseled cross	Feet 321. 39
Durham, 4.5 mi. SW. of, on NW. side of rd., at concrete culvert, cemented in railing; copper nail.	318. 91
Durham, 3.7 mi. SW. of, 1,000 ft. NE. of small bridge over creek, 300 ft. SW. of farmhouse, on NW. wing wall of concrete culvert; stand-	

ard tablet stamped "280 87 W 1923".....

Durham, 2.6 mi. SW. of, at rd. fork E., in front of house, on SW. end of concrete retaining wall; chiseled cross\_\_\_\_\_\_

Durham, 1.8 mi. SW. of, at W. end of straight stretch of rd. across Durham Meadows, at rd. forks, in retaining wall between two rds. and 10 ft. NE. of its S. end, cemented in top surface of wall; copper nail

Durham, at S. end of main street through Durham Center, on E. side of rd., at rd. forks, cemented in large sunken granite boulder; standard tablet stamped "227 88 W 1923"\_\_\_\_\_\_

Durham, at S. end of bridge between Durham and Durham Center, on W. side of rd., just S. of iron end post of railing, on last capstone; chiseled cross\_\_\_\_\_\_

Durham, 1.0 mi. N. of, at top of hill, in NW. corner of crossroads,

Higganum, 150 ft. NW. of town hall and post office, at SE. corner of concrete highway bridge, on top of wing wall; standard tablet stamped "62 99 W 1923"\_\_\_\_\_\_\_

Higganum, 1.0 mi. SE. of, 1.9 mi. NW. of Haddam, opposite "The Cabin Tea House", on W. side of rd., on W. end of large sunken rock bearing bronze memorial plate on its front; chiseled knob...

Haddam, 0.6 mi. NW. of, near foot of long hill, at N. end of stone wall, on W. side of rd., about 5 ft. above rd. level, on sloping surface of solid rock; chiseled square\_\_\_\_\_\_

Haddam, at Brainerd Public Library, on N. side of building, on granite sill of W. basement window; standard tablet stamped "88 100 W 1923"\_\_\_\_\_\_

cemented in sunken rock; copper nail\_\_\_\_\_\_

Near northeast corner of quadrangle, on Middletown-Saybrook highway

#### HARTFORD QUADRANGLE

[Latitude 41°45′-42°; longitude 72°30′-72°45′]

#### HARTFORD AND TOLLAND COUNTIES

#### Leveling in 1923 by R. M. Wilson

Hartford, 1.7 mi. W. of W. city limits, 5.2 mi. SE. of Avon, in SW. corner of crossroads, in root on N. side of large elm tree; copper nail—Hartford, about 0.1 mi. E. of W. city limits, on N. side of junction of Albany and Bloomfield Avenues, in top of granite property-line	Feet 156. 10
boundary post; copper nail————————————————————————————————————	110. 53
"58 111 W 1923"	57. 701
U. S. C. & G. S. B. M. designated "F 8"	36. 818
Hartford, at N. entrance to post office, on E. side of steps, about 2 ft. above sidewalk; upper surface of granite guard block	57. 61
U. S. C. & G. S. B. M. designated "Tidal 5"	52. 18 <b>2</b>
From Hartford northwest along Bloomfield Avenue and Granby-Hartford highway into Granby quadrangle	
Bloomfield, 1.7 mi. S. of, 1.8 mi. NW. of junction of Albany and	
Bloomfield Avenues at Hartford, 200 ft. NW. of short steep grade,	
on E. side of rd., in root on N. side of first tree in line N. of driveway	
to house; copper nail	135. 54
Bloomfield, 0.9 mi. S. of, 200 ft. N. of rd. forks, on W. side of rd., on	100. 01
top of N. wing wall of large concrete culvert; chiseled square	110. 18
Bloomfield, at front entrance of Prosser Library, at S. side of doorway,	110. 10
close to wall of building, on guard stone of steps; standard tablet	
stamped "126 179 W 1923"	125. 769
Bloomfield, 1.2 mi. N. of, 1,150 ft. N. of culvert and crossroads, 60 ft.	120. 100
S. of cross fence, 20 ft. E. of rd., on sunken rock; chiseled square.	141. 16
Bloomfield, 2.9 mi. N. of, 200 ft. N. of rd. fork E., 50 ft. S. of culvert,	111. 10
on W. side of rd., at S. end of guard rail fence, in top of large stump;	
copper nail.	155. 41
Bloomfield, 3.7 mi. N. of, 150 ft. NW. of R. R. crossing, in pasture	100. 11
land, on top of large granite boulder projecting about 3 ft. above	
ground; standard tablet stamped "201 180 W 1923"	200. 636
	200. 000
From Tolland quadrangle west along Stafford Springs-Thompsonville highway to Thompsonville	
Hazardville, 200 ft. N. of R. R. sta., 340 ft. N. of rd., on W. side of	
R. R. tracks, on top of N. wing wall of concrete coal dump; chiseled	
square	166. 02
Hazardville, at NE. corner of Main and Maple Streets, at front en-	
trance of Hazardville Institute, on W. end of doorsill; standard	
tablet stamped "165 176 W 1923"	$165. \ 197$
Hazardville, 1.4 mi. NW. of junction of Main and Maple Streets at,	
2.6 mi. E. of R. R. sta. at Thompsonville, 100 ft. W. of rd. fork N.,	
on N. side of rd., on E. end of head wall of bridge over Freshwater	
Brook; chiseled square	132. 11
Thompsonville, 1.6 mi. E. of, 300 ft. E. of end of long tangent in rd.,	
200 ft. E. of house occupied by Mr. Bostick, on N. side of rd.; top	
of valve nut of fire hydrant	139. 62
U. S. C. & G. S. B. M. designated "S 8"	75. 856

#### MERIDEN QUADRANGLE

[Latitude 41°30′-41°45′; longitude 72°45′-73°]

#### HARTFORD, LITCHFIELD, MIDDLESEX, AND NEW HAVEN COUNTIES

#### Leveling in 1923 by R. M. Wilson

# From New Haven quadrangle north along New Haven-Northampton highway into Granby quadrangle

Cheshire, in N. part of town, about 100 ft. NE. of rd. fork W. to Waterbury, on E. side of rd., on top of large boulder; chiseled cross	Feet 279. 40
Cheshire, 1.9 mi. N. of, 3.2 mi. S. of Milldale, about opposite State reformatory, at rd. fork E., in root of large tree; copper nail	203. 09
end of SE. concrete wing wall of overhead bridge; standard tablet stamped "163 72 W 1923"	162. 648
driveway to house, on large boulder; chiseled cross Milldale, 0.8 mi. S. of, in SE. corner crossroads, at fence corner, in	235. 45
large rock; chiseled cross	188. 12
stamped "173 73 W 1923"	173. 141
EW. rd., on railing of small concrete bridge; copper nail Plantsville, 0.2 mi. S. of, at rd. fork E., at E. side of new granite water	130. 81
trough, in E. side of iron rim of new manhole; chiseled squarePlantsville, 300 ft. E. of R. R. sta., 1.0 mi. S. of Southington, at NW.	153. 53
corner of bridge over brook, in retaining wall, in piece of broken grindstone in top course; chiseled cross	138. 75
Southington, in center of square opposite town hall, on E. side of upper step of large granite memorial drinking fountain; standard tablet stamped "168 80 W 1923"	167. 648
Southington, 1.5 mi. N. of, at rd. fork W., at E. side of rd. and on N. side of driveway to house, on small concrete culvert; chiseled cross.	157. 11
Southington, 2.8 mi. N. of, 3.5 mi. S. of Plainville, 500 ft. W. of main rd., on S. side of branch rd. W., on railing of small concrete bridge;	
chisel cut.  Plainville, 2.3 mi. S. of, at Queen Street School, on S. side of building,	153. 41
on E. end of concrete sill of W. low window; chiseled crossPlainville, 1.2 mi. S. of, 600 ft. S. of rd. forks, on W. side of rd., in	179. 22
heading of small concrete culvert; chiseled cross	180. 93 185. 219
Plainville, in NE. corner of intersection of East Main Street and East Street, on top of red-sandstone milepost; chiseled cross	192, 60
Plainville, 1.5 mi. N. of, 2.6 mi. S. of Farmington, on E. side of rd., on top of red-sandstone milepost; chiseled cross	202. 52
Farmington, 1.2 mi. S. of, opposite highest part of Rattlesnake Moun-	202. 32
tain, across rd. from large frame farmhouse, on E. side of rd., 30 ft. S. of gate, in wall, on large stone; chisel cut	193. 77
under portico, cemented in red sandstone; standard tablet stamped "245 81 W 1923"	244. 899
Farmington, 1.7 mi. N. of, on E. side of rd., on heading of small culvert; chiseled cross.	180. 71

# From Waterbury quadrangle east along Waterbury-Middletown highway into Middletown quadrangle

Waterbury, 3.0 mi. E. of, 4.0 mi. W. of Marion, near lower end of long steep curve in rd., 100 ft. SW. of small culvert, on N. side of rd., in	Feet
large sunken rock; standard tablet stamped "557 75 W 1923" Marion, 2.3 mi. W. of, in NE. corner of crossroads, in large rock;	557. 133
Chisel cut	640. 15
side of rd., about 4 ft. above rd. level, cemented in solid rock; copper nail	731. 99
Marion, 0.5 mi. W. of, opposite rd. fork NE. across trolley tracks, on S. side of rd., about 5 ft. above rd. level, cemented in solid rock; standard tablet stamped "316 74 W 1923"	315. 714
Marion, 0.5 mi. E. of, 1.2 mi. W. of Milldale, on top of NW. wing wall of concrete culvert over stream; chiseled cross	140. 57
Milldale, 0.5 mi. W. of, at R. R. bridge over highway, on S. side of rd., in W. retaining wall of bridge, on concrete footing of lower end;	110.0.
chiseled cross	154. 12
line, 1,500 ft. W. of crossroads, on N. side of rd., on top of large boulder; chiseled crossMilldale, 1.9 mi. E. of, 3.2 mi. W. of Meriden, in SE. corner of cross-	278. 71
roads, in root of maple tree; copper nail	339. 50
Meriden, 2.6 mi. W. of, 600 ft. E. of rd. fork N. at top of hill, on N. side of rd., in solid rock; standard tablet stamped "419 77 W 1923".  Meriden, 2.0 mi. W. of, at Spruce Street et trance to Hubbard Park, 30 ft. SE. of SW. end of footbridge, in lawn, on large rock; chiseled	418. 715
cross	289. 88
W. end of top of large concrete retaining wall; chiseled cross  Meriden, on Cook Avenue, on W. side of main building of Meriden Hospital, under portico of doctors' entrance, at top of steps, on	132. 42
granite sill; standard tablet stamped "147 78 W 1923"	147. 263
"144 79 W 1923"	143. 947
cemented in stone slab; standard tablet stamped "187 B 7 1923" Meriden, at NE. corner of Pearl and E. Main Streets, 11.7 ft. W. of	187. 086
fire plug, on curbstone; chiseled cross	351. 09
retaining wall, at E. side of gate to factory warehouse, on sand- stone slab of culvert; standard tablet stamped "293 94 W 1923"	292. 492

#### MIDDLETOWN QUADRANGLE

[Latitude 41°30′-41°45′; longitude 72°30′-72°45′]

#### HARTFORD AND MIDDLESEX COUNTIES

#### Leveling in 1923 by R. M. Wilson

# From Guilford quadrangle north along New Haven-Hartford highway into Hartford quadrangle

The state of the s	
Durham, 2.7 mi. N. of, 3.4 mi. SW. of municipal building at Middle-	
town, 300 ft. NW. of outlet end of Dooley Pond, in SW. corner of crossroads, cemented in red-sandstone ledge; standard tablet	Feet
stamped "253 89 W 1923"	252. 803
Middletown, 2.2 mi. SW. of, at front entrance of Long Hill School,	202. 000
about 5 in. N. of wall of building, on S. end of lower E. step;	
chiseled cross	174, 53
Middletown, 1.4 mi. S. of, 200 ft. S. of corner of Durham Avenue and	111.00
Norfolk Street, at S. end of pond, on NE. corner of small concrete	
bridge; chiseled cross	78. 67
Middletown, on SW. corner of Pleasant and Main Streets, at W.	
entrance of South Congregational Church, on W. side of door, close	
to wall of building, on second step; standard tablet stamped "57	
90 W 1923''	56. 711
Middletown, at S. side of entrance of municipal building, on top step;	
standard tablet stamped "52 91 W 1923"	52. 383
Middletown, at N. end of Main Street, at W. entrance of Catholic	
church, at W. side of door, on top of step; standard tablet stamped	
"54 92 W 1923"	54. 214
U. S. C. & G. S. B. M. designated "Tidal 8"	10. 907
Cromwell, 300 ft. NE. of R. R. sta., 7 ft. W. of granite monument	
inside iron guard fence, on red-sandstone well slab; bottom of letter	
"T"	29. 37
Cromwell, 200 ft. N. of post office, on E. side of rd., on concrete retain-	
ing wall 10 ft. from its lower end; chiseled cross	<b>35. 45</b>
Cromwell, 1.4 mi. N. of post office, at rd. fork W., in root on N. side of	
large maple tree at corner; copper nail	140. 68
Cromwell, 1.8 mi. N. of, 3.4 mi. S. of Rocky Hill, at SW. entrance of	
Plains School, at S. side of door, on top step; standard tablet stamped	147 100
"147 95 W 1923"	147. 138
on W. side of rd., in solid rock; chiseled cross	191, 26
Rocky Hill, at Center School, at N. side of NE. entrance, in concrete	191. 20
coping; standard tablet stamped "107 96 W 1923"	106. 895
Rocky Hill, 1.5 mi. N. of, 2.1 mi. S. of Wethersfield, 200 ft. S. of R. R.	100. 030
crossing, at Rocky Hill-Wethersfield town line, on top of NW. wing	
wall of highway bridge; copper nail	25. 50
Wethersfield, 1.1 mi. S. of, at SW. corner of crossroads, in heading of	20.00
concrete culvert; copper nail	23, 56
Wethersfield, at NW. corner of Main and Church Streets, at N. side	
of entrance of Masonic Building, on W. end of lower concrete step;	
standard tablet stamped "45 97 W 1923"	44. 640
Wethersfield, 1.4 mi. N. of, 2.8 mi. S. of post office at Hartford, 100 ft.	
S. of Wethersfield-Hartford town line, E. of Hartford Avenue, in	
center of E. concrete wall of Valley R. R. bridge over Folly Brook, 6	
ft. N. of S. end of wall; copper bolt	30. 40

Hartford, 1.9 mi. S. of post office, near corner of Wethersfield Avenue and Bodwell Street, at SE. corner of smaller building of Henry C. Dwight School, on concrete water table, about 3 in. above ground; chisel cut	Feet 58. 13
Gilead quadrangle	
Meriden, 3.3 mi. E. of, 5.6 mi. W. of municipal building at Middletown, at low end of S-bend in rd., on S. side of rd., on rock projecting from cut bank; chiseled cross	465. 05
Middletown, 4.4 mi. W. of, at W. end of fill over which rd. crosses Mount Higby Reservoir, near W. end of S. railing of concrete culvert; copper nail	367. 57
Middletown, 3.6 mi. W. of, at crossroads, 15 ft. SW. of corner of house, in large flat rock; standard tablet stamped "379 93 W 1923"	378. 700
Middletown, 3.1 mi. W. of, at top of hill, on N. side of driveway to house, on large rock; chiseled cross	340. 34
side of branch rd., on S. side of small culvert; chiseled cross	109. 91
highway, on second capstone from bottom; chiseled cross Portland, at E. abutment of R. R. bridge over Connecticut River	34. 56
between Middletown and Portland; SW. corner of bridge seat, U. S. C. E. B. M. designated "A 36"	32. 929
rd., on culvert, on middle of upper S. edge of sandstone corner slab; chiseled cross	47. 05
Portland, 2.1 mi. E. of, 2.9 mi. W. of Cobalt, at top of long hill, opposite rd. fork N., on S. side of rd., about 10 ft. above rd. level, cemented in solid rock; standard tablet stamped "196 104 W 1923" Cobalt, 1.3 mi. W. of, about 300 ft. SW. of R. R. tracks, 75 ft. SW. of rd. forks, at point where rd. makes sharp grade turn through rock	196. 011
cut, on S. side of rd., at SW. end of cut, cemented in solid rock; copper nail	167. 37
squareCobalt, 0.5 mi. W. of, at top of hill, on NW. side of rd., at N. end of	263, 66
granite retaining wall, on S. end of lower granite step; chiseled square	305. 96
Hampton rd., in large rock; standard tablet stamped "230 105 W 1923"	230. 202
highway bridge over R. R., on top of highest part of solid granite outcrop; chiseled square	378. 68
East Hampton, 1.0 mi. W. of, 80 ft. E. of rd. fork N., on N. side of rd., on E. end of upper edge of long flat rock; chiseled knobEast Hampton, 0.5 mi. N. of post office, in NE. corner of crossroads,	436. 87
at E. end of front steps of Swedish church, on top surface of granite end block; standard tablet stamped "487 106 W 1923"	486. 458

From Guilford quadrangle northwest along Old Saybrook-Hartford highway to Middletown	
<ul> <li>Higganum, 1.5 mi. NW. of, at rd. fork S., 200 ft. W. of concrete culvert, in top of large sunken rock; copper nail</li></ul>	Feet 172. 27
chiseled cross Middletown, 3.2 mi. SE. of, at rd. fork N. about 30 ft. E. of main rd., 25 ft. N. of house, in outcrop of solid rock; standard tablet stamped	361. 64
"347 98 W 1923"	347. 202
cross	212. 08
chiseled cross	182. 96
MOOSUP QUADRANGLE	
[Latitude 41°30′-41° 45′; longitude 71° 45′-72°]	
NEW LONDON AND WINDHAM COUNTIES	
Leveling in 1923 by R. M. Wilson	
From Putnam quadrangle southwest along Worcester-Groton highway into Norwich quadrangle	•
Wauregan, 0.5 mi. SE. of post office, 150 ft. SE of schoolhouse, 40 ft. NW. of frame house, 100 ft. N. of rd. forks, at edge of school yard, on solid ledge; standard tablet stamped "253 149 W 1923" Wauregan, in front of schoolhouse, 10 ft. S. of steps to main (W.) entrance, at edge of rd., on small ledge; chiseled cross, State	Feet 253, 204
B. M. 14	250. 22
ft. S. of stone wall, on large flat rock; bottom of chiseled square Central Village, 0.5 mi. S. of R. R. crossing, in S. part of town, 150 ft. S. of rd. fork E. to Moosup, at end of small mill pond, on top of	184. 94
SE. wing wall of concrete culvert over canal; chiseled square Central Village, 1.4 mi. S. of R. R. erossing at, 1.4 mi. W. of Moosup, 2.1 mi. N. of St. Paul's Church at Plainfield, 20 ft. W. of R. R. crossing, 2 ft. S. of rail, at cattle guard, on flat rock; chiseled square,	178. 66
U. S. C. & G. S. B. M. 36	199. 29
squarePlainfield, 100 ft. SE. of St. Paul's Church, 500 ft. NE. of Plainfield Grammar School, 10 ft. W. of corner of stone wall, 15 ft. E. of rd.,	310. 83
in solid ledge; standard tablet stamped "203 150 W 1923"	202. 871
Plainfield, at St. Paul's Church, on SE. corner of first step of main entrance; chiseled cross, State B. M. 11	201. 15
large rock; chiseled square	158. 66

Plainfield, 1.4 mi. SW. of, 325 ft. SW. of center line of junction of branch rd. W., on SE. side of rd., about 10 ft. above rd. level, near	Feet
stone wall, in large rock; standard tablet stamped "189 151 W 1923".  Plainfield, 2.5 mi. SW. of, 150 ft. E. of R. R. crossing, on E. side of	188. 637
branch rd., 100 ft. S. of gate in stone wall, in bank of small gravel	
pit, on large rock; chiseled square	156. 71
Plainfield, 2.5 mi. SW. of, 4.1 mi. NE. of Slater Library at Jewett City, on NE. side of R. R. crossing, on base of crossing sign; chiseled	
cross, State B. M. 10	153. 93
Jewett City, 2.6 mi. NE. of, at rd. fork N., on W. side of main rd., on	
E. side of branch rd., 10 ft. E. of corner of stone wall, about 10 ft. above rd. level, in large sunken rock; standard tablet stamped	
"165 152 W 1923"	164. 875
Jewett City, 1.2 mi. NE. of, 200 ft. S. of bridge over R. R., 30 ft. E.	111 09
of rd., at small dam, on S. gate wall of N. spillway; chiseled square Jewett City, 600 ft. SE. of Main Street, on NE. side of School Street,	111, 02
on third granite step from bottom, at SE. entrance of Jewett City	
school; standard tablet stamped "125 153 W 1923"	125. 393
common corner of grounds of Jewett City Savings Bank and Slater	
Library, at edge of sidewalk; highest point of square granite pyramid-	
topped post projecting about 2 ft. above sidewalk	119. 53
rd. to Lisbon sta.; top of small granite post	104. 95
Jewett City, 1.7 mi. S. of, at top of hill, on W. side of rd., about 2 ft.	
above rd. level, on E. end of large outcrop of solid rock, in line with right-of-way wall, on small step of vertical end of outcrop; chiseled	
square	195. 13
NEW HAVEN QUADRANGLE	
[Latitude 41°15′-41°30′; longitude 72°45′-73°]	
NEW HAVEN COUNTY	
Leveling in 1922 and 1923 by R. M. Wilson	
From New Haven northwest along New Haven-Naugatuck highway into Derby quadrangle	
U. S. C. & G. S. B. M. designated "U 3"	Feet 28. 110
New Haven, 2.1 mi. NW. of city hall, near Westville district, on	
Whalley Avenue bridge over West River, on S. side of street, near NE. corner of base of second parapet post from E. end of bridge,	
set flush with sidewalk; standard tablet stamped "18 66 W 1922"	17. 853
New Haven, 4.9 mi. NW. of, 150 ft. S. of T-rd. E., on E. side of rd., at	004 40
point where rd. runs close to stream, in solid rock; copper nail New Haven, 5.8 mi. NW. of, at Y-rd. S., near SW. corner of grass	224. 40
triangle formed by junction, 3 ft. N. of end of stone wall, in sunken	
rock; copper nail[Line jogs into Derby quadrangle.]	393. 56
Bethany, at town hall, at N. side of S. entrance, in concrete coping	
of foundation; standard tablet stamped "637 64 W 1922"	637. 127
Bethany, 1.1 mi. N. of, in NW. corner of crossroads, near end of culvert, in sunken rock; copper nail	730. 65
Bethany, 2.3 mi. N. of, 4.7 mi. SE. of Naugatuck, at T-rd. E., at	
corner of stone wall, in stone step; copper nail	497. 37

From New Haven north along New Haven-Northampton highway into Meriden quadrangle	
U. S. C. & G. S. B. M. designated "T 3"	Feet 24. 954
New Haven, 2.5 mi. NW. of post office, 3.8 mi. SW. of city hall corner at Centerville, on Pine Street at a point 200 ft. W. of Dixwell Avenue, at W. side of front entrance of Pine Street School, in granite step; standard tablet stamped "66 67 W 1923"	65. 448
section of Mathers Street and Dixwell Avenue, on fire hydrant;	70.04
highest part of valve nut Centerville, 0.9 mi. SW. of city hall corner, 125 ft. W. of R. R. bridge	79. 64
over highway, in open field, in large flat cut stone; chisel mark Centerville, 500 ft. W. of fountain at city hall corner, at W. side of front entrance to Centerville School, cemented in concrete step;	85. 24
standard tablet stamped "72 68 W 1923"  Centerville, 1.2 mi. N. of city hall corner, 1.1 mi. S. of Mount Carmel, on E. side of rd., on S. end of lower front step of brick church, in	72. 051
red sandstone; chiseled cross Mount Carmel, 0.5 mi. N. of, opposite rd. fork W. under R. R. tracks,	94. 40
on E. side of rd., about 40 ft. N. of S. end of ledge, cemented in solid rock; standard tablet stamped "119 69 W 1923"	119. 166
rock of retaining wall; chiseled cross	123. 20
stamped "120 70 W 1923".  Cheshire, 2.2 mi. S. of, 1.0 mi. E. of Brooks Vale, 40 ft. S. of crossroads, 15 ft. E. of main rd., in base of stone wall, on large rock;	119. 774
chiseled cross	156. 75
heading of concrete culvert; copper nailCheshire, at town hall, just S. of main front entrance, in foundation;	158. 55
standard tablet stamped "262 71 W 1923"	261. 843
From New Haven northeast along New Haven-Middletown highway into Guilford quadrangle	
U. S. C. & G. S. B. M. designated "U 3"	28. 110
flagstone base of drinking fountain; chiseled cross New Haven, 2.2 mi. NE. of, 2.0 mi. SW. of main highway crossing at Montowese, 1,000 ft. SW. of bridge under R. R. tracks, on NE. abutment of concrete bridge over Quinnipiac River; standard	22. 77
tablet stamped "12 84 W 1923"	11. 821
"65 84 W 1923"  Montowese, 1.9 mi. NE. of main highway crossing at, 3.3 mi. SW. of Northford, 200 ft. SW. of crossroads, at North Hill School, on E. end of lower N. step close to foundation of building; chisel	64. 821
mark	119. 98

SPIRIT LEVELING, IN CONNECTICUT, 1922 TO 1935	
Northford, 2.2 mi. SW. of, at cross roads, on SE. side of main rd., cemented in railing of concrete culvert; copper nail	Feet 117. 48
Northford, 1.2 mi. SW. of, near foot of steep hill, in NW. corner of	
crossroads, on highest part of granite boulder; chiseled cross	111. 99
tablet stamped "170 85 W 1923"	169. 680
(reported June 28, 1933, as covered by grading)	185. 12
Northford, 1.7 mi. NE. of, on SE. side of rd., cemented in concrete railing of large culvert; copper nail	211. 93
standard tablet stamped "272 86 W 1923"	271. 702
NEW LONDON QUADRANGLE	
[Latitude 41°15′-41°30′; longitude 72°-72°15′]	
NEW LONDON COUNTY	
Leveling in 1923 by R. M. Wilson	
From Saybrook quadrangle east along New Haven-Providence highway to New London	
East Lyme, 1.6 mi. W. of, on S. side of rd., opposite house, between rd. and old trolley grade, at foot of hill, on top of large boulder; chiseled square	Feet 98. 53
10 ft. N. of main rd., on E. side of branch rd., at base of stone wall, in large rock; chiseled square	96. 64
In large rock, chiseled square	90. UT

East Lyme, 1.6 mi. W. of, on S. side of rd., opposite house, between rd. and old trolley grade, at foot of hill, on top of large boulder; chiseled square	Feet 98. 53
East Lyme, 0.8 mi. W. of, at rd. fork N., 300 ft. E. of country store,	
10 ft. N. of main rd., on E. side of branch rd., at base of stone wall,	06 64
in large rock; chiseled squareEast Lyme, 600 ft. N. of crossroads, 100 ft. E. of concrete bridge over	96. 64
Great Brook, 15 ft. N. of rd., about 5 ft. above rd. level, on W. slope	
of granite outcrop; standard tablet stamped "51 118 W 1923"	50. 735 °
East Lyme, 1.5 mi. E. of, 0.5 mi. E. of bridge over Niantic River, on S.	
side of rd., on W. side of lane, about 5 ft. NE. of corner of stone wall,	0.4.40
at edge of rd., in large rock; chiseled square	84. 40
East Lyme, 2.6 mi. E. of, 4.5 mi. W. of city hall at New London, 1,000	
ft. E. of crossroads, on N. side of rd., 20 ft. E. of gate, at base of stone wall, on top of large rock; chiseled square	45. 74
New London, 4.0 mi. W. of, 1,000 ft. E. of crossroads, 300 ft. E. of	10. 11
small rock-covered hill, on N. side of rd., in large rock; standard	
tablet stamped "107 W 1923" (reported in 1924 as destroyed)	107. 295
New London, 2.9 mi. W. of, 300 ft. W. of cemetery, on S. side of rd.,	
at edge of rd., on large rock; chiseled square	39. 45
New London, 1.8 mi. W. of, at top of small hill, 200 ft. E. of rd. fork	
S., on S. side of rd., on large rock; chiseled square	68. 61

From New London northwest along New London-Colchester highway into Saybrook quadrangle	
U. S. C. & G. S. B. M. designated "Y 5"	Feet 32. 575
chiseled square	182. 37
intersection of NS. rd., on large rock; chiseled square	160. 46
"152 136 W 1923"  Chesterfield, 3.8 mi. SE. of, 100 ft. N. of rd. fork E., 100 ft. S. of rd. fork W., on W. side of rd., at highest part of small rock cut, about 5 ft. above rd. level, on solid rock; chiseled square	151. 950 170. 61
Chesterfield, 2.6 mi. SE. of, 100 ft. SW. of rd., at wooden church, on	170. 01
S. end of front stone step; chiseled square	183. 41
stamped "208 137 W 1923"	208. 003
end of S. gate wall.	159. 90
Chesterfield, 1.2 mi. NW. of, 4.2 mi. SE. of Salem school, 0.2 mi. NW. of Brookside Farm, in SE. corner of crossroads, 10 ft. W. of corner of stone wall; on outcrop of solid rock; chiseled square	174. 97
Salem, 3.4 mi. SE. of, 100 ft. SW. of schoolhouse near fence line, on S. side of rd., in large rock; standard tablet stamped "351 138 W 1923"	250 555
From New London north along highway west of Thames River into	350. 777
Norwich quadrangle	
New London, 0.6 mi. N. of city hall, 30 ft. S. of junction of Boston Post Road and rd. to Norwich, on E. side of Norwich rd., near	
telephone pole, on curbstone; chiseled square	25. 70
square, on NE. corner of base of fountain; chiseled square New London, 1.3 mi. N. of city hall, at NE. corner of Norwich rd. and Allyn Street, 6 in. E. of corner post of substantial granite wall, on	40. 76
capstone; chiseled square	128. 65
large rock; chiseled square	218. 59
sunken rock; standard tablet stamped "103 125 W 1923"Uncasville, 2.1 mi. S. of, at top of small hill, on W. side of rd., on	102. 515
lower end of rock outcrop; chiseled square	91. 00
tion of wall; chiseled square	158. 1 <b>7</b>

Uncasville, 200 ft. S. of crossroads and post office, in SW. corner of upper crossroads, on large outcrop of solid rock; standard tablet stamped "90 124 W 1923"Uncasville, 200 ft. W. of post office, on large masonry dam, on central part between two spillways, on SE. corner of top stone of wing wall;	Feet 90. 407
chiseled square	67. 95
chiseled squareUncasville, 1.7 mi. N. of, at foot of long hill, 50 ft. N. of small concrete	89. 45
culvert on E. side of rd., near top of ledge; chiseled squareUncasville, 2.7 mi. N. of, 4.2 mi. S. of municipal building at Norwich,	80. 07
200 ft. N. of top of hill, on E. side of rd., on top of large boulder; standard tablet stamped "295 123 W 1923"Norwich, 2.8 mi. S. of, at rd. fork W., 300 ft. S. of lower end of mill pond, on W. side of rd., at E. end of building, at top of railing	295. 410
of concrete steps; chiseled square	40. 33
From Groton north along highway on east side of Thames River into Norwich quadrangle	
U. S. C. & G. S. B. M. designated "E 6"	41. 762
vert, on sloping surface of solid rock; chiseled square	35. 48
W 1923"	<b>1</b> 5. 81 <b>3</b>
on SE. corner of capstone of bridge seat; chiseled square	23. 57
solid rock; chiseled square————————————————————————————————————	62. 99
in large rock; standard tablet stamped "45 127 W 1923"	44. 499
squareGales Ferry, 3.6 mi. N. of, 5.3 mi. S. of Norwich, at rd. fork E. to Ledyard Center, on E. side of rd., at S. end of concrete head wall of	45. 33
culvert, on capstone of masonry retaining wall; chiseled square Norwich, 4.3 mi. S. of, 50 ft. E. of SE. end of approach of long bridge over river, on E. side of rd., at S. side of gate, at base of stone wall,	47. 20
on large rock; standard tablet stamped "10 128 W 1923" Norwich, 3.2 mi. S. of, at rd. fork E. to Poquetanuck, at SW. corner of old meeting house, in foundation under brick base of building,	10. 095
on S. end of projecting corner stone; chiseled square	76. 13
end, on large boulder; chiseled square	178, 16

In northeast corner of quadrangle, on Norwich-Westerly highway	
Norwich, 3.8 mi. SE. of post office at, 100 ft. S. of crossroads, on W. side of rd., on S. end of head wall of concrete culvert; chiseled square	Feet 84. 98
•	
Leveling in 1934 by R. G. Clinite	
From Saybrook quadrangle northeast along Hadlyme-Norwich highway into Norwich quadrangle <sup>4</sup>	
Gardner Lake M. E. Church, 1.8 mi. SW. of, 1.9 mi. NE. of Salem four corners, 30 ft. S. of rd. forks, on SE. side of dirt rd. SW., in root of 20-in. oak tree; copper nail and washer	417. 50
Gardner Lake M. E. Church, 1.1 mi. SW. of, 0.4 mi. SW. of Salem-Montville town line, in SE. angle of crossroads, on top of concrete	
highway bound stone; chiseled cross	418. 39
From Chesterfield northeast along road to point on Wheelers Pond near Oakdale	
Chapel Hill School, 0.8 mi. SW. of, 1.4 mi. NE. of Chesterfield, on NW. side of Bogue Brook Reservoir, on S. side of rd., inside small cemetery and 3 ft. S. of its N. wall, in root of W. one of two large	
spruce trees; copper nail and washer	237. 37
standard tablet stamped "C 3 431 1934"	431. 180
roads, on N. corner of storm sewer; chiseled square	433. 26
head wall of culvert; chiseled square	335. 1 <b>3</b>
U. S. C. & G. S. B. M. designated "530"	261. 101
From Saybrook quadrangle at road forks 1.4 miles southwest, thence 0.7 mile northwest from Chesterfield south along roads to Giant Neck	
Chesterfield, 1.4 mi. SW., thence 0.5 mi. NW. from, 0.3 mi. SE. of rd. forks, 45 ft. SW. of rd., 8 ft. NE. of N. corner of schoolhouse, in	077 005
embedded boulder; standard tablet stamped "C 2 278 1934" Chesterfield, 1.4 mi. SW. of, 40 ft. W. and 60 ft. S. of junction of North Lyme-Chesterfield rd. with rd. S., in root on NW. side of	277. 995
11-in. white oak tree; copper nail and washer Chesterfield, 2.6 mi. SW. of, 0.8 mi. NE. of E. cove of Powers Lake, in NW. angle of junction of private rd. S., on rock ledge; chiseled	275. 59
squarePowers Lake, on NW. side of E. cove, 300 ft. SW. of head of cove, 15 ft. NW. of shore, in root of 10-in. oak tree; copper nail and	175. 48
washer	162. 79

<sup>4</sup> This line ends at U. S. C. & G. S. Monument 526, in Norwich quadrangle, the elevation of which, according to figures of the U. S. G. S., is 431.527 feet.

	Feet
Powers Lake; surface of water June 26, 1934, at 9:35 a. m	156. <b>3</b>
[Line jogs into Saybrook quadrangle.]	
Yale Engineering Camp (on S. side of Powers Lake), 0.6 mi. S. of	
entrance to, 1.1 mi. N. of Boston Post Road, in S. angle of N.	•
junction of double forks of rd. SE., on top of large boulder; chiseled	
square	263. 42
[Line jogs into Saybrook quadrangle.]	
Giant Neck Beach Club, 3.0 mi. N. of, near Bride Lake Brook, 50 ft.	
S. and 40 ft. W. of junction of rd. W. marked "Society Road," on	
E. side of stone wall, in root on E. side of triple-trunk black birch	
tree; copper nail and washer	41. 06
Giant Neck Beach Club, 1.2 mi. N. of, 160 ft. E. of junction of EW.	
highway and rd. S., 60 ft. W. of junction of highway and rd. N., on	
N. side of highway, in root on NE. side of 27-in. ash tree; copper	
nail and washer	30. 40
Giant Neck Beach Club, about 200 ft. N. of entrance, at N. Y.,	
N. H. & H. R. R. bridge 40.96 (over improved rd.), at N. end of W.	
abutment, 4.6 ft. above rd. level, on NE. corner of third stone	
above ground; chiseled square	10. 56
Giant Neck Beach Club, 0.4 mi. W. of, 0.8 mi. E. of South Lyme sta.,	
on R. R. bridge 40.58; chiseled square, U. S. C. & G. S. designation	
"O 5," U. S. C. E. designation "97"	17. 516
From Stonington quadrangle north along Noank-Ledyard road 1.0 mile, thence	
west along New Haven-Providence highway to Groton	
Willow Spring Farm, 0.3 mi. N. of, 4.4 mi. N. of Noank, at crossroads	
0.1 mi. N. of forks of rd. from Ledyard, in NW. angle of crossroads,	
on top of large boulder; chiseled square	291. 84
Willow Spring Farm, 0.8 mi. N. of, 1.2 mi. N.E. of Groton Center, at	
intersection of Noank-Ledyard rd. and Groton-Old Mystic highway,	
25 ft. N. and 55 ft. E. of crossroads, on N. side of highway, on top	
of embedded boulder; chiseled circle	243. 96
Groton Center, in SE. angle of four corners, 4 in. NW. of corner of	
stone wall, in root on SW. side of 36-in. ash tree; copper nail and	
washer	117. 90
Groton Center, 0.4 mi. W. of four corners, 30 ft. N. of center line of	
highway, at curve, in edge of woods, on top of large boulder; stand-	
ard tablet stamped "C 5 94 1934"	93. 824
Groton Center, 1.2 mi. W. of, 2.4 mi. NE. of R. R. sta. at Groton, in	
SE. angle of forks of rd. marked "Poquonock 2 M", at W. end of	
sand pile, on boulder; chiseled circle	50. 23
Groton, 0.9 mi. NE. of R. R. sta. at, on N. side of highway, in NE.	100 50
angle of crossroads, on top of head wall; chiseled circle	129. 53
U. S. C. & G. S. B. M. designated "E 6 4"	41. 762

#### NEW MILFORD QUADRANGLE

[Latitude 41°30′-41°45′; longitude 73°15′-73°30′]

#### FAIRFIELD, LITCHFIELD, AND NEW HAVEN COUNTIES

Leveling in 1922 by R. M. Wilson

From Danbury quadrangle north along highway west of Still River to bridge over Housatonic River at New Milford, thence across bridge and north along highway and road to point on Lake Waramaug

Feet 250. 54
248. 60
243. 309
282. 38
202. 00
209. 71 235. 1
260. 432
422. 46
404. 14
358. 0 <b>64</b>
503. 68
508. 28
661. 856
700. 986
224. 11

New Milford, 1.9 mi. S. of, on N. side of highway bridge over river, on E. abutment; chisel mark on stone	Feet 246. 94
small picnic ground at "Lovers Leap", 50 ft. S. of sharp bend in rd., in solid rock; standard tablet stamped "312 31 W 1922"New Milford, 3.4 mi. S. of, in SE. corner of junction of T-rd. E., about	311. 490
150 ft. W. of schoolhouse, in rock; copper nail New Milford, 4.1 mi. S. of, 200 ft. S. of T-rd. E., 100 ft. NE. of May- brook farmhouse, on E. side of rd., on top of bank, in sunken rock;	222. 93
copper nail  New Milford, 5.0 mi. S. of, at T-rd. NE., near site of old bridge, 50 ft.  NE. of main rd., on N. side of T-rd., in solid rock; standard tablet	193. 93
stamped "174 30 W 1922"	173. 611 158. 84
From New Milford southeast along winding highways and roads into Water- bury quadrangle at a point southwest of Woodbury	
New Milford, 1.1 mi. SE. of United Bank building, at top of first hill E. of town on rd. to Bridgewater, on S. side of rd., at fence corner between two gates, in rock; copper nail	579. 14
New Milford, 1.3 mi. SE. of, at T-rd., on S. side of rd., on N. end of	
concrete culvert; copper nail	473. 61
yard, in top of stone wall; copper nailBridgewater, 0.9 mi. N. of, at T-rd. W., on E. side of rd., in solid rock;	746. 39
copper nailBridgewater, 300 ft. S. of crossroads, in N. end of step of town hall;	<b>7</b> 56. 94
standard tablet stamped "659 38 W 1922"	658. 935
copper nail	484. 24
in rock outcrop; standard tablet stamped "318 39 W 1922" Roxbury sta., 0.8 mi. NE. of, 1.5 mi. NW. of crossroads at Roxbury,	318. 296
at T-rd. N., 30 ft. N. of main rd., 5 ft. S. of stone wall, in top of large rock; copper nail	353. 76
Roxbury, 0.9 mi. NW. of crossroads at T-rd. N., on E. side of rd., in N. end of masonry culvert; copper nail.	529. 78
Roxbury, at crossroads, opposite store, in corner stone of retaining	
wall; standard tablet stamped "568 40 W 1922", set verticallyRoxbury, 1.3 mi. SE. of, 200 ft. SE. of crossroads, at S. end of gate on	567. 764
W. side of rd., in large rock; copper nailRoxbury, 2.1 mi. SE. of, at T-rd. W., in NE. corner of large concrete	659. 58
culvert, at highest part of wing wall; copper nail	522. 78
rock; copper nail	567. 24

Reet.

229, 514

248.18

258.82

233.48

140.951

97.58

158.86

#### NORWALK QUADRANGLE

[Latitude 41°-41°15': longitude 73°15'-73°30']

#### FAIRFIELD COUNTY

# Leveling in 1922 by R. M. Wilson From South Norwalk north along Norwalk-Danbury highway into Danbury guadranele

U. S. C. & G. S. B. M. designated "Tidal 3"	17. 018
"36 W 1 1922"  Norwalk, 1.2 mi. N. of soldiers' monument, on W. side of State rd. to Danbury, 200 ft. N. of Ward Street, across sidewalk from NE. corner of factory of Foster & Stewart Co., in concrete curbing;	35. 666
Norwalk, 3.7 mi. N. of, 2.5 mi. S. of R. R. sta. at Wilton, at rd. fork E. to South Wilton Heights, at NE. corner of stone wall, opposite	73. 20
Old Forge Tavern, in top of large rock; copper nail	134. 04
Wilton, 1.3 mi. S. of R. R. sta., at E. side of forks of paved rd. SE. to Westport, in concrete culvert; copper nail	154. 10
6 ft. S. of SE. corner of garage, in ledge about 1 ft. above rd. level;  brass plug  Cannondale, at rd. forks E. to R. R. sta., 1.6 mi. N. of Wilton sta., in	205. 88
SW. corner of concrete base of ornamental cannon; copper nail Cannondale, 1.0 mi. N. of, 2.7 mi. S. of Branchville, 50 ft. N. of rd. E., at junction of rd. W., at corner of stone wall, in top of large rock;	227. 83
copper nail  Branchville, 1.4 mi. S. of, 500 ft. N. of rd. fork E. across bridge, on W. side of rd., at entrance to house of Mr. McIlwain, on S. side of	267. 73
bottom part of concrete steps; copper nail  From Danbury quadrangle southeast along Danbury-Bridgeport highway into Bridgeport quadrangle	296. 46
Easton, at rd. fork E. to Easton Center, near upper end of upper reservoir, on W. side of rd., in concrete culvert; copper nail Easton, 1.0 mi. SE. of, 300 ft. N. of rd. fork S. to Westport, at large concrete culvert, on N. end of W. railing; standard tablet stamped	234. 23
11000	

"230 14 W 1922"\_\_\_\_\_

#### NORWICH QUADRANGLE

[Latitude 41°30′-41°45′; longitude 72°-72°15′]

#### NEW LONDON, TOLLAND, AND WINDHAM COUNTIES

#### Leveling in 1923 by R. M. Wilson

From Gilead quadrangle southeast along Stafford Springs-New London highway into New London quadrangle

Willimantic, 2.1 mi. NW. of county courthouse at, directly opposite	Feet
rd. fork S., on N. side of rd., on sunken rock; chiseled squareWillimantic, 0.8 mi. W. of, on S. side of junction of Rockville and	296. 91
Hartford rds., at W. side of entrance to cemetery, on stone wall 12 ft. W. of its E. end, in capstone; chiseled square	274, 84
Willimantic, at Main and High Streets, on E. side of courthouse, at	
entrance to police sta., on S. end of stone doorsill; standard tablet stamped, by U. S. C. & G. S., "265.518 M 9 1923" (U. S. C. & G. S.	
B. M. designated "M 9") Willimantic, at Main and Church Streets, in front window of H. C.	265. 518
Murray Block, at E. end of stone sill; standard tablet stamped, by	
U. S. C. & G. S., "244.813 N 9 1923" (U. S. C. & G. S. B. M. designated "N 9")	244. 813
Willimantic, 1.9 mi. SE. of courthouse at, 300 ft. S. of point where	
trolley tracks diverge from rd., on S. side of driveway to house, on W. side of rd., in base of stone wall, on large rock; chiseled square	256. 22
Willimantic, 2.9 mi. SE. of, 0.9 mi. NW. of R. R. sta. at South Windham, at top of hill, on W. side of rd., about 6 ft. above rd. level, in	
base of stone wall, in large rock; chiseled square	241. 05
South Windham, at E. end of main building of Smith-Winchester Manufacturing Co., at S. side of large door, cemented in concrete	
foundation of building; standard tablet stamped "166 131 W 1923".  South Windham, 200 ft. W. of R. R. sta., on W. side of rd., on N. end	165. 455
of head wall of concrete culvert; chiseled square	152. 54
South Windham, 1.6 mi. SE. of R. R. sta. at, 1,100 ft. N. of R. R. crossing, 20 ft. W. of rd., 10 ft. E. of trolley tracks, in large flat	
rock; chiseled squareSouth Windham, 2.8 mi. SE. of, on W. side of rd. and at its highest	238. 94
part, on large farm, on N. side of driveway to barn, beside large	
tree, in base of stone wall 3 ft. N. of its end, on large rock; chiseled square	315, 35
South Windham, 3.9 mi. SE. of, 5.4 mi. N. of R. R. sta. at Yantic, at	010.00
top of steep grade at N. end of Franklin Hill, 1,000 ft. N. of schoolhouse, on W. side of rd., 3 ft. W. of right-of-way fence, cemented in	
large rock; standard tablet stamped "416 132 W 1923"	416. 015
above rd. level, on sloping surface of solid rock outcrop; chiseled	
SquareYantic, 3.1 mi. NW. of, 1,000 ft. SE. of schoolhouse, 75 ft. W. of rd.,	452. 67
opposite culvert, 60 ft. NE. of tool shed, in pasture land, about 15	
ft. above rd. level, in sunken rock; standard tablet stamped "208 133 W 1923"	207. 440
Yantic, 1.8 mi. N. of, 300 ft. N. of rd. fork N., on E. side of rd., opposite large frame farmhouse, 30 ft. N. of shed, at corner of	
stone wall and in its base, on large rock; chiseled square	177. 59

Yantic, 0.8 mi. N. of, at rd. fork to Lebanon Green, 20 ft. S. of school- house, in stone retaining wall 1.5 ft. E. of its corner, on second stone	Feet
from top; chiseled square	143. 34 112. 547
Yantic, 0.3 mi. S. of post office, 200 ft. W. of R. R. crossing, 50 ft. S. of main rd., at W. side of branch rd., near base of stone wall, in	
solid rock; top of iron guy-wire anchor fastened in rock Yantic, 0.9 mi. S. of post office, 3.1 mi. NW. of municipal building at Norwich, at S. corner of Huntington Green, at NW. corner of	123. 09
church, on capstone of retaining wall; chiseled square Norwich, 2.0 mi. N. of, 200 ft. W. of church, 30 ft. N. of rd., at base of Meeting House Rock, cemented in solid ledge; standard tablet	125. 74
stamped "128 135 W 1923"	128. 385
square upper part; chiseled squareNorwich, at entrance on E. side of municipal building, at S. side of	107. 04
door, in granite sill; standard tablet stamped "41 130 W 1923" Norwich, on Main Street, between High and Forest Streets, at fire sta., in sill of W. doorway; standard tablet stamped "43 129 W	40. 560
1923"Norwich, near S. city line, on rd. to New London, 100 ft. N. of corner	42. 543
of South Street, on E. side of rd., on fire hydrant; top of valve nut Norwich, near S. city line, on W. side of New London rd., in line with N. side of South Street, on top of retaining wall, on large rock;	29. 60
chiseled square	24. 12
From Moosup quadrangle southwest and south along Plainfield-Groton highway into New London quadrangle	
Jewett City, 3.0 mi. SW. of Slater Library at, on rd. to Norwich at point where rd. and river diverge, at bottom of hill, 200 ft. S. of culvert, 50 ft. W. of rd., in large rock; standard tablet stamped	• ,
"87 154 W 1923"  Jewett City, 3.7 mi. SW. of, 5.3 mi. NE. of municipal building at Norwich, 300 ft. W. of R. R. signal tower, on W. side of rd., at	87. 071
edge, on large rock; chiseled square	102. 62
Norwich, 3.5 mi. NE. of, at bridge over Shetucket River, on S. side of rd., on top of W. end of railing of bridge; standard tablet stamped	129. 83
"46 155 W 1923"	46. 187
rock; chiseled square	83. 00
tablet stamped "54 156 W 1923"	<b>54. 436</b>

Norwich, in front of post office, at edge of sidewalk, on W. end of lower concrete step; chiseled cross, State B. M	Fect 35. 01
U. S. C. & G. S. B. M. designated "Tidal 2" (standard disk stamped "No. 2 11.31")  Norwich, 0.9 mi. S. of highway bridge over river, in front of Laurel	11. 225
Hill School, at edge of sidewalk, at S. side of steps, on capstone of retaining wall; chiseled square.	84. 40
From Norwich southeast along Hartford-Westerly highway into New London quadrangle	
Norwich, 300 ft. E. of post office, 100 ft. E. of junction of Main and East Main Streets, at highway bridge over R. R. tracks, on S. end	
of E. bridge seat; chiseled square Norwich, 1.1 mi. SE. of municipal building, at top of hill, at E. side of	35. 74
junction of Main and Palmer Streets, 3 in. W. of stone wall, on outcrop of solid rock; chiseled square	153, 90
Norwich, 2.4 mi. SE. of, in SE. corner of junction of rd. E., 40 ft. E. of main rd., at N. end of stone wall, at W. side of gate, on large rock;	100. 00
chiseled square Norwich, 2.9 mi. SE. of, 240 ft. NW. of crossroads, 30 ft. W. of main	113. 78
rd., in pasture, on top of large rock projecting about 6 ft. above ground; drill hole marking site of standard tablet, now removed, stamped "68 143 W 1923"	67. 996
From Willimantic northeast along Willimantic-Chaplin highway into	07. 990
Woodstock quadrangle Willimantic, at S. side of junction of Union and Main Streets, at NE.	
corner of dye house of American Thread Co., on W. end of doorsill;	
standard tablet stamped, by U. S. C. & G. S., "0 9 1923 192.017" (U. S. C. & G. S. B. M. designated "0 9")	192. 017
Willimantic, 1.6 mi. NE. of courthouse, at N. end of steel bridge over Natchaug River, on top of W. wing wall, in concrete; chis-	
eled square	165. 62
on E. side of rd., on concrete spillway of small reservoir; chiseled	
Willimantic, 3.7 mi. NE. of, 1.1 mi. SW. of crossroads at North Windham, about 500 ft. E. of top of hill, on S. side of rd., at point where rd. and telephone line diverge, about 10 ft. above rd. level, at top of cut bank, on large sunken rock; standard tablet stamped	241. 92
"285 157 W 1923"	284. 536
PALMER QUADRANGLE	
[Latitude 42°-42°15′; longitude 72°15′-72°30′]	
TOLLAND COUNTY	
Leveling in 1934 by E. M. Wheeler	
From Scantic River east along winding roads near Connecticut-Massachusetts State line into Brookfield quadrangle near Moulton Pond	
North Somers, 1.4 mi. N. of crossroads at, 0.1 mi. S. of State line, at concrete bridge over Scantic River, on E. end of N. abutment;	Feet
chiseled square[Line jogs into Massachusetts.]	215. 19

North Somers, 1.8 mi. NE. of, 1.3 mi. E. of bridge over Scantic River, 0.3 mi. SE. of State line, on estate of George Platt, 95 ft. SW. of	
center line of rd., on top of E. foundation pier of observation tower; standard tablet stamped "WH 6 352 1934"	Feet 352. 351
Reference mark, 110 ft. E. of tablet, 15 ft. SW. of center line of rd., in root on N. side of 12-in. maple tree; copper nail and washer North Somers, 2.2 mi. NE. of, 2.4 mi. E. of bridge over Scantic River, 65 ft. SW. of junction of rd. from Hampden with T-rd. SE., 15 ft. NW. of center line of rd., in root on E. side of 18-in. oak tree; copper	354. 89
nail and washer North Somers, 3.2 mi. E. of, 3.3 mi. SE. of bridge over Scantic River, in W. angle of intersection of NWSE. and NESW. rds., 20 ft.	583. 18
NW. of intersection, 20 ft. SW. of center line of rd., in root on W. side of 16-in. oak tree; copper nail and washer	723. 49
rd., on top of boulder flush with ground; chiseled square [Line jogs into Massachusetts.]  Stafford post office, 3.1 mi. NW. of, 0.4 mi. S. of State line, in triangle at junction of NS. rd. with T-rd. E., 100 ft. S. of junction, 25 ft.	515. 35
E. of NS. rd., on top of boulder flush with ground; chiseled square.  [Line jogs into Massachusetts.]  Staffordville, 2.7 mi. N. of, 0.7 mi. S. of State line, 325 ft. N. of junction of T-rd. from N. with EW. rd., 10 ft. W. of center line of rd.	772. 35
from N., on ledge; chiseled square	999. 17 755. 56
PUTNAM QUADRANGLE	
[Latitude 41°45′-42°; longitude 71°45′-72°]	
WINDHAM COUNTY	
Leveling in 1923 by R. M. Wilson	
From Woodstock quadrangle northeast along Hartford-Mansfield-Providence highway to Putnam	
Abington, 1.2 mi. E. of crossroads at, 1.5 mi. SW. of Pomfret sta., on S. side of rd., at concrete bridge over Mashamoquet Brook, on W. end of head wall; chiseled squarePomfret sta. (Pomfret Center post office), 0.5 mi. S. of, in SW. corner of crossroads, on W. one of two danger signs, on SW. corner of concrete	Feet 394. 86
base of sign; chiseled square	321. 62
Pomfret sta., 300 ft. N. of, at SE. corner of R. R. bridge over highway, in concrete abutment; standard tablet stamped "372 163 W 1923"_Pomfret sta., 300 ft. NE. of, about 150 ft. SE. of R. R. bridge over	371. 887
highway, on SW. side of rd., on heading of small concrete culvert; chiseled cross, State B. M	353. 02
SW. corner of building; chiseled square	611. 16

·	
Pomfret, at front entrance of Christ Church (Episcopal), on W. flight of steps; NW. corner of top step, State B. M	Feet 612. 25
of large rock; standard tablet stamped "589 165 W 1923"	589. 114
monument, about 5 ft. above ground; chiseled line Pomfret, 1.0 mi. E. of crossroads at, 2.7 mi. SW. of municipal building at Putnam, at foot of long hill, on S. side of rd., on W. end of head	589. 71
wall of concrete culvert; chiseled square————————————————————————————————————	359. 91
Putnam, at Main and Front Streets, at entrance to dry goods store of Bugbee & Wolf; SW. corner of first stone step (State B. M)	467. 67 279. 16
Leveling in 1922 by D. H. Baldwin	
From Putnam south along Worcester-Groton highway into Moosup quadrangle	
Putnam, at municipal building, about 5 ft. NE. of its S. corner, in water table a few inches above ground; standard tablet stamped	
"274 1 B 1922"	274. 250
Putnam, at Smith Street public school, at S. corner of building, in foundation, in center of front face of granite stone, about 3 ft.	266. 71
above ground; standard tablet stamped "325 2 B 1922"	324. 522
Van Den Noort Streets; top of hydrant	312. 04
6 in. above ground; standard tablet stamped "290 3 B 1922" Reference mark, about 100 ft. NW. of tablet, near street corner; top	290. 164
of hydrant	289. 06
etery, on end stone of corner curve of curb; chiseled square Putnam, 2.6 mi. SE. of R. R. sta. at, 1.6 mi. N. of Attawaugan, 0.2 mi. N. of Putnam-Killingly town line, on W. side of rd., 6 ft. W. of S. end of guard fence, on large rock projecting about 3 ft. above	289. 07
ground, near top of rock; chiseled squareAttawaugan, 1.4 mi. N. of, at Putnam-Killingly town line, on E. side of State rd., on top of granite town-line boundary mounment, which projects about 2.4 ft. above ground and is marked "P" on one side	367. 66
and "K" on the opposite side; chiseled square	400. 24
"411 4 B 1922"  Reference mark, 93 ft. SE. of tablet, 28 ft. S. and 18 ft. E. of center	411. 260
line of junction of State rd. and rd. E., on E. side of State rd., in edge of bank, in top of boulder; chiseled square	415. 98

Attawaugan, at junction of State rd. and rd. NW., 100 ft. S. of sign-post, on W. side of rd., on culvert stone; chiseled squareAttawaugan, 0.6 mi. S. of, 0.8 mi. NE. of Dayville (Killingly post office), in grass triangle at rd. forks, in E. side of crotch of double	Feet 296. 71
elm tree at a point about 2 ft. above ground; chiseled square Dayville, at E. corner of Main Street and Attawaugan Avenue,	305. 40
opposite Killingly post office, on corner curbstone; chiseled square Dayville, at R. R. crossing of Main Street, at N. end of sta.; top of	243. 79
E. rail————————————————————————————————————	243. 9
Dayvillé, in front of public school, on N. side of street and electric railway, on curb line, 3 ft. N. of N. rail, on granite capstone of catch	259. 978
basin; chiseled square	252. 56
Square	261. 46
420 ft. N. of T-rd. W., 135 ft. S. of stone culvert, on E. side of rd., in bank, on large rock; chiseled square	255. 89
at a point 2.4 ft. above pavement; standard tablet stamped "236 6 B 1922"	235. 995
Street, at Y-fork, in grass triangle, on top of stone cap around man- hole cover; chiseled square	249. 18
Danielson, 1.4 mi. S. of, on E. side of rd., 53 ft. N. of center of culvert over brook, 1 ft. N. of large elm tree, in base of large boulder near	
its W. end and 0.8 ft. N. of iron bolt	234. 67
48-in. oak tree; copper nail and washer	302. 89
T-rd. E., on line with stone wall, on N. side of wall, on large flat rock; chiseled square	253. 92
of old State rd., 37.4 ft. N. of site of standard tablet stamped "7.B 1922 148 1923 258" (destroyed in 1924), near stone wall, on top of granite town-line boundary post projecting 2 ft. above bank;	
chiseled square	259. 87
NE. corner of bridge, in rock; top of bolt	226. 23
Hallows Cemetery, at edge of rd., on rock: chiseled square	236. 99

#### SANDISFIELD QUADRANGLE

[Latitude 42°-42°15'; longitude 73°-73°15']

#### HARTFORD AND LITCHFIELD COUNTIES

#### Leveling in 1923 by R. M. Wilson

#### Near southwest corner of quadrangle, on Canaan-Winsted highway

West Norfolk, at rd. fork N., on S. side of rd., at small bridge over	Feet
stream, on corner stone of E. bridge seat; chiseled square	883. 8 <b>2</b>

#### Leveling in 1934 by R. G. Clinite

From Granville quadrangle at a point about 0.6 mile south of Connecticut-Massachusetts State line south along winding road near Litchfield-Hartford county line into Waterbury quadrangle

county line into waterbury quadrangle	
Pinehurst Club, 0.6 mi. N. of, 4.6 mi. along winding rd. SE. of Tolland post office (Mass.), 40 ft. E. and 30 ft. S. of junction of T-rd. E.,	
10 ft. S. of fence corner, in root on W. side of 28-in. maple tree;	
rail spike	1, 209. 29
Pinehurst Club, 130 ft. S. of entrance, 15 ft. W. of rd., on ledge;	
chiseled square	1, 172. 66
Pinehurst Club, 0.5 mi. SE. of, about 4.5 mi. along winding rd. N. of	
Riverton, 35 ft. S. and 15 ft. E. of rd. fork NW., 50 ft. E. of bridge,	
in root on E. side of 22-in. oak tree; rail spike	921. 36

#### SAYBROOK QUADRANGLE

[Latitude 41°15′-41°30′; longitude 72°15′-72°30′]

#### MIDDLESEX AND NEW LONDON COUNTIES

#### Leveling in 1923 by R. M. Wilson

# From Guilford quadrangle southeast along Middletown-Saybrook highway to Saybrook

Haddam, 1.6 mi. E. of Brainerd Public Library at, in village of Shailerville, at junction of rd. fork SW., on W. side of rd., in lower end of outcrop of solid rock; chiseled cross	Feet 93. 20
Haddam, 2.4 mi. SE. of, on W. side of rd., on heading of high culvert;	70.00
chiseled square	72. 90
tablet stamped "53 101 W 1923"	53. 059
East Haddam, <sup>5</sup> at E. end of highway bridge over Connecticut River, on top of N. wing wall of E. abutment; standard tablet stamped "29 102 W 1923"	28. 494
East Haddam, <sup>5</sup> at retaining wall S. of general store, on S. side of base of wall, set in solid rock; brass plug, U. S. C. E. B. M. designated	
"A 33" (established in 1909) East Haddam, at base of retaining wall of general store, on solid rock; chiseled line marking high-water mark of river during freshet	8. 896
of May 2, 1854Chester, 2.6 mi. NW. of, 1.5 mi. SE. of junction of rd. to East Haddam, on W. side of rd., about 3 ft. above rd. level, on solid rock;	13. 99
chiseled square	66. 55

<sup>&</sup>lt;sup>5</sup> On spur line run east from B. M. "101 W 1923", described above.

Chester, 1.4 mi. NW. of, on E. side of rd., on heading of concrete culvert; chiseled square	Feet . 71. 59
Chester, 1.0 mi. NW. of, in SE. corner of crossroads, at end of stone wall, on top of large granite corner stone; chiseled crossChester, 0.5 mi. E. of, 1.3 mi. N. of town hall at Deep River, 200 ft. N. of crossing of main highway and rd. from Chester to Chester sta., on E. side of highway, on outcrop of solid rock; standard	62. 07
tablet stamped "75 103 W 1923"	75. 406
W 1923"	53. 625
N. side of branch rd., on highest part of large rock; chiseled square. Centerbrook, 0.4 mi. N. of, 200 ft. N. of mill and rd. forks, on W. side of rd., about 4 ft. above rd. level, on outcrop of solid rock;	53. 29
chiseled squareCenterbrook, 500 ft. E. of main rd. forks in center of town, 20 ft. E.	38. 92
of SE. corner of old Congregational Church, on N. side of rd., in outcrop of solid rock; standard tablet stamped "54 113 W 1923". Centerbrook, 1.2 mi. SE. of, 2.9 mi. N. of Saybrook sta., at junction of rd. fork N., on E. side of branch rd., at S. end of stone wall, just N. of concrete-topped gatepost, on top of wall, on SW. corner of	53. 822
last stone; chiseled square	22. 68
long, embedded rock; chiseled square	51. 08
rd., in stone wall near its base, on large rock; chiseled square U. S. C. & G. S. B. M. designated "E 5"	56. 83 22. 493
From Saybrock northeast along New Haven-Providence highway (Boston Post Road) into New London quadrangle	
Saybrook sta., 1.3 mi. NE. of, at W. side of junction of Spring Brook and Boston Post Roads, in root on E. side of large tree; copper	
nail	29. 00 26. 568
old Lyme, 0.7 mi. W. of corner of main street and Boston Post Road, in SW. corner of intersection of post rd. and Old Lyme-North Plain highway, on S. side of rd., in W. end of foundation of small	37. 75
culvert, on high corner of large stone; chisel cut.  Old Lyme, at corner of main street and Boston Post Rd., about 0.5 mi. N. of post office, on E. side of main street, in S. end of base of	29. 10
stone wall, in large rock; chiseled squareOld Lyme, 1.0 mi. NE. of corner of main street and Boston Post Road, at point where rd. passes through small rock cut, 10 ft.	23. 88
N. of rd., on W. slope of outcrop of solid rock; chiseled square	38. 89

<sup>&</sup>lt;sup>6</sup> On spur from main line.

Old Lyme, 2.5 mi. NE. of, at S. end of Rogers Lake, at cemetery, in W. end of front wall, cemented in coping; standard tablet stamped "51 116 W 1923"	Feet 51. 129 36. 8
1.0 mi. E. of Rogers Lake, 600 ft. E. of small rock cut, on S. side of rd., on railing of concrete culvert; chiseled square  East Lyme, 3.8 mi. SW. of, at foot of steep hill, about halfway around sharp curve, 100 ft. NW. of rd. forks, 10 ft. N. of rd., on top of large handon chiseled square.	113. 72
large boulder; chiseled square	117. 88 207. 876
From point on Boston Post Road just east of highway bridge over Connecticut River north along Old Lyme-North Plain highway to Hamburg 7	201. 010
Old Lyme, 0.9 mi. NW. of corner of main street and Boston Post Road, 1,200 ft. N. of intersection of post rd. and Old Lyme-North Plain highway (just E. of bridge over river), opposite Lyme coal dock, at edge of rd. to Hamburg, in rock; brass plug, U. S. C. E.	
B. M. designated "A 29" (established in 1909)	22. 385
rd., in large boulder, cemented in drill hole; copper nail————————————————————————————————————	49. 38
chiseled square————————————————————————————————————	208. 20
corner, on NE. corner of end capstone; chiseled square————————————————————————————————————	221. 66
boulder; chiseled square	113. 36
stamped "26 115 W 1923"	25. 807
chiseled horizontal line marking high-water level in 1862	7. 82 7. 325
From Lyme station north along road to Old Lyme	
U. S. C. & G. S. B. M. designated "J 5"Old Lyme, 0.5 mi. S. of corner of main street and Boston Post Road, 100 ft. N. of public library, on E. side of rd., 10 ft. S. of N. end of stone wall, about 15 ft. above rd. level, in solid ledge; standard	23. 655
tablet stamped "30 114 W 1923"	29. 638

Single-run spur line checked by U. S. C. E. tidal bench mark at Hamburg.

147.89

177.48

#### into New London quadrangle Salem, 25 ft. NW. of S. one of two churches, 60 ft. SE. of schoolhouse, 120 ft. NE. of rd., in large sunken rock; standard tablet stamped Feet "362 139 W 1923"\_\_\_\_\_ 362. 385 Salem, 1.6 mi. SE. of, 2,150 ft. SE. of Salem four corners, at foot of hill, on NE. side of rd., at highest part of small rock cut, about 7 ft. above rd. level, on point of rock projecting toward rd.; chiseled square\_\_\_\_ 298, 44 Salem, 2.2 mi. SE. of, at edge of Horse Pond, opposite high rocky point, 20 ft. SW. of rd., on large rock at edge of water at a point 3 in. from large drill hole; chiseled square\_\_\_\_\_ 433.60 Leveling in 1934 by R. G. Clinite Near northeast corner of quandrangle on Hadlyme-Norwich highway Salem, 0.9 mi. NE. of four corners at, 1.6 mi. E. of Salem schoolhouse, 2.1 mi. SW. of Salem-Montville town line, at junction of highway and "The Old Road", in E. side of top of large boulder; chiseled square\_\_\_\_\_ 421.45 . From New London quadrangle at T-rd. junction near East Lyme-Salem town line south along winding roads and back into New London quadrangle Chesterfield, 2.4 mi. by rd. NW. of, about 0.2 mi. (air line) S. of East Lyme-Salem town line, 100 ft. NW. of rd. forks, in SW. corner of orchard, in top of large boulder; chiseled circle \_\_\_\_\_ 393. 36 Chesterfield, 1.4 mi. SW. and 0.7 mi. NW. of, 1.1 mi. S. of lastdescribed bench mark, 50 ft. S. and 20 ft. E. of junction of North Lyme-Chesterfield rd. and rd. N., on bank 5 ft. above rd. level, on embedded boulder; chiseled square\_\_\_\_\_ 317. 71 [Line jogs into New London quadrangle.] Powers Lake; surface of water June 26, 1934\_\_\_\_\_ 156.3 Yale Engineering Camp (on S. side of Powers Lake), 20 ft. N. and 20 ft. W. of entrance to instrument house, in top of granite ledge; standard tablet stamped "C 1 249 1934"..... 249. 343 Yale Engineering Camp, 90 ft. SW. of entrance to, in NW. angle of

crossroads, on top of large boulder; chiseled circle (established by Yale engineering students)\_\_\_\_\_\_

Yale Engineering Camp, 1.1 mi. S. of entrance to, 2.2 mi. W. of crossroads at East Lyme, at junction of New Haven-New London highway (Boston Post Road) and rd. N., on S. side of highway, 5 ft. N. of fence, on boulder; chiseled circle\_\_\_\_\_\_\_

[Line jogs into New London quadrangle.]

#### SHEFFIELD QUADRANGLE

[Latitude 42°-42°15'; longitude 73°15'-73°30']

#### LITCHFIELD COUNTY

#### Leveling in 1923 by R. M. Wilson

From Sandisfield quadrangle near West Norfolk west along Winsted-Canaan highway to Canaan, thence southwest along Canaan-Falls Village road into Cornwall quadrangle

East Canaan, 0.7 mi. E. of R. R. sta., 2.6 mi. W. of West Norfolk,	
100 ft. W. of bridge over Blackberry River, on S. side of rd., on top	
of E. wing wall of large concrete culvert; standard tablet stamped, erroneously, "732 207 W 1923"	Feet 751. 434
East Canaan, across tracks in front of R. R. sta., on NE. corner of	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
concrete base of semaphore signal; chiseled square	810. 24
East Canaan, 0.6 mi. W. of R. R. sta., 1.8 mi. E. of post office at Canaan, at foot of small hill, 30 ft. W. of small culvert, 20 ft. N. of	
rd., about 6 ft. above rd. level, on solid ledge; chiseled square	809. 55
Canaan, 0.6 mi. E. of post office, at R. R. bridge over highway, on	
N. side of rd., at E. end of pier supporting bridge, on NE. corner of top stone; chiseled square	· 702. 46
Canaan, 200 ft. E. of post office, at SE. corner of stone church (Epis-	
copal), about 6 ft. above ground, on NE. corner of foundation of	701 200
buttress; standard tablet stamped "702 208 W 1923" Canaan, 200 ft. N. of R. R. sta., on N. side of small triangular green,	701. 308
on fire hydrant; top of valve nut	675. 90
Canaan, at R. R. sta., just SW. of crossing of tracks of main lines, at R. R. water tank, on N. one of 3 pillars supporting tank on its E.	
side, on NE. corner of stone foundation of pillar, marked "8";	
chiseled circle	669. <b>24</b>
Canaan, 1.4 mi. SW. of post office, on sand rd. at point where it reaches base of small rocky hill, on W. side of rd., et end of stone	
wall, 20 ft. SW. of gate, 20 ft. NE. of large pine tree growing in	
cleft that divides large rock into halves, on sunken rock; chiseled square	675. 84
Canaan, 2.0 mi. SW. of, 3.3 mi. N. of Falls Village, about 0.5 mi. E.	015. 64
of concrete bridge over Housatonic River, 150 ft. NW. of rd. forks,	
in side hill pasture, on large limestone ledge; standard tablet stamped "684 209 W 1923"	683. 660
SPRINGFIELD QUADRANGLE	
[Latitude 42°-42°15'; longitude 72°30'-72°45']	
HARTFORD AND TOLLAND COUNTIES	
Leveling in 1933 by R. G. Clinite	
From Connecticut-Massachusetts State line south along North Street to its intersection with Halloday Avenue, thence northwest and back to State line	
Suffield, 1.8 mi. N. of, 200 ft. SW. of North Street School, 40 ft. W. and	
80 ft. N. of intersection of North Street and Halloday Avenue, in	Feet 169. 82
root on W. side of 18-in. elm tree; copper nail and washer North Street School, 1.5 mi. NW. of, 40 ft. SW. and 10 ft. NW. of	109. 02
junction of Halloday Avenue and woods rd., in root on SW. side of	
18-in. white-oak tree; copper nail and washer North Street School, 2.5 mi. NW. of, 2.3 mi. SE. of Feeding Hills	184. 00
(Mass.), at State line, on NE. side of rd., in center of top of State-	
line monument; rim of small hole	214. 60

#### Near west boundary of quadrangle

West Suffield, 5.2 mi. NW. of, 1.8 mi. SE. of Southwick (Mass.), at State line, 20 ft. E. of center line of rd., on top of State-line bound stone; drill hole	Feet 264. 57 256. 56
STAMFORD QUADRANGLE	
[Latitude 41°-41°15'; longitude 73°30'-73°45']	
FAIRFIELD COUNTY	
Leveling in 1932 by J. A. Anderson	
From Connecticut-New York State line at point about 1 mile northeast of Banksville south along Bedford-Stanwich road about 1.3 miles, thence northwest along road and back to State line at Banksville	
Stanwich, 2.2 mi. N. of, 4.8 mi. S. of Bedford (N. Y.), on State line, on E. side of rd., about 4 ft. above ground; top of State-line monument.	Feet 530. 07
Stanwich, 1.6 mi. N. of, at crossing of small stream; top of W. wall of bridge	371
Stanwich, 1.2 mi. N. of, at SE. corner of intersection of East Middle Patent Road and NWSE. rd., at edge of rd.; top of rock outcrop_Stanwich, 1.5 mi. NW. of, 0.8 mi. SE. of Banksville; rd. summitBanksville, 0.4 mi. E. of, on State line, about 4 ft. above ground; top	478. 20 508
of State-line monument	480. 48
about 4 ft. above ground; top of granite State-line monument	456. 63
Leveling in 1932 by J. C. McGuire	
From Connecticut-New York State line at crossing of Blind Creek southeast along Armonk-Port Chester highway and road following State line to point 2.2 miles north of Port Chester (New York State)	
Glenville, 4.1 mi. NW. of, about 3 mi. NE. of Purchase (N. Y.), 13 ft.  E. of State line, on S. edge of concrete pavement of New Lake Street; chisel cut	415. 07
Glenville, 3.9 mi. NW. of, 5.8 mi. NW. of Port Chester (N. Y.), about 0.2 mi. E. of State line, 120 ft. S. of center line of triangle at junction of New Lake and King Streets, on E. side of low stone wall, on 4.5-by-5-ft. boulder in place forming bottom course of wall and extending beyond its E. and W. faces, on top of E. end of boulder;	
standard tablet stamped "C 1 1932"	480. 747 472. 40
Chisel cut	712. <b>4</b> U
State-line monument; chisel cut	345. 30

Glenville, 2.4 mi. NW. of, 4.2 mi. N. of Port Chester (N. Y.), on W. side of King Street, at driveway entrance to Hilholme estate, on top of NE. corner of N. headstone; chisel cut (in N. Y.)	Feet 352. 17
crete carriage stepping stone	318. 17
on W. side of stone wall, on protruding stone; chisel cut Glenville, 0.8 mi. W. of, 2.7 mi. N. of Port Chester (N. Y.), 170 ft. NE. of school, 96 ft. N. of church, at NE. corner of junction of King Street and Ridge Street (Port Chester-Glenville highway), on top	314. 74
of curb; chisel cut	276. 87
Port Chester, N. Y., 2.4 mi. N. of, at junction of King Street and Glenville rd., in center of Glenville rd., on E. side of circular curb; chisel	
Port Chester, 2.2 mi. N. of, 533 ft. S. 45° E. of junction of King Street and Glenville rd., 295 ft. E. of center line of King Street, in middle	199. 40
of field, in top of rock outcrop; standard tablet stamped "C 2 1932" Reference mark 1, 325 ft. S. 60° W. of tablet, about 450 ft. S. of center line of Glenville rd., 30 ft. W. of center line of King Street, 45 ft. S. of center line of driveway to Who Torok Cottage, in root of 30-in.	200. 055
maple tree; nail and washer	193. 42
Reference mark 2, 390 ft. S. 35° W. of tablet, on ConnNew York State line; top of NW. corner of State-line monument	199. 96
STONINGTON QUADRANGLE	
[Latitude 41°15′-41°30′; longitude 71°45′-72°]	
. NEW LONDON COUNTY	
Leveling in 1923 by R. M. Wilson	
From New London quadrangle southeast along Norwich-Westerly highway to Connecticut-Rhode Island State line	
Norwich, 5.1 mi. SE. of, 7.8 mi. NW. of North Stonington, at top of hill, in SE. corner of crossroads, 8 ft. NW. of end of stone wall, on sunken rock; chiseled square————————————————————————————————————	Feet 153. 15
North Stonington, 4.9 mi. NW. of, at top of hill, opposite rocky bank, on W. side of rd., about 3 ft. above rd. level, on top of large boulder	140. 692
in bank; chiseled square	238. 38
of rd., on large rock; chiseled square	241. 40
stamped "239 145 W 1923"	239. 234

North Stonington, 1.6 mi. NW. of, at rd. fork S., 20 ft. W. of main rd., at NW. corner of stone wall, in base of wall, on sloping surface of large corner stone; chiseled squareNorth Stonington, 0.4 mi. NW. of, on N. side of rd. at SE. corner of cemetery, on easternmost capstone of retaining wall; chiseled	Feet 177. 43
North Stonington, 600 ft. W. of post office, at front entrance of Wheeler School and Library, in recess at E. side of E. column, cemented in granite step; standard tablet stamped "148 146 W	142. 40
North Stonington, 1.3 mi. SE. of, about 150 ft. NW. of frame farm-house, 40 ft. NW. of highest part of small cut bank, 6 ft. W. of	147. 451
wall, on W. side of rd., in outcrop of solid rock; chiseled square Westerly (R. I.), 3.1 mi. NW. of, 50 ft. N. of rd. fork SW., near top of small hill, on W. side of rd., 1 ft. E. of stone wall, on large sunken	135. 34
rock; chiseled square	113. 15
"89 147 W 1923"U. S. C. & G. S. B. M. designated "Q 6"	89. 336 30. 216
Leveling in 1934 by R. G. Clinite	
From Noank north along Noank-Ledyard road into New London quadrangle	
U. S. C. & G. S. B. M. designated "K 6"	19. 432
washer	21. 48
Brook, on shelf at top of wing wall; chiseled square	36. 21
of rd., in root on E. side of 24-in. white-oak tree; copper nail and washer	113. 38
stand in triangle, in NW. corner of meadow, 1 ft. SE. of stone wall, in top of large boulder; standard tablet stamped "C 4 188 1934"  Reference mark, 50 ft. N. and 40 ft. E. of tablet, on SE. side of	187. 499
triangle at rd. forks, on embedded boulder; chiseled square	187. 49

#### TOLLAND QUADRANGLE

[Latitude 41°45′-42°; longitude 72°15′-72°30′]

#### HARTFORD AND TOLLAND COUNTIES

#### Leveling in 1923 by R. M. Wilson

From Gilead quadrangle north along Willimantic-Stafford Springs highway to Stafford Springs

Eagleville, 3.0 mi. SE. of, 3.8 mi. NW. of county courthouse at Willimantic, 125 ft. N. of rd. fork E., 30 ft. E. of rd., in large sunken	Feet
rock; standard tablet stamped "331 166 W 1923"	331. 349
Eagleville, 2.1 mi. SE. of, about 2 mi. E. of South Coventry, in NE.	
corner of crossroads, on head wall of concrete culvert; chiseled	
square	276. 76
Eagleville, 0.8 mi. SE. of, at NW. corner of large concrete culvert, on	2.00
head wall; chiseled square	291. 58
Eagleville, 0.7 mi. NW. of, about in middle of small hill, at junction	201. 00
of abandoned rd., 20 ft. N. of rd., on sunken rock; chiseled square_	319. 76
· · · · · · · · · · · · · · · · · · ·	519. 70
Eagleville, 1.5 mi. NW. of, 3.6 mi. S. of Hall Memorial School at	
South Willington, 0.2 mi. W. of Mansfield State Training School, 230	
ft. SW. of crossroads, on N. side of Coventry rd., at base of stone	400 000
wall, in solid ledge; standard tablet stamped "404 167 W 1923".	403. 639
South Willington, 2.4 mi. S. of, at rd. fork NE., on W. side of rd., on	
head wall of culvert; chiseled square	408. 44
South Willington, 1.5 mi. S. of, 75 ft. N. of crossroads, 30 ft. E. of	
rd., in pasture land, on top of sunken rock; chiseled square	379. 49
South Willington, at front entrance of Hall Memorial School, under	
N. end of portico, near base of pillar, 3 in. E. of wall, on granite stone	
in floor; chiseled cross	396. 80
South Willington, near NW. corner of factory building of Gardner	
Hall Co., on E. side of rd., on high corner of large retaining wall;	
standard tablet stamped "409 168 W 1923"	409. 303
South Willington, 1.7 mi. N. of Hall Memorial School, at 0.5 mi. S.	
of West Willington sta., 150 ft. N. of rd. forks at top of hill, on E.	
side of rd., on concrete catch basin; chiseled square	492. 80
West Willington sta., 500 ft. E. of, at crossroads garage, on front	
face of building, on NE. corner of concrete foundation, near top	
of concrete; chiseled cross	415. 92
West Willington sta., 500 ft. E. of, in SE. corner of crossroads, on	110.02
large sunken rock; chiseled square	417. 10
West Willington sta., 1.8 mi. N. of, 4.0 mi. S. of town hall at Stafford	2211 20
Springs, on E. side of rd., at bridge over S. channel of Roaring	
Brook, on S. end of concrete head wall; standard tablet stamped	
"417 169 W 1923"	417. 164
Stafford Springs, 2.8 mi. S. of, at N. end of long level tangent, 50 ft.	417. 104
	432, 68
S. of old gravel pit, on E. side of rd., on solid ledge; chiseled square_	402, 00
Stafford Springs, 1.8 mi. S. of, at highway bridge over Williamntic	
River, on NW. wing wall at point 4 ft. N. of corner of steel struc-	400 10
ture of bridge; chiseled square	430. 16
Stafford Springs, 1.7 mi. S. of, on S. abutment of R. R. bridge over	100 15
Willimantic river, on NW. corner of bridge seat; chiseled square	<b>436. 43</b>
Stafford Springs, 1.7 mi. S. of, 50 ft. W. of R. R. crossing, 15 ft. S.	
of rd., at base of rocky hill, on large sunken rock; standard tablet	
stamped "437 170 W 1923"	437. 1 <b>45</b>

Stafford Springs, 0.8 mi. S. of, on W. side of rd., about 4 ft. above rd. level, on top of large square-faced rock; chiseled squareStafford Springs, at town hall, on S. side of main entrance, near wall of building, 1 ft. E. of base of ornamental lamp post; standard tablet stamped "479 171 W 1923"	Feet 457. 22 478. 684
From Stafford Springs west along Stafford Springs-Thompsonville highway into Hartford quadrangle	
Stafford Springs, 0.8 mi. NW. of town hall, near corner of Center and West Streets, in grounds of Rhode Island Worsted Co., on N. side of shop buildings, at N. end of spillway of dam, in masonry of dam structure; standard tablet stamped "501 172 W 1923" Stafford Springs, 2.2 mi. NW. of town hall at, 1.5 mi. E. of Congregational Church at West Stafford, on N. side of rd., at top of slight rise, at edge of rd., on sloping surface of large rock; chiseled	500. 836
square	<b>525. 43</b>
rd., 15 ft. N. of corner of stone wall, on large rock; chiseled square- West Stafford, 100 ft. SW. of Congregational Church, 100 ft. W. of	559. 94
rd. S. to Crystal Lake, on S. side of rd., about 4 ft. above rd. level, on solid ledge; standard tablet stamped "551 173 W 1923" West Stafford, 1.0 mi. NW. of Congregational Church at, 800 ft.	550. 650
SE. of house, 15 ft. N. of rd., on rock outcrop near rd., on E. slope of largest part of outcrop; chiseled square	<b>7</b> 80. <b>2</b> 5
at Somers, 400 ft. W. of watering trough, on N. side of rd., at top of bank, about 7 ft. above rd. level, on top of rock outcrop; chiseled square	750. 48
Somers, 1.6 mi. E. of, 200 ft. NW. of house, on N. side of rd., 15 ft. E. of gate to field, in large sunken rock; standard tablet stamped "533 174 W 1923"	532. 844
Somers, 0.6 mi. E. of, 500 ft. W. of rd. forks, on N. side of rd., on curved curbing around lawn in front of Kibbe Place, at NW. end	
of curbing, 2 in. S. of square granite post; chiseled square Somers, 300 ft. E. of main crossroads, at front entrance of Congrega-	313. 36
tional Church, 2 in. S. of E. pillar, on granite slab; chiseled square. Somers, 0.8 mi. W. of, 1.0 mi. E. of Somersville, 0.6 mi. E. of Scantic River, in SW. corner of crossroads, on red-sandstone rock at end	271. 61
of small drain culvert; chiseled square	226. 39
county line, on N. side of rd., in head wall of large concrete culvert; standard tablet stamped "176 175 W 1923"	175. 817
From Mansfield Depot west along Mansfield-Hartford highway to Bolton Notch	
Mansfield Depot, 100 ft. NE. of, at R. R. water tank, on concrete foundation of SW. column supporting tank; chiseled squareMansfield Depot, 1.2 mi. W. of, 2.2 mi. E. of main rd. forks at Coven-	323. 21
try, 400 ft. E. of rd. forks, at top of hill, on S. side of rd., on top of large boulder; chiseled square (reported in 1928 as destroyed) Coventry, 1.1 mi. E. of, 200 ft. E. of bridge over Skungamaug River, 50 ft. W. of crossroads, on N. side of Coventry rd., on rock outcrop;	563. 40
chiseled square	484. 74

SPIRIT LEVELING IN CONNECTICUT, 1922 TO 1935	
Coventry, 0.5 mi. E. of, in SW. corner of crossroads, 10 ft. W. of large maple tree, on sunken rock; chiseled squareCoventry, in W. part of town, 400 ft. E. of large culvert, 50 ft. NW. of main rd. forks, in large sunken rock; standard tablet stamped	Feet 621. 12
"603 177 W 1923"  Coventry, 1.1 mi. W. of main rd. forks at, 1.6 mi. E. of bridge at Quarryville, about 0.4 mi. E. of Ash Brook, 0.2 mi. W. of top of hill, in SW. corner of crossroads, at base of stone wall, on W. end	602. 648
of corner stone; chiseled square————————————————————————————————————	747. 45 ·
top of hill, on S. side of rd., on large sunken rock; chiseled square—Quarryville, 340 ft. E. of bridge over Hop River, 1,500 ft. E. of church, 30 ft. N. of rd., about 3 ft. above rd. level, on sunken rock; standard	758. 14
tablet stamped "659 178 W 1923"	658. 411
bridge over river; chiseled squareU. S. C. & G. S. B. M. designated "D 9"	651. 42 582. 883
WATERBURY QUADRANGLE	
[Latitude 41°30′-41°45′; longitude 73°-73°15′]	
HARTFORD, LITCHFIELD, AND NEW HAVEN COUNTIES	
Leveling in 1923 by R. M. Wilson	
From New Milford quadrangle northeast along road near Hesseky Brook to its junction with Roxbury-Woodbury road, thence east to Woodbury	
South Britain, 3.3 mi. N. of, 3.7 mi. SW. of Masonic Temple at Woodbury, 0.2 mi. S. of Litchfield-New Haven county line, in NW. corner of Pine Tree Crossroads, in stone wall at point 10 ft. N. of its corner, in large rock at base of wall; standard tablet stamped "324 41 W 1922"	Feet 323. 505
Woodbury, 2.4 mi. SW. of, on N. side of rd., at short, steep slope, opposite E. end of barn, in solid rock; copper nail	310. 21
S. of small bridge, at door to office of garage, 6 in. NE. of NE. corner of main building of garage, on SE. end of upper concrete step; chisel cut	262. 24
From Woodbury east along Woodbury-Meriden highway into Meriden quadrangle	
Woodbury, 0.7 mi. SE. of Masonic Temple, at foot of long hill toward Waterbury, in grass triangle at Y-rd. forks, on sunken rock; chiseled cross	266. 07
Woodbury, 1.5 mi. SE. of, 300 ft. NE. of top of long hill, on N. side of rd., in large rock; copper nail	614. 02
Woodbury, 3.1 mi. SE. of, 3.1 mi. W. of town hall at Middlebury, 0.8 mi. SW. of Quassapaug Pond at its outlet, at sharp bend in rd., 200 ft. N. of rd. E., on E. side of rd., opposite stone house, in solid	F00 444
rock; standard tablet stamped "600 47 W 1922"	599. 444
cross	696. 14

THE STATE OF THE S	
Middlebury, 0.9 mi. W. of, at E. end of long curve in rd., 600 ft. SW. of	Feet
rd. forks, on N. side of rd., in solid rock; copper nail	741. 62
Middlebury, at NE. corner of public square, at front entrance of	
town hall, on W. side of door, in N. end of middle concrete step;	<b>#</b> 00 000
standard tablet stamped "723 48 W 1922"	723. 233
Middlebury, 0.6 mi. E. of town hall, at T-rd. S. to Naugatuck, in	
SE. corner of junction, on rock; chiseled cross	605. 10
Middlebury, 1.2 mi. E. of, at rd. fork W., in front of large farmhouse,	
in NE. corner of culvert; copper nail	487. 59
Middlebury, 2.4 mi. NE. of, 3.4 mi. W. of soldiers' monument at	
Waterbury, 300 ft. E. of crossroads, on N. side of rd., behind water-	.=
ing trough, in solid rock; copper nail	479. 08
Waterbury, 2.0 mi. W. of, 100 ft. S. of crossroads, on N. side of drive-	
way to house, on top of large, partly sunken granite boulder;	
standard tablet stamped "490 49 W 1922"	490. 041
Waterbury, at W. end of center public square, at SW. corner of base	
of soldiers' monument; standard tablet stamped "282 50 W 1922"	281. 448
Waterbury, in E. part of city, on N. side of rd., at SE. corner of Mill	
Plain School, in corner stone; standard tablet stamped "473 76 W	
1923"	473. 198
From Derby quadrangle north along Naugatuck-Torrington highway into	
Winsted quadrangle	
Waterburg 20 mi Staff 1 4 mi N of St Manual Changle at Name	
Waterbury, 2.2 mi. S. of, 1.4 mi. N. of St. Mary's Church at Nauga-	
tuck, 30 ft. N. of corner of stone wall on W. side of rd., on large	001 77
rock; copper nail	261. <b>77</b>
Waterbury, in S. part of town, near NE. corner of Howard Street	
bridge over Naugatuck River, 18 in. NE. of post of iron railing, in	
large stone of masonry wing wall; standard tablet stamped "247	040.005
53 W 1922"	246. 985
Waterbury, in Oakville district, at bridge over Steele Brook carrying	
main highway to Watertown, on E. end of S. concrete parapet of	055 045
bridge; standard tablet stamped "355 52 W 1922"	355. 247
Waterville, on Thomaston Avenue, on W. side of rd., on S. end of	
concrete bridge over Hancock Brook, on top of parapet; standard	
tablet stamped "292 51 W 1922"	291. 807
Waterville, 1.2 mi. N. of, 500 ft. NE. of R. R. bridge near N. end of	
yards of Chase Metal Works, in middle of S-bend in rd., on E.	
side of rd., 10 ft. from fence, in solid ledge of rock; chisel cut	297. 84
Waterville, 2.0 mi. N. of, at rd. fork W. across river, on S. side of W.	
abutment of steel bridge, cemented in concrete; copper nail	309. 52
Waterville, 3.2 mi. N. of, 3.6 mi. S. of post office at Thomaston, at	
rd. fork E., 200 ft. E. of main rd., on S. side of branch rd., near base of	
stone wall, in solid rock; standard tablet stamped "334 82 W 1923".	333. 616
Thomaston, 2.4 mi. S. of, at trolley bridge over R. R. and river, at E.	
end of girder span of bridge, 6 in. from easternmost corner of cap-	
stone, on top of tall stone pier; chiseled cross	353. 64
Thomaston, 1.4 mi. S. of, at top of small hill, on W. side of rd., in out-	
crop of solid rock; chiseled cross	362. 87
U. S. C. & G. S. B. M. designated "W 7"	392. 493
Thomaston, 1.2 mi. N. of post office at, 60 ft. N. of rd. fork W., 55 ft.	
N. of S. end of solid hogback ledge, 15 ft. E. of rd., directly opposite	
house, on solid rock; chiseled square	407. 89

Thomaston, 2.2 mi. N. of, 50 ft. S. of rd. fork E., 20 ft. W. of rd., near fence line, on large rock; chiseled square Thomaston, 3.0 mi. N. of, at N. end of yard of Fluteville School, 100 ft. NE. of school building, 35 ft. W. of roadway, about 1 ft. above ground, near base of large solid ladge, in solid rock; standard tablet	Feet 432. 17
ground, near base of large solid ledge, in solid rock; standard tablet stamped "450 194 W 1923"	449. 537
surface of solid rock; chiseled squareCampville, 0.5 mi. SE. of, on E. side of rd., on top of N. wing wall of small concrete bridge; chiseled square	443. 13 471. 84
Campville, 1,000 ft. NW. of rd. fork SW. over bridge, 30 ft. NE. of rd., in low field, on isolated ledge; standard tablet stamped "467.779	
195 W 1923", U. S. C. & G. S. designation "468"	467. 779
of concrete culvert; chiseled square	493. 54
From Derby quadrangle north along Southbury-Minortown-Litchfield highway and road into Winsted quadrangle	
Woodbury, 0.8 mi. S. of Masonic Temple, 3.2 mi. N. of Southbury, at T-rd. E. to Waterbury, on E. side of rd., in N. end of small concrete bridge; copper nail	242. 50
Woodbury, in S. part of village, 40 ft. E. of Main Street, directly in front of Masonic Temple, at base of 30-ft. cliff upon which temple stands, in solid rock; standard tablet stamped "281 42 W 1922"	281. 036
North Woodbury, 200 ft. N. of crossroads, store, and post office, on W. side of rd., on NE. corner of broken top of milestone; chiseled cross	277. 98
North Woodbury, 0.5 mi. N. of post office, at rd. forks at top of small	211. 90
hill, on S. side of rd., in large rock; copper nail	323. 10
stamped "377 44 W 1922"	376. 961
Minortown, at T-rd. S., 30 ft. N. of bridge over Nonewaug River, on S. side of rd., in large boulder; copper nail	378. 43
Minortown, 1.4 mi. NE. of, at junction of main rds. to Woodbury, Waterbury, and Litchfield, on N. side of junction, in sunken rock; standard tablet stamped "480 45 W 1922"	479. 525
Minortown, 2.7 mi. N. of, 2.7 mi. SE. of Bethlehem, near top of long hill, at Y-rd. fork E., on S. side of rd., in heading of culvert; copper	2,0,020
nail	697. 64
Bethlehem, 2.2 mi. SE. of, in SW. corner of crossroads, at top of hill, 6 ft. W. of end of stone wall, in large rock in wall; copper nail Bethlehem, 0.8 mi. SE. of, at T-rd. S., on N. side of rd. opposite junc-	786. 89
tion, in base of stone wall, on large rock; copper nail Bethlehem, 300 ft. NE. of post office, at crossroads, 10 ft. S. of corner	846. 51
of church, in sunken rock; standard tablet stamped "861 46 W 1922"  Bethlehem, in N. part of public square, on NE. corner of base stone	860. 761
of granite monument; chiseled cross	859. 85

Bethlehem, 1.4 mi. NE. of, 1.8 mi. S. of Morris, at top of long hill up from Bethlehem, in grass triangle at junction of rd. fork S., in sunken rock; copper nail	1, 066. 54
designated "N"	976. 37 898. 49
Litchfield, at front entrance of town hall, inside vestibule, at E. side of door, in granite step; standard tablet stamped "1084.502 218 W 1923", U. S. C. & G. S. designation "1085"	
From Middlebury southeast along Middlebury-Naugatuck highway into Derby quadrangle	
Middlebury, 1.6 mi. E. of town hall at, 3.9 mi. NW. of high school at Naugatuck, near foot of long hill, 100 ft. E. of rd. fork N., on N. side of rd., at concrete bridge over Hop Brook, on E. end of head wall of bridge; chiseled square	391. 66
chiseled square	325. 66
WINSTED QUADRANGLE	
[Latitude 41°45'-42°; longitude 73°-73°15']  HARTFORD AND LITCHFIELD COUNTIES	
Leveling in 1923 by R. M. Wilson	
From Waterbury quadrangle north and northeast along Waterbury-Winsted- Granby highway into Granby quadrangle	
East Litchfield, at rd. fork W., at steel-girder highway bridge over Naugatuck River, on E. side of rd., about 3 ft. below rd. level, on N. bridge seat; standard tablet stamped "509.365 196 W 1923", U. S. C. & G. S. designation "510"	Feet 509. 365 509. 18
concrete culvert; chiseled square	517. 52
wall; chiseled square  Torrington, at corner of South Main Street and Burke Avenue, at South School, on S. side of E. entrance, on granite guard stone of	
steps; standard tablet stamped "555 197 W 1923"	55 <b>4</b> . 28 <b>4</b>

Torrington, at corner of Main Street and City Hall Avenue, at city hall, at steps on S. side of main entrance, on fourth step from top; standard tablet stamped "570.637 198 W 1923", U. S. C. & G. S. designation "571"	Feet 570. 637
Torrington, at corner of North Main and North Elm Streets, at W. entrance to North School, on S. side of door, on granite step; standard tablet stamped "606 199 W 1923"	605. 969
Torrington, 1.2 mi. N. of city hall at, 200 ft. N. of rd. forks, at N. borough limit, on W. side of rd., on flat, sunken rock; chiseled square	648. 52
Torrington, 2.2 mi. N. of, 2.9 mi. SW. of post office at Burrville, near top of slight rise in rd., 60 ft. W. of rd., 50 ft. E. of R. R. tracks, 30 ft. S. of small frame house, about 4 ft. above ground, on top of large,	<b>7</b> 10.11
smooth boulder; chiseled square	719. 11
surface of outcrop; standard tablet stamped "730 200 W 1923" Burrville, 0.4 mi. SW. of post office, 150 ft. N. of bend in swampy stream close to R. R. tracks, on NW. side of rd., at base of small	729. 912
cut, on solid ledge; chiseled square————————————————————————————————————	728. 32
extreme corner of wall, on large rock; chiseled square Burrville, 1.0 mi. N. of post office at, 3.0 mi. S. of soldiers' monument at Winsted, in NE. corner of crossroads, in large concrete retaining wall at a point near its S. end and about 2 ft. above rd. level;	722. 11
standard tablet stamped "732 201 W 1923"	731. 750
track level, on NW. corner of concrete pier; chiseled square	701. 80
winsted, at corner of Park Place and South Main Street, at main building of Gilbert School, at S. entrance on W. side of building, on N. side of steps, on guard stone; standard tablet stamped	710. 71
"714 189 W 1923" Winsted, in NE. part of town, at corner of Main and Beech Streets, at office building of Wm. L. Gilbert Clock Co., 2 ft. S. of doorway at front entrace, about 6 in. above sidewalk, on water table; chiseled	713. 470
square	705. 62
end of head wall of small concrete culvert; chiseled square Riverton, 1.2 mi. SW. of, near top of hill, 50 ft. SE. of crossroads, in pasture land, on W. sloping face of large sunken rock at point	642. <b>93</b>
about 1 ft. above ground; chiseled square Riverton, on W. side of rd., at S. end of bridge over Still River, on top	760. 55
of concrete wing wall; standard tablet stamped "500 188 W 1923".  Riverton, at front entrance of Union Church, 6.7 ft. E. of center of	499. 881
door, on upper edge of foundation stone; chiseled cross	503. 98

Riverton, 0.9 mi. N. of Union Church, at rd. forks at point where main rd. leaves river and starts uphill, 50 ft. NW. of frame house, on W. side of rd., on S. end of concrete retaining wall; chiseled square	Feet 517. 19
Riverton, 2.0 mi. NE. of, at top of small hill, in S. corner of rd. forks to NE. and SE., at corner of stone wall, about 8 ft. above rd. level, on top of large rock; chiseled square	875. 08
From Granby quadrangle west and northwest along New Hartford-Canaan highway into Sandisfield quadrangle	
Winsted, 3.5 mi. SE. of soldiers' monument at, 200 ft. W. of sharp curve in rd., 100 ft. E. of rocky bank, 5 ft. above rd. level, on top of large rock at S. edge of rd.; standard tablet stamped "569 190	
W 1923"	568. 339
square Winsted, 1.5 mi. SE. of, 60 ft. E. of culvert, 30 ft. S. of rd., 10 ft.	647. 30
below rd. level, on large rock flush with ground; chiseled square Winsted, at corner of Main and Elm Streets, at Winchester Hotel, in vestibule at front door, in granite step; standard tablet stamped	689. 15
"178 202 W 1923" Winsted, near W. end of Main Street, at Public Library, on N. side of	718. 189
steps at front entrance, on guard stone; standard tablet stamped "763 203 W 1923"	762. 623
fork W., at curve where river is close to rd., on NE. side of rd., on outcrop of rock; chiseled square	897. 23
Winsted, 4.0 mi. NW. of, 0.2 mi. N. of Colebrook sta., on E. side of rd., 10 ft. E. of end of stone wall, 10 ft. N. of spring, on large rock;	1 040 44
chiseled square	1, 043. 46
stamped "1128 204 W 1923"	1, 127. 956
of large sunken rock; chiseled squareNorfolk, 2.8 mi. SE. of, 525 ft. E. of driveway N. to house, on N. side of rd., under fence line, on flat, embedded rock; chiseled	1, 296. 36
square Norfolk, 1.6 mi. E. of, 125 ft. E. of rd. forks NE. and E., 100 ft. S. of	1, 408. 07
schoolhouse, on NE. side of main rd., on large rock outcrop at point near its top; standard tablet stamped "1441 205 W 1923" Norfolk, 0.9 mi. E. of post office, 50 ft. S. of crossroads, at top of hill, 3 ft. N. of stone wall, about 2 ft. above rd. level, on large	
sunken rock; chiseled square	1, 420. 04
stamped "1230 206 W 1923"	1, 229. 81 <b>3</b>
driveway leading uphill to house, on S. side of rd., on top of large rock projecting 2 ft. above ground; chiseled square	981. 87

# From Cornwall quadrangle east and southeast along Cornwall-Torrington highway to Torrington

mgnway w torringen		
Goshen, in NE. corner of crossroads, in front of town hall, on concrete base of soldiers' monument; standard tablet stamped "1334	Feet	
216 W 1923"	1, 333. 514	Ŀ
Reference mark, 200 ft. E. of tablet, near N. corner of horse sheds behind church, near fence corner, on large boulder; chiseled square.	1, 320. 76	
Goshen, 0.9 mi. E. of town hall, at rd. fork N., on S. side of rd., in stone wall, at E. side of gate, about 1 ft. above ground, on upper surface of large stone at end of wall; chiseled square	1 061 60	
Goshen, 2.1 mi. E. of, 2.6 mi. NW. of crossroads at West Torrington, at Goshen-Torrington town line, on S. side of rd., 3 ft. NW. of	1, 261. 68	
fence corner, on large sunken rock; chiseled square West Torrington, 1.4 mi. NW. of, 450 ft. E. of crossroads, 175 ft. W. of cemetery, 30 ft. N. of rd., in open field, about 3 ft. above ground,	1, 269. 10	
on top of large rock; standard tablet stamped "963 217 W 1923" Reference mark, 450 ft. W. of tablet, at crossroads, 100 ft. N. of	962. 778	
main rd., at fence line on W. side of crossroad, on sunken rock; chiseled square	990. 20	
West Torrington, 0.9 mi. NW. of, 500 ft. NW. of rd. fork N., on W.	990. 20	
end of concrete dam of small reservoir; chiseled square West Torrington, 175 ft. E. of crossroads, 1.7 mi. NW. of city hall	<b>7</b> 85. 68	
at Torrington, on S. side of rd., at steel bridge over Hart Brook,		
on W. bridge seat; chiseled square	637. 11	
From Waterbury quadrangle northeast along Litchfield-Torrington highway to Torrington		
Litchfield, 1.7 mi. NE. of town hall, 4.4 mi. SW. of city hall at Torrington, at top of long hill, 100 ft. SW. of crossroads, on NW: side		
of rd., in stone retaining wall at point 20 ft. NE. of its SW. end, on capstone; chiseled square	1, 145. 10	
Torrington, 2.6 mi. SW. of, 200 ft. NE. of farmhouse, at SW. end of	1, 145. 10	
long, level tangent of rd., on S. side of rd., on large embedded boulder;		
chiseled square	866. 24	
WOODSTOCK QUADRANGLE		
[Latitude 41°45′-42°; longitude 72°-72°15′]		
TOLLAND AND WINDHAM COUNTIES		
Leveling in 1923 by R. M. Wilson		
From Norwich quadrangle northeast along Willimantic-Eastford highway to Phoenixville		
North Windham, on concrete steps at rear of store of B. O. Moore, on top step; chiseled cross, State B. M	Feet 260. 08	
spillway, on capstone; chiseled squareNorth Windham, 0.8 mi. NE. of crossroads, 200 ft. N. of rd. fork	238. 93	
SE. to Scotland, at crossing of Ames Brook, on E. side of rd., on N. end of head wall of concrete culvert; chiseled square	280. 11	

North Windham, 1.4 mi. NE. of, 650 ft. S. of rd. fork to Danielson, 100 ft. N. of farmhouse, on E. side of rd., in large outcrop of solid rock; standard tablet stamped "308 158 W 1923"North Windham, 1.5 mi. NE. of, 2.0 mi. SW. of Congregational Church at Chaplin, about 225 ft. SW. of rd. fork to Danielson, at culvert, on SW. end of NW. concrete head wall; chiseled cross,	Feet 307. 737
State B. M	309. 18
State B. MChaplin, in S. part of town, 0.5 mi. S. of Congregational Church, at top of hill, at rd. fork W., 15 ft. W. of main rd., 20 ft. N. of branch	287. 85
rd., in front yard of house, on outcrop of solid rock; bottom of chiseled square	420. 35
concrete carriage steps, on second step from bottom; chiseled cross, State B. M.	401. 77
Chaplin, 40 ft. NW. of NW. corner of Congregational Church, 150 ft. W. of rd., in solid ledge; standard tablet stamped "417 159 W 1923". Chaplin, 1.6 mi. N. of Congregational Church at, near top of hill, 20 ft. E. of rd., about 6 ft. below rd. level, in open field, on large	416. 566
sunken rock; chiseled squareChaplin, 2.0 mi. NE. of, at rd. fork E., 100 ft. N. of small stream,	424. 62
20 ft. W. of rd., on large granite rock; chiseled square	368. 98
standard tablet stamped "430 160 W 1923"	430. 246
Phoenixville, 1.2 mi. S. of bridge at, 300 ft. SW. of S-bend in river, 100 ft. S. of end of open field, on W. side of rd., in base of stone	445. 91
wall, on large boulder; chiseled squarePhoenixville, at bridge over Natchaug River, on N. side of W. end of	435. 29
bridge, on concrete base for railing; chiseled cross, State B. M Phoenixville, 50 ft. S. of SE. corner of bridge, 100 ft. E. of rd. forks at stores, in outcrop of solid rock; standard tablet stamped "463	469. 58
161 W 1923''From Phoenixville southeast along Ashford-Killingly highway into Putnam	462. 433
quadrangle	
Phoenixville, 0.9 mi. E. of bridge at, 200 ft. E. of top of third steep grade up from Phoenixville, 10 ft. S. of rd., on top of large boulder; chiseled square	695. 30
Phoenixville, 1.9 mi. SE. of, 2.7 mi. W. of post office at Abington, at highest part of rise, on N. side of rd., about 2 ft. above rd. level,	090. 00
on outerop of solid rock; chiseled square	725. 01
ard tablet stamped "605 162 W 1923"	604. 816

Abington, 0.3 mi. W. of crossroads and post office, 200 ft. E. of ceme-	
tery, on S. side of rd., on W. end of head wall of concrete culvert;	Feet
chiseled square	541. 24
Abington, about 100 ft. E. of crossroads at post office, at main en-	
trance to Episcopal Church, on NW. corner of large granite door-	
step; chiseled cross, State B. M.	549. 93
Abington, 0.4 mi. E. of post office, 400 ft. N. of R. R. sta., on N. side	
of rd., on E. bridge seat of iron highway bridge over R. R. tracks;	
standard tablet stamped "516 164 W 1923"	515. 876

## INDEX

Page	Page
Abington 41, 61-62	Connecticut River 26, 44, 45
Allyns Point	Cooperation 1-2
Anderson, J. A., leveling by 49	Cornwall 10
Ansonia 14	Cornwall Bridge 9
Attawaugan 42-43	Cornwall quadrangle 9-10
Avon	Coventry53-54
Ayer Hill 50	Cromwell 25
	Cudjoe Brook 61
Baldwin, D. H., leveling by	
Banksville	Danbury 10-11, 13
Bantam River	Danbury quadrangle 10-13
Beacon Falls 14	Danielson 43
Benchmarks, forms of	Datum of elevations 4-5
preservation and restoration of	Dayville43
Bethany 15, 28	Deep River45
Bethel	Derby quadrangle 14-15
Bethlehem 56-57	Dooley Pond
Blackberry River	Durham 21, 25
Bloomfield 22	77-1 77
Bolton Notch 54	Eagleville 52
Branchville10,37	East Canaan 48
Breakneck Pond 8	East Haddam 44
Bridgeport 7, 37	East Hampton 16, 26
Bridgeport quadrangle	East Hartland 18, 21
Bridgewater	East Litchfield
Brookfield	East Lyme 30, 46
Brookfield quadrangle	Easton 11, 37
Brooks Vale	Eccleston Brook 51
Burrville 5	Eightmile River 46
Campville	Elevations, datum of 4-5
Canaan 9,48	Falls Village 9
Cannondale 37	Farmington 20, 23
Canton 19	Farmington River
Centerbrook 45	Fawn Creek 17
Centerville 29	Fluteville School 56
Central Village	Folly Brook 25
Chapel Hill 33	Franklin Hill
Chaplin	Freshwater Brook 22
Cherry Brook 19	11000 11000 21000
Cheshire 23, 29	Gales Ferry 32
Chester44-45	Gardner Lake Church
Chesterfield	Giant Neck Beach Club
Clinite, R. G., leveling by 20-21,	Gilead quadrangle
33-34, 44, 47, 48-49, 51	Glenville 49-50
Cobalt26	Goshen 60
Colchester 17	Granby 18
Colebrook 59	Granby quadrangle
Columbia 16	Granville quadrangle 20-21
Columbia University Summer School of Sur-	Groton
veying, leveling by 2	Guilford quadrangle 21
Connecticut, cooperation with	
index map of, showing quadrangles into	Haddam 21, 44
which the State is divided and	Hamburg 46
routes followed by levelmen 5-6	Hancock Brook
. 3400 1010 104 03 1010 1110 1111 0 0	

### INDEX

	rage		Page
Hart Brook		North Bridgeport	•
Hartford	22, 26	North Hollow	20
Hartford quadrangle	. 22	North Somers	46
Hartland		North Stonington	50-5
Hazardville	. 22	North Windham	60-61
Hebron	. 16	North Woodbury	56
Higganum	21, 27	North Woodstock	8
Hop Brook (Waterbury quadrangle)		Northford	21, 30
Hop River (Tolland quadrangle)	. 54 '	Northville	38
Horse Pond	47	Norwalk	37
Housatonic River 9, 12	, 14, 35	Norwalk quadrangle	37
Hubbard Brook	20	Norwalk River	37
		Norwich 32-33, 39-	-40, 50
Jewett City	28, 39	Norwich quadrangle	38-40
Killingly	43		
King, C. A., work by		Oakdale	33
<b></b>	-	Old Lyme	45, 46
Lake Taunton	12	D.1	40 41
Lake Waramaug	35	Palmer quadrangle	
Lebanon Brook	8	Personnel	5
Leveling, classification of	2-3	Phoenixville	61
Lime Rock	9	Pinehurst Club	44
Litchfield		Plainfield	
Long Hill	15	Plainville	23
Lord Hill	46	Plantsville	23
Lyme. See East Lyme; Old Lyme.		Pomfret	
• • •		Port Chester, N. Y	50
Mansfield Depot	53	Portland	26
Maps, topographic	5	Powers Lake	34, 47
Marble Dale	35	Putnam	42
Marion	24	Putnam quadrangle	41-43
Marlboro	16, 17	0	
Mashamoquet Brook	41	Quarryville	54
Mashapaug	8	Quassapaug Pond	54
McGuire, J. C., leveling by		Quinnipiac River	29
Meriden	24, 26	Ridgewold	11
Meriden quadrangle		Riverton	
Middlebury54-		Roaring Brook	52
Middletown 25,		Rocky Hill	25
Middletown quadrangle	25-27	Rogers Lake	46
Mill Brook	27	Roxbury	36
Milldale	23, 24	Trouble of the second s	00
Minortown	56	Salem17,	21 47
Montowese	29	Sandisfield quadrangle	44
Moosup	27	Sandy Hook	12
Moosup quadrangle	27-28	Sandy Hook Bridge	
Morgan River	19	Saybrook	12, 13 45
Morris	57	Saybrook quadrangle	
Mount Carmel	29	Scantic River	49-47
Muddy Pond	. 8	Sea level, mean	4-5
Note-base Dimen	40.01	•	14
Natchaug River		SeymourShailerville	44
Naugatuck 14, 15,		· · · · ·	-
Naugatuck River	· ·	Sheffield quadrangle	48
New Hartford	19	Shelton	
New Haven		Shepaug	
New Haven quadrangle		Shepaug River	13
New London		Shetucket River	39
New London quadrangle		Somers	53
New Milford		Somersville	53
New Milford quadrangle		South Britain	
New Preston	35	South Willington	52
Newtown	1	South Windham	38
Noank	51	Southbury	15
Nonewaug River	56	Southington	23
Norfolk	59	Springfield quadrangle	
North Ashford	8	Stafford	41

### INDEX

Page	Page
Stafford Springs	Waterbury quadrangle 54-57
Staffordville	Waterville 55
Stamford quadrangle	Wauregan 27, 43
Stanwich	West Cornwall 9
Steele Brook	West Goshen
Stepney 12	West Granby 18
Still River 58	West Norfolk 44
Stonington quadrangle	West River 28
Straitsville	West Stafford
Stratford 7, 15	West Suffield 49
Suffield48	West Torrington 60
	West Willington 52
Tariffville18	Westerly, R. I
Paunton, Lake 12	Wethersfield 25
Phomaston 55-56	Wheeler, E. M., leveling by 8, 40-41
Thompsonville	Wheelers Pond 33
Tibbott, E. W., work by	Willimantic 17, 38, 40
Folland quadrangle 52-54	Willimantic River 52
Porrington 57-58, 60	Willow Spring Farm
	Wilson, R. M., leveling by 7, 9-20, 21-33, 35-40,
Uncasville 31-32	41-42, 44-47, 48, 50-51, 52-62
United States Coast and Geodetic Survey,	Wilton37
leveling by 1-3	Winsted 58, 59
United States Naval Marine Base 32	Winsted quadrangle 57-60
United States Submarine Base	Woodbury54,56
Upper Stepney 12	Woodstock quadrangle 60-62
Waramaug, Lake	Yale Engineering Camp 34, 49
Waterbury 24, 55	Yantic 38-37