

4/12/2007 157 7.2 741 27.6 301 367 44.7 18.8 0.67 97.3 32.0 0.53 40.1 29.4 243 <6 <0.2 0.12 464 601 3.1

31 175917066205400

analytical results from sampled wells and piezometers given in table 1 were used to prepare the trilinear diagrams presented A more thorough discussion of the areal variation of dissolved solids concentrations and hydrochemical facies is presented by subareas due to the heterogeneous nature of aquifer hydrologic and hydrogeologic conditions. The subareas with

Dissolved solids concentrations in this area ranged from 324 to 5,860 mg/L (fig. 3). Dissolved solids in well 5 had a decrease in dissolved solids concentration of 61 mg/L from 1986 (Gómez-Gómez, 1991) to 2007. The principal

Dissolved solids concentrations ranged from 330 to 472 mg/L (fig. 3). The lower dissolved solid concentrations to concentration decrease of 22 mg/L from 1986 to 2007. The principal hydrochemical facies is calcium-bicarbonate (figs. 4B

an increase of 586 mg/L in dissolved solids concentration from 1986 to 2007 (Gómez-Gómez, 1991). This increase was probably caused by the upconing of groundwater from deeper parts of the aquifer. The historic trend of chemical characteristics in well 28 indicates a decrease of 144 mg/L in dissolved solids concentration and a change from

	_
Middle	Juana Díaz Formati
	Ponce Limestone
Early	Volcanics

Map number (fig.2)	USGS site identification	Latitude Longitude (NAD83)	Date of sample collection	Depth of well (feet)	рН	Specific conduc- tance (µS/cm)	Tempera- ture (Degrees C)	Acid neutra- lization capacity, (mg/L as CaCO <sub>3</sub> )	Bicarbo- nate (mg/L as HCO <sub>3</sub> )	Ca	Mg	К	Na	CI	F	SiO 2	SO ₄	B (µg/L)	Fe (µg/L)	Mn (µg/L)	Br	Dis- solved solids, sum of consti- tuents	Cl/Br (molar basis)	Sodium adsorption rate (SAR)
32	175944066204200	175937 662040	4/12/2007	na	7.1	777	28.2	279	340	66.7	24.8	0.97	62.4	47.5	0.43	37.4	39.2	179	<6	<0.2	0.17	454	630	na
33	175853066182800	175846 661827	4/18/2007	na	7.1	1,040	28.3	317	386	83.6	30.7	1.55	95.4	75.2	0.42	36.8	83.0	276	<6	0.5	0.35	637	484	na
34	175826066180600	175819 661805	4/4/2007	na	7.0	906	29	303	369	94.3	26.2	1.07	59.8	57.5	0.31	39.3	73.9	184	<6	<0.2	0.22	541	589	na
35	175851066174600	175843 661743	4/4/2007	120	7.1	819	28.6	277	336	87.5	24.1	1.04	50.8	49.0	0.29	38.0	68.9	161	<6	< 0.2	0.19	492	581	na
36	175823066164600	175816 661645	4/17/2007	na	6.9	884	27.7	293	357	91.9	28.6	1.37	57.6	51.7	0.33	38.4	65.8	153	<6	<0.2	0.20	545	583	1.3
37	175708066163001	175701 661629	5/22/2007	50	7.0	1,740	27.2	254	310	141	65.7	2.32	102	345	0.22	41.8	65.9	184	156	21.3	1.27	936	612	na
38	175708066163000	175701 661629	5/22/2007	115	6.7	7,740	27.7	203	248	578	251	4.75	609	2,390	0.30	38.8	246	178	6	0.41	8.53	4,260	631	na
39	175708066163002	175701 661629	5/22/2007	220	6.6	31,000	28.2	179	218	1,970	988	15.4	4,180	11,000	0.12	30.6	1,520	392	103	25.1	39.9	19,900	621	na
40	175748066160400	175741 661605	4/4/2007	162	7.3	874	27.4	315	384	79.7	26.9	0.93	68.2	45.3	0.38	40.7	50.8	177	<6	< 0.2	0.23	537	444	1.7
41	175810066152700	175803 661526	4/18/2007	120	7.0	810	28	261	318	80.3	26.6	0.83	53.4	47.3	0.34	39.1	54.1	125	3	0.2	0.22	502	485	na
42	175858066151600	175851 661515	4/3/2007	na	7.1	869	28.3	251	306	85.3	28.8	0.96	48.8	62.9	0.28	37.7	71.6	109	<6	0.6	0.27	527	525	1.2
43	175735066151800	175728 661517	5/17/2007	82	7.0	1,340	27.5	431	525	110	58.4	0.5	98.3	117	0.39	39.7	118	227	<6	4.9	0.44	810	599	na
44	175721066151400	175714 661513	5/16/2007	87	7.2	870	27.3	297	362	90.8	31.2	1.06	54.8	61.9	0.29	39.2	51.5	121	16	<0.2	0.24	530	258	na
45	175721066151401	175714 661513	5/16/2007	20	7.0	3,560	27.5	275	335	216	126	1.12	222	852	0.97	37.0	169	375	<6	694	2.86	1,880	298	na
46	175804066150700	175757 661506	4/4/2007	150	7.1	1,150	27.8	309	377	85.4	22.8	1.23	129	96.5	0.27	39.4	96.9	286	<6	<0.2	0.42	747	518	3.2
47	175854066144500	175847 661444	4/2/2007	na	7.1	1,140	28.8	341	416	96.2	25.3	0.96	106	105	0.48	38.9	59.5	264	<6	0.2	0.40	698	592	na
48	175916066144000	175908 661435	4/2/2007	300	6.9	1,110	27.6	311	379	88.2	16.9	1.07	117	107	0.63	33.5	63.4	314	<6	1.7	0.38	614	635	na
49	175711066143600	175704 661435	5/16/2007	74	6.8	6,060	28.1	379	462	409	195	2.5	700	1,510	0.47	39.2	699	838	<6	18.2	4.76	3,810	715	na
50	175711066143601	175704 661435	5/17/2007	17	7.5	4,320	28.5	419	509	63.8	43.0	6.24	794	1070	0.42	38.2	158	566	8.4	242	3.75	2,590	643	na
51	175828066142200	175821 661421	4/2/2007	na	7.0	977	28.4	309	377	85.0	30.2	0.97	74.1	80.5	0.32	38.4	44.7	192	<6	<0.2	0.36	582	504	na
52	175822066134800	175815 661348	4/2/2007	118	7.1	993	27.9	315	384	89.0	27.9	1.11	84.0	86.3	0.34	38.4	45.2	219	<6	< 0.2	0.32	598	608	na
53	175812066133200	175805 661331	4/18/2007	150	7.1	1,290	27.8	379	462	86.3	30.3	1.08	148	130	0.43	38.8	84.8	395	8	0.2	0.48	757	610	3.5
54	175824066130900	175816 661309	4/4/2007	na	7.5	1,250	29.3	451	548	23.6	7.5	0.51	246	71.5	1.81	35.8	87.5	711	16	0.3	0.28	758	576	na
55	175755066105000	175748 661049	4/3/2007	85	6.8	673	27.9	269	328	65.9	21.8	0.92	45.6	38.2	0.32	35.6	16.5	114	<6	<0.2	0.14	393	615	na
56	175747066101000	175740 661009	4/3/2007	na	6.8	825	27.7	336	410	47.8	22.0	0.75	98.7	46.9	0.60	36.1	23.0	203	<6	< 0.2	0.16	484	661	na
57	175728066100900	175721 661008	5/2/2007	na	7.5	1,270	28.7	497	604	57.1	59.6	0.53	141	105	0.65	37.5	39.2	421	80	158	0.30	744	789	na
58	175719066085500	175713 660901	5/17/2007	99	7.3	572	27.8	205	250	48.3	21.8	0.31	44.7	39.4	0.51	39.1	24.5	116	<6	0.7	0.13	345	683	na
59	175832066031300	175827 660312	4/3/2007	120	6.3	449	28.2	123	150	36.0	9.6	0.54	42.0	40.2	0.27	30.9	30.7	99.2	<6	<0.2	0.14	267	647	na
60	175840066024100	175833 660240	4/3/2007	na	6.6	669	28.5	215	262	63.2	23.7	0.45	47.3	56.1	0.27	37.3	42.3	86.2	<6	0.3	0.19	403	665	na
61	175832066022000	175823 660216	4/3/2007	na	6.9	783	27.5	201	245	63.8	26.4	0.46	54.1	81.9	0.28	37.0	57.2	100	<6	<0.2	0.29	446	637	na

irrigation water.

to the Río Jueyes area, Puerto Rico.



modified from U.S. Geological Survey OFR 98-38. (Bawiec, 2001) Roads from the P.R. Department of Transportation. Lambert conformal conic projection. North American Datum 1983. Figure 5. Hydrochemical facies in the South Coast aquifer, April 2 through May 30, 2007



Figure 6. Chloride-to-bromide ratio as a function of chloride in groundwater from wells in the South Coast aguifer, April 2 through May 30, 2007.

## GROUNDWATER-QUALITY SURVEY OF THE SOUTH COAST AQUIFER OF PUERTO RICO, APRIL 2 THROUGH MAY 30, 2007 By José M. Rodríguez and Fernando Gómez-Gómez 2009

## The Río Jueyes to the Río Seco

Dissolved solids concentrations in this area ranged from 492 to 19,900 mg/L (fig. 3). Wells 37 (936 mg/L), 38 (4,260 mg/L), and 39 (19,900 mg/L) were drilled to 50, 115, and 225 feet, respectively (table 1). These results are evidence of the mixing of freshwater and saline water related to depth in the aquifer. Dissolved solids concentrations increased in wells 43 (270 mg/L), 51 (70 mg/L), 52 (151 mg/L), and 53 (130 mg/L) from 1986 to 2007 (Gómez-Gómez, 1991). The area where these wells are located is classified as having the potential of changing its water type from calcium-bicarbonate to calcium-chloride or sodium-chloride (fig. 5). The dissolved solids 800-contour-line delineated inland near wells 43 and 49 coincides with a buried bedrock-high inferred by Renken and others (2002). In the Río Jueyes to the Río Seco area, the principal water type is calcium-bicarbonate (figs. 4D and 5). Calcium-chloride water type was detected in wells 37, 38, 45, and 49 located near the coastline in the Salinas area (fig. 5). Well 39 is on the boundary between the calcium-chloride and sodium-chloride types and well 50 indicates a sodium-chloride water type. Well 54 showed sodium-bicarbonate water type that is associated with inter-fan areas. Lower dissolved solids concentrations distribution east of the Río Nigua indicates that the aguifer is affected by streamflow infiltration. East of the Río Seco Dissolved solids concentrations in this area ranged from 267 to 744 mg/L (fig. 3). Dissolved solids concentration in well 55 increased from 320 to 393 mg/L from 1986 to 2007. The principal water type in this area is the calcium-bicarbonate (figs. 4*E* and 5). Well 56 plots on the boundary of calcium-sodium bicarbonate type water (fig. 4*E*). Chloride-to-Bromide Ratio in Groundwater

Figure 6 shows the chloride-to-bromide ratio on a mole per mole basis in relation to chloride showing the theoretical freshwater-saltwater mixing line. The molar chloride-to-bromide ratio of seawater is approximately 640, based on chloride and bromide concentrations of 19,000 and 67 mg/L, respectively (Hem, 1989), which is similar to low chloride freshwater from wells located near the streams flowing through the coastal plain. Groundwater mixing between these endpoint sources will yield a proportional value to each that plots along the freshwater-seawater mixing line (Land and others, 2004). Groundwater with higher chloride concentration (above 250 mg/L) from wells 2, 3, 5, 23, 26, 28, 29, 37 to 39, 45, 49, and 50 reflects the mixing with seawater. Wells 16 to 19 and 24 in the Santa Isabel area and wells 44 and 45 in the Salinas area showed a low chloride-to-bromide ratio (less than 300) indicative of bromide enrichment relative to chloride. Bromide enrichment is associated with brine sources (Morell and others, 1986) and the use of pesticides and their application to agricultural fields (Flury and Papritz, 1993; Vengosh and Pankatov, 1998; Custodio and Alcalá-García, 2003). Classification of Groundwater Quality Groundwater samples collected from irrigation wells were classified (fig.7) using the U.S. Department of

Agriculture (USDA) irrigation water classification diagram (Richards, 1954). Water is classified as being a low, medium, high, or extremely high sodium and salinity hazard, using the sodium adsorption ratio (SAR) and the specific conductance. Most of the samples from wells used for irrigation were in the classification of low sodium hazard and medium to high salinity hazard. High salinity hazard water can be used for irrigation only in soils with moderate to good permeability. Wells 2, 3, and 29 were classified as very high salinity hazard water. Water in this classification is generally undesirable for irrigation and is only suitable for occasional use on soils of good or high permeability (Richards, 1954). During the sample collection period, users of groundwater from well 29 attributed the adverse effects to their crops on the quality of the All groundwater samples were classified into four categories based on the dissolved solids concentrations and the specific conductance: fresh, slightly saline, moderately saline, and very saline (fig. 8; Robinove and others, 1958; Díaz, 1974). All samples from public-supply, domestic, and industrial wells were in the freshwater category. Seven samples from public-supply wells had dissolved solids concentrations above 500 mg/L, which is the drinking-water secondary maximum contaminant level (SMCL) for dissolved solids (U.S. Environmental Protection Agency, 2003). Most samples from irrigation wells were classified as freshwater; however, four wells plotted in the slightly saline category (wells 2, 3, 16, and 29). Samples from piezometers near the coast in Santa Isabel and Salinas (wells 38, 39, 45, 49, and 50) were in the slightly (wells

## **References Cited**

Conclusions







**Figure 4C.** Piper diagram showing main groundwater constituents and historical data in the Río Descalabrado

50 PERCENT CHLORIDE CALCIUM

the Río Descalabrado area, Puerto Rico.





from Richards, 1954).

**ΕΧΡΙ ΔΝΔΤΙΩΝ** \*45 Data point and well number 100 1.000 CHLORIDE, IN MILLIMOLES PER LITER





A synoptic groundwater-quality survey was conducted by the U.S. Geological Survey in the South Coast aquifer from Ponce to Arroyo in south-central Puerto Rico from April 2 through May 30, 2007. The data obtained consisted of in-situ from Ponce to Arroyo in south-central Puerto Rico from April 2 through May 30, 2007. The data obtained consisted of in-situ from Ponce to Arroyo in south-central Puerto Rico from April 2 through May 30, 2007. The data obtained consisted of in-situ from Ponce to Arroyo in south-central Puerto Rico from April 2 through May 30, 2007. The data obtained consisted of in-situ from Ponce to Arroyo in south-central Puerto Rico For Physical properties and water sample collection for laboratory analyses of common dissolved constituents. An total of 61 water samples were collected. These data were used to define the regional distribution of dissolved solids concentrations above 800 mg/L. In general, dissolved solids concentrations below 500 mg/L were detected near streams and concentrations above 800 mg/L matched with areas of potential mixing of freshwater infiltration through soils and surficial deposits. Calcium-chloride type associated with the intrusion of saline water. Shawater and freshwater Instable and Salinas. Hydrochemical facies delineated in this survey are similar to those diffied by a USGS study conducted in 1986. Compared to the 1986 conditions, changes were observed in the Ponce and satia lashel and Salinas. Hydrochemical facies were detected, respectively. The chloride-to-bromide ratio in groundwater samples is evidence that mixing of freshwater is occultions, changes were classified based on the strata slabel and Salinas. Some wells in the Santa Isabel and Salinas areas showed a low chloride-to-bromide ratio, which is associated with the Santa Isabel and Salinas. Hydrochemical facies and industrial wells were in the freshwater and salina samples from public-supply, domestic, and industrial wells were in the freshwater and salina samples in the Santa Isabel and Salinas. Amonyo	<ul> <li>Flury, M., and Papritz, A., 1993, Bromide in the natural environment: Occurrence and toxicity: Journal Environmental Quality, 22, p. 747-758.</li> <li>Giusti, E.V., 1971, Water resources of the Coamo area, Puerto Rico: U.S. Geological Survey Water-Resource Bulletin 9, 31 p.</li> <li>Glover, Lynn, 1971, Geology of the Coamo area, Puerto Rico, and its relation to the volcanic arc-trench associatio U.S. Geological Survey Professional Paper 636, 102 p., 4 pls.</li> <li>Hem, J.D., 1989, Study and interpretation of chemical characteristics of natural water: U.S. Geological Survey Water-Supply Paper 2254, 263 p.</li> <li>Land, M., Reichard, E.G., Crawford, S.M., Everett, R.R., Newhouse, M.W., and Williams, C.F., 200 Ground-water quality of coastal aquifer systems in the West Coast Basin, Los Angeles County, Californi 1999-2002: U.S. Geological Survey Scientific Investigations Report 2004-5067, 80 p.</li> <li>Morell, I., Medina, J., Pulido, A., and Fernadez-Rubio, R., 1986, The use of bromide and strontium as indicator marine intrusion in the aquifer of Oropesa-Torreblanca, in Boekelman, R.H. and others, eds., Proceedings 9 Saltwater Intrusion Meeting (SWIM), Water Management Group, Department of Civil Engineering: The Netherlands, Delf University of Technology, p. 629-640.</li> <li>Panno, S.V., Hackley, K.C., Hwang, H.H., Greenberg, S.E., Kaprac, I.G, Landberger, S., and O'Kelly, D.J., 200 Characterization and identification of Na-Cl sources in ground water: Ground Water, 44, no. 2: 176-187.</li> <li>Piper, A.M., 1944, A graphic procedure in the geochemical interpretation of water analyses: American Geophysic Union Transactions, v. 25, p. 914-923.</li> <li>Gómez-Gómez, Fernando, 1991, Hydrochemistry of the South Coastal Plain Aquifer system of Puerto Rico and i relation to surface water recharge, in Gómez-Gómez, Fernando, Quiñones- Aponte, Vicente, and Johnson, A. eds., Regional Aquifer Systems of the United States: Aquifers of the Caribbean Islands: American Wat Association Monograph Series No. 15, Internati</li></ul>
References Cited	Renken, R.A., Ward, W.C., Gill, I.P, Gómez-Gómez, Fernando, Rodríguez-Martínez, Jesús, and others, 200 Geology and hydrogeology of the Caribbean Islands Aquifer System of the Commonwealth of Puerto Rico and the U.S. Virgin Islands: U.S. Geological Survey Professional Paper 1419, 139 p., 5 pls.
Bawiec, Walter, 2001, Geology, geochemistry, geophysics, mineral occurrences, and mineral resources assessment for the Commonwealth of Puerto Rico: U.S. Geological Survey Open-File Report 98-38.	Richards, L.A., ed., 1954, Diagnosis and improvement of saline and alkali soils: Washington, D.C., U. Department of Agriculture Agricultural Handbook No. 60, 160 p.
Custodio, Emilio, and Alcalá-García, Francisco, 2003, El potencial de la relación Cl/Br como indicador del origen de la salinidad de los acuíferos costeros españoles: Tecnología de la intrusión de mar en acuíferos costeros, Instituto Geológico y Minero de España, p. 401-412.	Robinove, C.J., Langford, R.H., and Brookhart, J.W., 1958, Saline-water resources of North Dakota: U. Geological Survey Water-Supply Paper 1428, 72 p.
Davis, S.N., Whittemore, D.O., and Fabrika-Martin, J., 1998, Uses of chloride/bromide ratios in studies of potable water: Ground Water, 36, no. 2: 338-350.	Rodríguez-Martínez, Jesús, Santiago-Rivera, Luis, Rodríguez, J.M., and Gómez-Gómez, Fernando, 200 Surface-water, water-quality, and ground-water assessment of the municipio of Ponce, Puerto Rico, 2002-200 U.S. Geological Survey Scientific Investigations Report 2005-5243, 96 p., 2 pls.
Díaz, J.R., 1974, Coastal salinity reconnaissance and monitoring systemsouth coast of Puerto Rico: U.S. Geological Survey Open-File Report 74-1, 28 p.	U.S. Environmental Protection Agency, 2003, National Secondary Drinking Water Standards: Office of Water EPA 816-F-03-016.
^	U.S. Geological Survey, variously dated, National field manual for the collection of water-quality data: U. Geological Survey Techniques of Water-Resources Investigations, book 9, chaps. A1-A9.

Vengosh, A., and Pankatov, I., 1998, Chloride/bromide and chloride/fluoride ratios of domestic sewage effluents and associated contaminated ground water: Ground Water, 36, no. 5: 815-824.



Figure 4E. Piper diagram showing main groundwater constituents and historical data east of the Río Seco area,