

NASA/TM—2008-214991



NASA's PEM Fuel Cell Power Plant Development Program for Space Applications

Mark A. Hoberecht

Glenn Research Center, Cleveland, Ohio

NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI Program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Reports Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.
- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include creating custom thesauri, building customized databases, organizing and publishing research results.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at 301-621-0134
- Telephone the NASA STI Help Desk at 301-621-0390
- Write to:
NASA Center for AeroSpace Information (CASI)
7115 Standard Drive
Hanover, MD 21076-1320



NASA's PEM Fuel Cell Power Plant Development Program for Space Applications

Mark A. Hoberecht

Glenn Research Center, Cleveland, Ohio

Prepared for the
2006 Fuel Cell Seminar
Honolulu, Hawaii, November 13–17, 2007

National Aeronautics and
Space Administration

Glenn Research Center
Cleveland, Ohio 44135

Level of Review: This material has been technically reviewed by technical management.

Available from

NASA Center for Aerospace Information
7115 Standard Drive
Hanover, MD 21076-1320

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161

Available electronically at <http://gltrs.grc.nasa.gov>

NASA's PEM Fuel Cell Power Plant Development Program for Space Applications

Mark A. Hoberecht
National Aeronautics and Space Administration
Glenn Research Center
Cleveland, Ohio 44135

Introduction

Proton-exchange-membrane (PEM) fuel cells were the primary electrical power source on both the Gemini and Apollo missions, and more recently, alkaline fuel cells have powered the Shuttle Orbiter. During the first twenty years of Shuttle operation, PEM fuel cell technology underwent only minor development for space applications, while development for commercial terrestrial applications was initiated and has grown exponentially. However, NASA recognized the advantages that PEM technology promises over existing alkaline fuel cell technology for space applications, and beginning in 2001, embarked on a five-year PEM fuel cell power plant development program. These advantages include enhanced safety, increased robustness, improved modularity, higher power levels, longer life, lower weight, improved reliability and maintainability, higher peak-to-nominal power capability, the ability to operate on lower purity propulsion-grade reactants, reduced ground and mission operations support, and lower recurring costs. NASA's five-year program has been conducted by a three-center NASA team of Glenn Research Center (GRC, lead), Johnson Space Center (JSC), and Kennedy Space Center (KSC). The program was initially aimed at developing PEM fuel cell hardware for a reusable launch vehicle (RLV) application, but more recently has shifted to applications supporting the NASA Exploration Program.

In contrast to the early days of PEM fuel cell technology development when NASA pioneered fuel cell development during the Gemini and Apollo eras, NASA is now able to leverage technology advances from the commercial sector in developing PEM fuel cell technology for space applications. The major differences between commercial terrestrial technology and space technology are that space fuel cells must be able to operate with pure oxygen as the oxidant (as opposed to air) and water removal must take place in a multi-gravity environment (from zero-gravity to several times that of Earth's gravity). These challenges have been the primary focus of NASA's development effort. The first phase of the effort, to develop breadboard hardware in the 1 to 5 kW power range, was conducted by two competing vendors under NASA contract. The second phase of the effort, to develop Engineering Model hardware at the 10 kW power level, was conducted by the winning vendor from the first phase of the effort. Both breadboard power plants and the single engineering model power plant were delivered to NASA for independent testing.

Breadboard Development Effort

Phase I of NASA's five-year program was the development of breadboard power plants by two competing vendors, ElectroChem, Inc. and Teledyne Energy Systems, Inc. This effort, which occurred during the first two years of the program, was concentrated on building power plants of sufficient size to demonstrate the capabilities of the two vendor's technologies. The goal was to deliver power plants at minimum cost in a short period of time, hence off-the-shelf hardware was utilized as much as possible. Table 1 shows a comparison of the design parameters for the two breadboard units.

TABLE 1.—BREADBOARD POWER PLANT COMPARISON

Vendor	ElectroChem	Teledyne
Nominal power, kW	1.0	5.0
Number of cells	45	82
Cell active area, cm ²	232	302
Nominal current density, mA/cm ²	110	270
Peak power capability, peak: nominal	6:1	>6:1
Reactant recirculation approach	Passive (ejectors)	Active (pumps)




Figure 1.—ElectroChem breadboard schematic.




Figure 2.—ElectroChem fuel cell stack.




Figure 3.—Teledyne breadboard schematic.




Figure 4.—Teledyne fuel cell stack.

Figures 1 to 4 show schematic representations of the breadboard power plant units as well as photos of the individual fuel cell stacks within each breadboard unit.

After design and fabrication, the breadboard power plant unit from each vendor was delivered to NASA for independent testing. Following several months of extensive performance testing under several load profiles, Teledyne was selected to participate in the engineering model portion of the program.

Engineering Model Development Effort

Phase II of NASA's five-year program was the development of a single engineering model power plant by Teledyne Energy Systems, Inc. The goal of this effort, which took place during the final three years of the program, was to further advance PEM fuel cell technology at the system level. The fidelity of the engineering model power plant was to more closely resemble space flight hardware than the off-the-shelf commercial hardware utilized in the breadboard power plants. Table 2 summarizes the key engineering model system requirements.

The engineering model power plant as delivered to NASA fully met all of the above program goals, except for a 25 percent excess in power plant weight. Schedule and cost constraints prevented further reductions in balance-of-plant weight surrounding the fuel cell stack, which was the major contributor to the excess. Just as with the breadboard units, at the conclusion of design and fabrication the engineering model unit underwent independent testing by NASA. However, the engineering model testing was more extensive than that of the breadboards. The test regime included routine tests such as polarization curves, a variety of performance tests under multiple load profiles, specialty tests such as rapid start-up and loss-of-coolant tests, and environmental tests such as thermal vacuum and vibration tests. A photograph of the engineering model in NASA GRC's fuel cell test facility is shown in figure 5.

TABLE 2.—ENGINEERING MODEL POWER PLANT KEY REQUIREMENTS

Requirement	Goal
Nominal power, kW	7 to 10
Voltage regulation, V	30 ± 10 percent
Voltage response time, s	<0.2
Operating life, hr	10,000
Operating temperature, °C	60 to 80
Operating pressure, kPa	<690
Power plant weight, kg	<140
Power plant volume, m ³	<0.2




Figure 5.—Teledyne engineering model fuel cell power plant.

Summary

Recognizing the advantages that PEM fuel cell technology promises over existing alkaline fuel cell technology used on the Shuttle Orbiter, NASA is completing a five-year PEM fuel cell power plant development program for future space applications. This effort has been conducted by a three-center NASA team led by Glenn Research Center in Cleveland, Ohio. By leveraging significant advances in commercial PEM fuel cell technology, NASA has successfully adapted terrestrial technology for space applications by addressing the key mission requirements of using pure oxygen as an oxidant and operating in a multi-gravity environment.

Competing vendors developed breadboard units in the 1 to 5 kW power range during the first phase of the program, and a single vendor developed a nominal 10 kW engineering model power plant during the second phase of the program. This engineering model unit underwent a series of performance and environmental tests conducted by NASA to assess its applicability for future space missions. Although not yet of flight hardware fidelity, the PEM fuel cell engineering model power plant was very similar in terms of form, fit, and function to the alkaline fuel cell power plant used on the Shuttle Orbiter. With continued advances in fuel cell stack and balance-of-plant ancillary hardware, PEM fuel cell technology will be ready to meet the electrical power needs of future space missions.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 01-01-2008			2. REPORT TYPE Technical Memorandum		3. DATES COVERED (From - To)
4. TITLE AND SUBTITLE NASA's PEM Fuel Cell Power Plant Development Program for Space Applications			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Hoberecht, Mark, A.			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER WBS 083229.04.14.01.01.05		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration John H. Glenn Research Center at Lewis Field Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER E-16163		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORS ACRONYM(S) NASA		
			11. SPONSORING/MONITORING REPORT NUMBER NASA/TM-2008-214991		
12. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Categories: 15, 16, 20, and 44 Available electronically at http://gltrs.grc.nasa.gov This publication is available from the NASA Center for AeroSpace Information, 301-621-0390					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT A three-center NASA team led by the Glenn Research Center in Cleveland, Ohio is completing a five-year PEM fuel cell power plant development program for future space applications. The focus of the program has been to adapt commercial PEM fuel cell technology for space applications by addressing the key mission requirements of using pure oxygen as an oxidant and operating in a multi-gravity environment. Competing vendors developed breadboard units in the 1 to 5 kW power range during the first phase of the program, and a single vendor developed a nominal 10-kW engineering model power plant during the second phase of the program. Successful performance and environmental tests conducted by NASA established confidence that PEM fuel cell technology will be ready to meet the electrical power needs of future space missions.					
15. SUBJECT TERMS Fuel cells; Fuel cell power plants; Manned space flight; Reusable launch vehicles					
16. SECURITY CLASSIFICATION OF:		17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 10	19a. NAME OF RESPONSIBLE PERSON STI Help Desk (email: help@sti.nasa.gov)	
a. REPORT U	b. ABSTRACT U			c. THIS PAGE U	19b. TELEPHONE NUMBER (include area code) 301-621-0390

